FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery Ref. No. MSDS-2022-06 Effective Date: 1-June-2022 Page 1 / 6

This product is a consumer product which is used in a hermetically sealed state. So, it is not an object of the SDS system. This document is provided as technical information only. The information and recommendations set forth are made in good faith and are believed to be accurate as of the date of preparation. HW makes no warranty expressed or implied.

MATERIAL SAFETY DATA SHEET

Section 1: Chemical product and company identification

Name of Product : Coin Type Manganese Dioxide Lithium Batteries

Product models : CR1025 CR1216 CR1220 CR1225 CR1616 CR1620 CR1632 CR2016

CR2025 CR2032 CR2320 CR2330 CR2335 CR2354 CR2430 CR2450

CR2477 CR3032

Name of Company : Tiger Head Hi-Watt Battery (HW) Co., Ltd.

Address : FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE

ROAD TSIM SHA TSUI EAST KLN HK.

Department: : Lithium battery development & engineering department

Telephone number : TEL:+852 2348 0111 EFAX: +852 2573 7145

Date of preparation : 1-June-2022

Section 2: Hazards identification

This contains lithium, organic solvent, and other combustible materials. For this reason, improper handling of the battery could lead to distortion, leakage*, overheating, explosion of fire and cause human injury or equipment trouble. Please strictly observe safety instruction.

(*Leakage is defined as an unintended escape of liquid from a battery.)

Section 3: Composition/information of ingredients

| Material | CAS No. | Content (%) | |
|---------------------|-----------------------|-------------|--|
| Manganese Dioxide | 1313-13-9 | 16 - 37 | |
| Lithium metal | 7439-93-2 | 1 - 3 | |
| 1,2-Dimethoxyethane | 110-71-4 | 2.6 - 5.8 | |
| Lithium perchlorate | 7791-03-9 | 0.6 - 1.3 | |
| Propylene Carbonate | 108-32-7 | 4.3 - 8 | |
| Graphite | 7782-42-5 , 1333-86-4 | 1.8 - 5.5 | |
| Steel | 7439-86-6 , 7440-47-3 | 30 - 85 | |
| Polypropylene | 9003-07-0 | 0.5 - 10 | |

FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery Ref. No. MSDS-2022-06 Effective Date: 1-June-2022 Page 2 / 6

Lithium content per cell model

| Model | Weight of battery (in g) | Lithium content (in g) | Model | Weight of battery (in g) | Lithium content (in g) |
|--------|--------------------------|------------------------|--------|--------------------------|------------------------|
| CR1025 | 0.6 | 0.01 | CR2320 | 3.0 | 0.043 |
| CR1216 | 0.7 | 0.007 | CR2325 | 3.3 | 0.052 |
| CR1220 | 0.8 | 0.012 | CR2330 | 4.0 | 0.078 |
| CR1225 | 0.9 | 0.014 | CR2335 | 4.3 | 0.08 |
| CR1616 | 1.1 | 0.014 | CR2354 | 6.9 | 0.15 |
| CR1620 | 1.4 | 0.023 | CR2430 | 4.6 | 0.086 |
| CR1632 | 2.0 | 0.033 | CR2450 | 6.9 | 0.165 |
| CR2016 | 2.0 | 0.024 | CR2477 | 10.5 | 0.3 |
| CR2025 | 2.7 | 0.052 | CR3032 | 6.8 | 0.133 |
| CR2032 | 3.2 | 0.064 | | | |

Section 4: First aid measures

None unless internal materials exposure. If contents are leaked out, read the following instructions.

Inhalation: Fumes can cause respiratory irritation. Remove to fresh air and consult a physician.

Skin: Immediately flush skin plenty of water. If itch or irritation by chemical bum persists, consult a

physician.

Eyes: Immediately flush eye with plenty of water for at least 15 minutes. Consult a physician

immediately

Ingestion: If swallowing a battery, consult a physician immediately. If contents come into mouth,

immediately rinse by plenty of water and consult a physician.

Section 5: Firefighting measures

Extinguishing agent: Extinguisher of alkaline metal fire is effective. Plenty of cold water is also

effective to cool the surrounding area and control the spread fire. But hydrogen gas may evolve by the reaction of water and lithium and it can form an explosive mixture. Therefore, in the case that lots of lithium batteries are burning in a

confined space, use a smothering agent.

Firefighting procedure: Use self-contained breathing apparatus and full protective gear not to inhale

harmful gas.

FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery Ref. No. MSDS-2022-06 Effective Date: 1-June-2022 Page 3 / 6

Section 6: Accidental release measures

Accidental Releases: Do not breathe vapors or touch liquid with bare hands (see section 4).

Waste Disposal Methods: Evacuate area. If possible, a trained person should attempt to stop or contain the leak by neutralizing spill with soda lime or baking soda. A NIOSH Approved Acid Gas Filter Mask or Self-Contained Breathing Apparatus should be worn. Seal leaking battery and soda lime or baking soda in a plastic bag and dispose of as hazardous waste.

Other: Follow North American Emergency Response Guide (NAERG)#138 for cells involved in an accident, cells that have vented, or have exploded.

Section 7: Handling and storage

1) Handling

Never swallow.

Never reverse the positive and negative terminals when mounting.

Never short-circuit the battery.

Never heat.

Never expose to open flame.

Never disassemble.

Never weld the terminal or wire to the body of the battery directly.

Never touch the liquid leaked out of battery.

Never bring fire close to battery liquid.

Never keep in touch with battery.

2) Storage

Never let the battery contact with water.

Never store the battery in hot and high humid place.

Section 8: Exposure controls and personal protection

| Respiratory Protection | | N/A |
|---------------------------|---------------|-----|
| Ventilation | Local Exhaust | N/A |
| | Mechanical | N/A |
| | Special | N/A |
| | Other | N/A |
| Eye Protection | | N/A |
| Protective Gloves | | N/A |
| Other protective clothing | | N/A |

FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery Page 4 / 6

Ref. No. MSDS-2022-06 Effective Date: 1-June-2022

Section 9: Physical and chemical properties

Appearance : Coin shape. Contents are sealed in stainless steel vessel

Nominal Voltage : 3 V

PH : Not applicable because the article is not soluble in water

Boiling point/boiling range : Not applicable for the article
Melting point : Not applicable for the article
Decomposition Temperature : Not applicable for the article
Flash point : Not applicable for the article

Section 10: Stability and reactivity

Stability : Stable Incompatibility : Water

Hazardous polymerization : Will not occur Condition to avoid : See section 7 Hazardous decomposition or byproducts : Hydrogen

Section 11: Toxicological information

Acute Toxicity:

1,2-Dimethoxyethane:

LC₅₀ (Inhalation): N/A

LD₅₀: N/A

Eye Effects: Corrosive Skin Effects: Corrosive

Section 12: Ecological information

Aquatic Toxicity: Do not let internal components enter marine environments. Avoid releases into waterways, waste water, or groundwater.

Section 13: Disposal considerations

The battery disposal may be regulated by national or local government regulation. Please follow the instructions of proper regulation. As electric capacity is left in a discarded battery and it comes into contact with other metals, it could lead to distortion, leakage, overheating, or explosion, so make sure to cover the (+) and (-) terminals with friction tape or some other insulator before disposal.

FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery Page 5 / 6

Ref. No. MSDS-2022-06 Effective Date: 1-June-2022

Section 14: Transport information

In general, all cells/batteries being transported by ship, aircraft or railway, must be packaged in a safe and responsible manner. Do not leave them in high temperature or in high condensation. Battery cartons should be handled with care. Rough handling may result in batteries being short circuited or damaged.

Lithium metal cells and batteries are subject to the following transport rules. All HW lithium cells/batteries meet the requirements of the special provisions listed below:

| Regulatory Body | Special Provisions |
|-----------------|---|
| ADR | 188, 230, 310, 636, 656 |
| IMDG | 188, 230, 310, 957 |
| UN | UN 3090, UN 3091 |
| US DOT | 29, A54, A100, A101 |
| IATA, ICAO | Dangerous Goods Regulation (Packaging Instructions 968 – 970) |

Ocean Transportation

All Chener lithium coin cells/batteries can be transported as Non-Dangerous Goods by vessel as these articles satisfy with SP188 of IMO-IMDG Code.

Air Transportation

Chener Lithium cells/batteries can meet the requirement of IATA Dangerous Goods Regulations 60th Edition of 2019, Packing Instruction PI 968 - 970.

Proper Shipping Name : Lithium Metal Batteries

UN Number : UN3090

(When cell/batteries contained in equipment / packed with equipment,

it is UN3091)

Hazard Classification : Class 9 (Miscellaneous)

FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM SHA TSUI EAST KLN HK.

Tel: (852) 23480111 Fax: (852) 25737145

Lithium Metal Battery

Page 6 / 6

Ref. No. MSDS-2022-06 Effective Date: 1-June-2022

Section 14: Transport information (... continued)

| IATA DGR 59 th Edition, Packing Instruction (PI) | Packing Instruction (PI) brief description |
|--|--|
| PI 968 Section IA | Cells, Cargo Aircraft only; net quantity per package Max. 35kg |
| PI 968 Section IB | Cells, Cargo Aircraft only; net quantity per package Max. 2.5kg |
| PI 968 Section II | Cells, Cargo Aircraft only, not more than one package in any single consignment; net quantity per package Max. 2.5kg |
| PI 969 Section II | Cells packed with equipment |
| PI 970 Section II | Cells contained in equipment, button cell batteries |

- 1. for cells, the lithium content cannot be more than 0.3g for PI 968 Section II, not more than 1.0g for PI 968 Section IB, and can be more than 1.0g for PI 968 Section IA.
- 2. each cell is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria, PartIII, sub-section 38.3.
- 3. each cell is manufactured in good qualification factory.

Section 15: Regulatory information

Major applicable regulations for transportation are listed below:

- Technical Instructions for the Safety Transport of Dangerous Goods by Air, 2018-2019 Edition
- IATA Dangerous Goods Regulations 60th Edition (IATA DGR)
- IMO International Maritime Dangerous Goods Code 2016 Edition (IMO, IMDG Code)

Section 16: Other information

If you want further information, please contact:

Ms. May Lai

ADD:FLAT RM 705B 7/F HARBOUR CRYSTAL CENTRE 100 GRANVILLE ROAD TSIM

SHA TSUI EAST KLN HK.