

DATA SHEET

Alkaline

Order code	Manufacturer code	Description
18-3250	MN2400B	PK 4 MN2400B AAA ALKALINE BATT
18-3262	MN1500BK12	PK12 MN1500B AA ALKALINE BATT.
18-3265	MN1400B	PK 2 MN1400B C ALKALINE BATT.

Alkaline	Page 1 of 5
The enclosed information is believed to be correct, Information may change 'without notice' due to	Revision A
product improvement. Users should ensure that the product is suitable for their use. E. & O. E.	04/07/2003

Sales: 01206 751166 Technical: 01206 835555 Fax: 01206 7551188 Sales@rapidelec.co.uk Tech@rapidelec.co.uk www.rapidelectronics.co.uk



Page 1 of 4 MATERIAL SAFETY DATA SHEET (according to 91/155/EEC, as amended)

Product: DURACELL ALKALINE BATTERIES (COPPERTOP, ULTRA, and PLUS) **GMEL # 2002.6E**

Date / revised: 06/11/2003 Revision: 6

1. Substance/preparation and company name

Duracell Alkaline Batteries: Alkaline Manganese Dioxide Cells - MN1300 (D); MN1400 (C); MN1500 (AA) MN2400 (AAA); MX1300

(D); MX1400 (C); MX1500 (AA); MX2400 (AAA); MX2500 (AAAA); MX1604 (9V); MN908 (Lantern 6V); MN918 (Lantern 4.5V); MN1604 (9V); MN9100 (N), MN1203 (4.5V); 5K69 (Flatpack); 7K67 (Flatpack) (J)

and batteries comprised of these cells.

Company:	Country contact numbers:				
Duracell Batteries Ltd.	Austria:	02236 645240	Netherlands:	070 4131 800	
c/o Gillette U.K. Ltd.	Belgium:	02 711 9102	Norway:	022 72 8810	
Great West Road	Denmark:	33 26 9100	Portugal:	011 7210950	
Isleworth, Middlesex	Finland:	09 452 8737	Spain:	091 387 9600	
TW7 5NP	France:	01 47 48 70 00	Sweden:	08 6292700	
UK	Germany:	02 21 59670	Switzerland:	017 55 62 42	
	Italy:	02 66 7811	United Kingdom:	0181 560 1234	

2. Composition/information on ingredients*

Chemical nature:	Wt. %	CAS No.	EEC No.	Index No.	Classification
Manganese Dioxide	35-40	1313-13-9	215-202-6	025-001-00-3	Xn, R20/22
Zinc	10-25	7440-66-6	231-175-3	030-002-00-7	F; R-15; R-17
Potassium Hydroxide (35%)	5-10	1310-58-3	215-181-3	019-002-00-8	C; R35

^{*}Please note: Some Duracell alkaline batteries contain the Duracell Power CheckTM battery energy gauge which is a small conductive strip located underneath the PVC battery label that indicates the amount of charge in the battery. It is composed of minute quantities of conductive materials. Due to the small quantity of materials and their solid form, a health or environmental risk is unlikely.

3. Possible hazards

Critical hazards to man: If battery leaking, exposure to caustic ingredients may occur.

Critical hazards to the environment: Not applicable

Other Information: Keep batteries away from small children.

4. First aid measures

General advice: These chemicals and metals are contained in a sealed can. For consumer use, adequate hazard warnings are included on both the package and on the battery. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically. physically, or electrically abused. Contains concentrated (35%) potassium hydroxide, which is caustic. Anticipated potential leakage of potassium hydroxide is 2 to 20 ml, depending on battery size. A similar amount of zinc/zinc oxide may also leak.

If inhaled: Respiratory and eye irritation may occur if fumes are released due to heat or an abundance of leaking batteries. Remove to fresh air. Contact physician if irritation persists.

On skin contact: Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. Irrigate exposed skin with copious amounts of clear, tepid water for at least 15 minutes. If irritation, injury or pain persists, consult a physician.

On contact with eyes: Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. It battery is leaking and material contacts eyes, flush with copious amounts of clear, tepid water for 30 minutes. Contact physician at once.

IMATERIAL SAFETY DATA SHEET (according to 91/155/EEC, as amended)

Product: DURACELL ALKALINE BATTERIES (COPPERTOP, ULTRA, and PLUS) **GMEL # 2002.6E**

Date / revised: 06/11/2003 Revision: 6

4. First aid measures (continued)

On ingestion: Not anticipated due to size of batteries; choking may occur with the smaller AAA battery.

Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. Rinse the mouth and surrounding area with clear, tepid water for at least 15 minutes. Consult a physician immediately for treatment and to rule out involvement of the esophagus and other

tissues.

Notes to Physician: The primary acutely toxic ingredient is concentrated (35%) potassium hydroxide.

Anticipated potential leakage of potassium hydroxide is 2 to 20 ml, depending on battery size. This MSDS does not include or address the small button cell batteries, which can

be digested.

5. Fire fighting measures

Suitable extinguishing media: As appropriate for adjacent fire.

Special protective equipment: In fires involving large quantities of product, use self-contained breathing

apparatus and full protective clothing.

Further information: Hazardous decomposition products may be produced. (Sec. 10).

6. Accidental release measures

Personal precautions: Notify safety personnel of large spills. Caustic potassium hydroxide may be released

from leaking or ruptured batteries. Avoid eye or skin contact and inhalation of

vapours. Increase ventilation. Clean up personnel should wear appropriate protective

gear.

Environmental precautions: Not applicable Methods for cleaning up: Not applicable

7. Handling and storage

Handling

Avoid mechanical or electrical abuse. DO NOT short or install incorrectly. Batteries may explode, pyrolize or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Do not mix battery systems, such as alkaline and zinc carbon, in the same equipment. Replace all batteries in equipment at the same time. Do not carry batteries loose in pocket or bag. Do not remove battery tester or battery label.

Storage

Store at room temperature.

8. Exposure controls and personal protection

8-Hour TWAs: Manganese Dioxide (as Mn) - 5 mg/m³ (U.K.), (Ceiling)(OSHA);

0.2 mg/m³ (ACGIH/Duracell)

Potassium Hydroxide - 2 mg/m³ (Ceiling) (ACGIH); 2 mg/m³ (STEL) (U.K.)

Graphite (all kinds except fibrous) - 2 mg/m³ (ACGIH); (synthetic) - 15 mg/m³ (total, OSHA);

5 mg/m³ (respirable, U.K./OSHA)

These levels are not anticipated under normal consumer use conditions.

MATERIAL SAFETY DATA SHEET (according to 91/155/EEC, as amended)

Product: DURACELL ALKALINE BATTERIES (COPPERTOP, ULTRA, and PLUS) GMEL # 2002.6E

Date / revised: 06/11/2003 Revision: 6

8. Exposure controls and personal protection (continued)

Personal protective equipment

Respiratory equipment: None required under normal use conditions.

Hand protection: None required under normal use conditions. Use neoprene, rubber or nitrile gloves

when handling leaking batteries.

Eye protection: None required under normal use conditions. Wear safety glasses when handling leaking

batteries.

General safety and hygiene measures: Use only as directed.

9. Physical and chemical properties

Form and Colour: Copper top battery. Contents dark in colour.

Odour: Not applicable

Change in physical state

Melting point/melting range: Not available **Boiling point/boiling range**: Not available

Flash point: Not applicable

Explosion limits: Not available

Ignition temperature: Not available

Vapour pressure: Not available

Specific Gravity: Not applicable

% Volatiles: Not available

Solubility in water: Not applicable

Solubility in other solvents: Not applicable

pH value: Not available

Octanol/water partition coefficient (log POW): Not available

Viscosity: Not available

10. Stability and reactivity

Thermal decomposition: Batteries may burst and release hazardous decomposition products when exposed

to a fire situation.

Substance(s) to avoid: Strong oxidisers

Hazardous reactions: Contents incompatible with strong oxidising agents.

Hazardous decomposition products: Thermal degradation may produce hazardous fumes of zinc and

manganese; hydrogen gas; caustic vapours of potassium hydroxide

and other toxic by-products.

MATERIAL SAFETY DATA SHEET (according to 91/155/EEC, as amended) Page 4 of

Product: DURACELL ALKALINE BATTERIES (COPPERTOP, ULTRA, and PLUS) GMEL # 2002.6E

,

Date / revised: 06/11/2003 Revision: 6

11. Toxicological information

Toxicity information is available on the battery ingredients noted in Section 2, but, generally not applicable to intact batteries.

Chronic Health Effects: Not applicable to intact batteries.

12. Ecological information

Not available

13. Disposal considerations

Product: Dispose in accordance with appropriate regulations. If in doubt, contact your national Gillette office

for information. Do not incinerate, since batteries may explode at excessive temperatures.

14. Transport information

UN Number: None IMO Classification: None ADR Classification: None IATA Classification: None

These batteries are not regulated by U. S. DOT or international agencies as hazardous materials or dangerous goods when shipped. A shipping name of 'Alkaline Batteries - Non-hazardous' may be used on all domestic and international bills of lading.

15. Regulatory information

EC Labeling: None Risk Phrases: None Safety Phrases: None

Labeling is not required because batteries are classified as "articles" under the Dangerous Preparations Directive and as such are exempt from the requirements of the Directive.

16. Other information:

Preparation of MSDS:

Prepared by: Gillette Environment, Health and Safety Phone Number: Date: 06/11/2003

37 A Street 781.292.8151 **Revision:** 6

Needham, MA 02492 USA Replaces: 2007.5E

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.