



Glu Pens

WATER BOURNE ADHESIVE

Date: 27 October 2015

Fact Sheet No.: TDS00380

YOUR SMART ADVANTAGES

- Acid, lignin and solvent free
- 5mm glue lines
- Repositionable bonds

USES

Bostik Glu Pens are white, water-borne liquid adhesive, supplied in the form of a glue pen to ensure clean, easy and accurate application. Bostik Glu Pens carries a CE Mark - it has been designed to meet and exceed the stringent EC child safety legislation.

May be used for bonding paper, card and fabric and has the added convenience of being repositionable, making it ideal for creating sticky notes. Ideal for a variety of applications around the home, school and office and is solvent-free.

PRODUCT CHARACTERISTICS

Colour	Milky white
Form	Mobile liquid
Specific Gravity	1.1 approx.
Composition	Polyvinyl alcohol solution
Solids Content	10%
Product Code	30800973 10g Glu Pen blister x 6 30813322 36ml Jumbo Glu Pen blister x 6
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Service Temperature	-20°C to +45°C
Coverage	Up to 25 metres of 5mm bond per coat
Drying Times	Less than 1 minute

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Glu Pens refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure the surfaces to which the adhesive is to be applied are clean and dry.
2. Remove the cap and hold the pen at a right angle to the surface.
3. Gently push the nib to activate flow. Once glue begins to flow, the pen is ready for use.

APPLICATION

4. To apply simply draw the pen across one of the surfaces to be bonded to leave a line of glue, (for heavier or more absorbent surfaces, apply the glue to both surfaces).
5. To make sticky, repositionable notes, allow the glue surface to become "touch-dry", (surface may be touched without any transfer of glue to the fingers).
6. Remove any excess glue from the body of the pen and replace the cap firmly after use.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

CLEANING

7. Remove excess adhesive with a damp cloth.
8. Adhesive on clothing may be removed with water, before it dries.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Glu Pens, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.