according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Floor Paint

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Everbuild - A Sika Company

Site 41

Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

: everbuild.sds@uk.sika.com E-mail address

1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - repeated exposure, Category 1, Central nervous

system

H372: Causes damage to organs through pro-

longed or repeated exposure if inhaled.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word Danger

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint





Dispose of contents/container in accord-

ance with local regulation.



Hazard statements :	H226 H372	Flammable liquid and vapour. Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements :	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	Prevention:	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
	Response:	
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

• 919-446-0 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-

25%)

Additional Labelling:

EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

Disposal: P501

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,	Flam. Liq.3; H226	>= 10 - < 20
aromatics (2-25%)	STOT SE3; H336	
	STOT RE1; H372	
919-446-0	Asp. Tox.1; H304	
265-185-4	Aquatic Chronic2;	
01-2119458049-33-XXXX [corresponding group CAS 64742-82-1]	H411	

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint



2-butanone oxime
96-29-7
202-496-6
01-2119539477-28-XXXX

Carc.2; H351
Acute Tox.4; H312
Eye Dam.1; H318
Skin Sens.1; H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

BUILDING TRUST

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

Risks : No known significant effects or hazards.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint



Print Date 15.08.2017

Revision Date 14.08.2017 Version 4.0

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint







Version 4.0 Print Date 15.08.2017

of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against

fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint



Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

BUILDING TRUST

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : various

Odour : characteristic

Odour Threshold : No data available

Flash point : > 40 °C

Autoignition temperature : 235 °C

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : 0,6 %(V)

Upper explosion limit (Vol-%) : 6.5 %(V)

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : No data available

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : 3,9997 hPa

Density : ca.1 g/cm3

at 20 °C

Water solubility : No data available

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint

Revision Date 14.08.2017 Version 4.0 Print Date 15.08.2017

BUILDING TRUST

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic

: No data available

Viscosity, kinematic

: >30 mm2/s at 40 °C

at 40

Relative vapour density

: No data available

Evaporation rate

: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

2-butanone oxime:

Acute oral toxicity : LD50 Oral (Rat): 3.680 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Country GB 100000011670

7 / 12

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint

Revision Date 14.08.2017 Version 4.0





Print Date 15.08.2017

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Country GB 100000011670

8 / 12

according to Regulation (EC) No. 1907/2006

Everbuild Floor PaintRevision Date 14.08.2017







Version 4.0

Print Date 15.08.2017

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1263

14.2 UN proper shipping name : PAINT RELATED MATERIAL

14.3 Transport hazard : 3

class(es)

14.4 Packing group: IIIClassification Code: F1Labels: 3Tunnel restriction code: (D/E)14.5 Environmental hazards: no

IATA

14.1 UN number : 1263

14.2 UN proper shipping name : Paint related material

14.3 Transport hazard : 3

class(es)

14.4 Packing group: IIILabels: 314.5 Environmental hazards: no

IMDG

14.1 UN number : 1263

14.2 UN proper shipping name : PAINT RELATED MATERIAL

14.3 Class : 3 **14.4 Packing group** : ||||

Country GB 100000011670

9 / 12

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint



3 Lahels EmS Number 1 F-E EmS Number 2 S-E 14.5 Marine pollutant no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

BUILDING TRUST

(=> 0.1 %).

: Not applicable

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-

jor-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

FLAMMABLE LIQUIDS P₅c 5.000 t 50.000 t

VOC-CH (VOCV) : 10 % VOC-EU (solvent) : 10 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations


(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint Revision Date 14.08.2017







Version 4.0 Print Date 15.08.2017

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Harmful in contact with skin. H312

H317 May cause an allergic skin reaction. Causes serious eye damage. H318 May cause drowsiness or dizziness. H336 H351 Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure if H372

inhaled.

Toxic to aquatic life with long lasting effects. H411

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Chronic aquatic toxicity Aspiration hazard Asp. Tox. Carc. Carcinogenicity Eve Dam. Serious eye damage Flammable liquids Flam. Liq. Skin Sens. Skin sensitisation

Specific target organ toxicity - repeated exposure STOT RE STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

> Dangereuses par Route Chemical Abstracts Service

CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

Median lethal dosis (the amount of a material, given all at once, which LD50

causes the death of 50% (one half) of a group of test animals)

Median lethal concentration (concentrations of the chemical in air that LC50

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL** Persistent, bioaccumulative and toxic **PBT** Predicted no effect concentration **PNEC**

Regulation (EC) No 1907/2006 of the European Parliament and of the **REACH**

> Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a


European Chemicals Agency

Substances of Very High Concern **SVHC**

Very persistent and very bioaccumulative vPvB

according to Regulation (EC) No. 1907/2006

Everbuild Floor Paint









Version 4.0

Print Date 15.08.2017

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!