

## SAFETY DATA SHEET

### Acrylic Protective Lacquer

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Acrylic Protective Lacquer

**Product number** APL-b, EAPL15ML, EAPL500ML, EAPL05L, ZE

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Appliance protection.

**Uses advised against** No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier**

ELECTROLUBE. A division of HK WENTWORTH LTD  
 ASHBY PARK, COALFIELD WAY,  
 ASHBY DE LA ZOUCH, LEICESTERSHIRE LE65 1JR  
 UNITED KINGDOM  
 +44 (0)1530 419600  
 +44 (0)1530 416640  
 info@hkw.co.uk

##### 1.4. Emergency telephone number

**Emergency telephone** +44 1865 407333

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336  
 STOT RE 2 - H373

**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Pictogram



**Signal word**

**Danger**

## Acrylic Protective Lacquer

<b>Hazard statements</b>	<p>H225 Highly flammable liquid and vapour.  H315 Causes skin irritation.  H317 May cause an allergic skin reaction.  H319 Causes serious eye irritation.  H336 May cause drowsiness or dizziness.  H361d Suspected of damaging the unborn child.  H373 May cause damage to organs through prolonged or repeated exposure.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P260 Do not breathe vapour/ spray.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  P302+P352 IF ON SKIN: Wash with plenty of water.  P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Contains</b>	Toluene, butanone, 2-octyl-2H-isothiazol-3-one
<b>Supplementary precautionary statements</b>	<p>P201 Obtain special instructions before use.  P202 Do not handle until all safety precautions have been read and understood.  P240 Ground/ bond container and receiving equipment.  P241 Use explosion-proof electrical equipment.  P242 Use only non-sparking tools.  P243 Take precautionary measures against static discharge.  P261 Avoid breathing vapour/ spray.  P264 Wash contaminated skin thoroughly after handling.  P271 Use only outdoors or in a well-ventilated area.  P272 Contaminated work clothing should not be allowed out of the workplace.  P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P308+P313 IF exposed or concerned: Get medical advice/ attention.  P312 Call a POISON CENTER/ doctor if you feel unwell.  P314 Get medical advice/ attention if you feel unwell.  P321 Specific treatment (see medical advice on this label).  P332+P313 If skin irritation occurs: Get medical advice/ attention.  P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  P337+P313 If eye irritation persists: Get medical advice/ attention.  P362+P364 Take off contaminated clothing and wash it before reuse.  P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  P403+P233 Store in a well-ventilated place. Keep container tightly closed.  P403+P235 Store in a well-ventilated place. Keep cool.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

## Acrylic Protective Lacquer

<b>Toluene</b>		<b>30-60%</b>
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-XXXX
<b>Classification</b>		
Flam. Liq. 2 - H225		
Skin Irrit. 2 - H315		
Repr. 2 - H361d		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
<b>butanone</b>		<b>10-30%</b>
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX
<b>Classification</b>		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
<b>2-octyl-2H-isothiazol-3-one</b>		<b>&lt;1%</b>
CAS number: 26530-20-1	EC number: 247-761-7	
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b>		
Acute Tox. 4 - H302		
Acute Tox. 3 - H311		
Acute Tox. 3 - H331		
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### **General information**

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

##### **Inhalation**

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway.

Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

## Acrylic Protective Lacquer

<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
<b>Ingestion</b>	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
<b>Skin contact</b>	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
-----------------------------	--

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## Acrylic Protective Lacquer

### 5.3. Advice for firefighters

#### **Protective actions during firefighting**

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

#### **Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

### 6.2. Environmental precautions

#### **Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

### 6.3. Methods and material for containment and cleaning up

#### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 6.4. Reference to other sections

#### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## Acrylic Protective Lacquer

### Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapours may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Suspected of damaging the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

### Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Eliminate all sources of ignition. Take precautionary measures against static discharges. Earth container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

#### Storage class

Flammable liquid storage.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Toluene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

##### butanone

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### 8.2. Exposure controls

#### Protective equipment



## Acrylic Protective Lacquer

<b>Appropriate engineering controls</b>	Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.
<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Light (or pale).
<b>Odour</b>	Organic solvents.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.

## Acrylic Protective Lacquer

<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	-7°C CC (Closed cup).
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Bulk density</b>	0.91 kg/l
<b>Solubility(ies)</b>	Not available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	300-350 mPa s @ 20°C
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

##### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

##### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** The following materials may react strongly with the product: Oxidising agents.

##### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.

##### 10.5. Incompatible materials

**Materials to avoid** Oxidising materials. Acids - oxidising.

##### 10.6. Hazardous decomposition products



## Acrylic Protective Lacquer

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Skin corrosion/irritation

**Animal data** Irritating.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

##### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

##### Skin sensitisation

**Skin sensitisation** May cause skin sensitisation or allergic reactions in sensitive individuals.

##### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

##### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

##### IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

##### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development**

Suspected of damaging the unborn child.

##### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

**Target organs**

Central nervous system

##### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

##### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

##### **General information**

Avoid contact during pregnancy/while nursing. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

##### **Inhalation**

A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

## Acrylic Protective Lacquer

<b>Ingestion</b>	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
<b>Skin contact</b>	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.
<b>Route of entry</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target organs</b>	Central nervous system
<b>Medical considerations</b>	Skin disorders and allergies.

### Toluene

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> 8390 mg/kg, Dermal, Rabbit

#### Carcinogenicity

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### 2-octyl-2H-isothiazol-3-one

#### Acute toxicity - oral

**ATE oral (mg/kg)** 500.0

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 300.0

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 700.0

**ATE inhalation (vapours mg/l)** 3.0

**ATE inhalation (dusts/mists mg/l)** 0.5

## SECTION 12: Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met.

### 2-octyl-2H-isothiazol-3-one

#### Acute aquatic toxicity

**LE(C)<sub>50</sub>** 0.1 < L(E)C<sub>50</sub> ≤ 1

**M factor (Acute)** 1

#### Chronic aquatic toxicity

**M factor (Chronic)** 1

### 12.2. Persistence and degradability

## Acrylic Protective Lacquer

**Persistence and degradability** The degradability of the product is not known.

### Toluene

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### Toluene

**Bioaccumulative potential** log Pow: 2.65,

### 12.4. Mobility in soil

**Mobility** No data available.

### Toluene

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

### Toluene

**Results of PBT and vPvB assessment** No data available.

### 12.6. Other adverse effects

**Other adverse effects** None known.

### Toluene

**Other adverse effects** Not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **General information**

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

## Acrylic Protective Lacquer

### Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Vapour from residual product may create a highly flammable or explosive atmosphere inside the container. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not cut or weld used containers unless they have been thoroughly cleaned internally.

### SECTION 14: Transport information

#### General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

#### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

#### 14.5. Environmental hazards

## Acrylic Protective Lacquer

### Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**EmS** F-E, S-E

**ADR transport category** 2

**Emergency Action Code** •3YE

**Hazard Identification Number (ADR/RID)** 33

**Tunnel restriction code** (D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** Health and Safety at Work etc. Act 1974 (as amended).  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].  
EH40/2005 Workplace exposure limits.

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 2015/830 of 28 May 2015.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

##### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

### SECTION 16: Other information

## Acrylic Protective Lacquer

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.</p> <p>LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC<sub>50</sub>: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
<b>Classification abbreviations and acronyms</b>	<p>Flam. Liq. = Flammable liquid</p> <p>Eye Irrit. = Eye irritation</p> <p>Repr. = Reproductive toxicity</p> <p>Skin Irrit. = Skin irritation</p> <p>Skin Sens. = Skin sensitisation</p> <p>STOT RE = Specific target organ toxicity-repeated exposure</p> <p>STOT SE = Specific target organ toxicity-single exposure</p>
<b>Classification procedures according to Regulation (EC) 1272/2008</b>	<p>STOT RE 2 - H373: STOT SE 3 - H336: Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: Repr. 2 - H361d: : Calculation method. Flam. Liq. 2 - H225: : Expert judgement.</p>
<b>Training advice</b>	<p>Read and follow manufacturer's recommendations. Only trained personnel should use this material.</p>
<b>Issued by</b>	Toni Ashford
<b>Revision date</b>	18/01/2017
<b>Revision</b>	0
<b>SDS number</b>	835
<b>Hazard statements in full</b>	<p>H225 Highly flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H311 Toxic in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H331 Toxic if inhaled.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.