

P18 EVERBUILD GAS LEAK DETECTOR

Page: 1

Compilation date: 18/11/14

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: P18 EVERBUILD GAS LEAK DETECTOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	EVERBUILD BUILDING PRODUCTS LTD
	SITE 41, KNOWSTHORPE WAY
	CROSS GREEN INDUSTRIAL ESTATE
	LEEDS
	WEST YORKSHIRE
	LS9OSW
	ENGLAND
Tel:	0044 113 240 3456
Fax:	0044 113 240 0024
Email:	sds@everbuild.co.uk
ncy telephone num	ber

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319

Classification under CHIP: This product has no classification under CHIP.

2.2. Label elements

Label elements under CLP:

Hazard statements: H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements:	P264: Wash hands thoroughly after handling.
	P501: Dispose of contents/container to in accordance with local regulations.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}\text{C}.$
	P261: Avoid breathing vapours.

P18 EVERBUILD GAS LEAK DETECTOR

Page: 2

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P251: Pressurized container: Do not pierce or burn, even after use.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM LAROYL SARCOSINATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
205-281-5	137-16-6	Xi: R38	-	1-10%

COCONUT DIETHANOLAMIDE

271-657-0	68603-42-9	Xi: R38; Xi: R41	Skin Irrit. 2: H315; Eye Dam. 1: H318;	1-10%
			Aquatic Chronic 2: H411	

SODIUM NITRITE

231-555-9	7632-00-0	O: R8; T: R25; N: R50	Ox. Sol. 3: H272; Acute Tox. 3: H301;	<1%
			Aquatic Acute 1: H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

P18 EVERBUILD GAS LEAK DETECTOR

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes. Cool containers at risk with water spray jet.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Contact with skin and eyes can cause freeze

burns

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

P18 EVERBUILD GAS LEAK DETECTOR

8.2. Exposure controls

 Engineering measures:
 Ensure there is sufficient ventilation of the area.

 Respiratory protection:
 Self-contained breathing apparatus must be available in case of emergency.

 Hand protection:
 Protective gloves.

 Eye protection:
 Safety glasses. Ensure eye bath is to hand.

 Skin protection:
 Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquified gas

Colour: Colourless

Odour: Barely perceptible odour

Solubility in water: Slightly soluble

Boiling point/range°C: 100

Relative density: 1.02

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

P18 EVERBUILD GAS LEAK DETECTOR

Page: 5

Hazardous ingredients:

SODIUM NITRITE

ORL	MUS	LD50	175	mg/kg
ORL	RAT	LD50	180	mg/kg
SCU	RAT	LD50	96600	µg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: Drowsiness or mental confusion may occur.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of according to local or national legislation

Waste code number: 16 05 04

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

P18 EVERBUILD GAS LEAK DETECTOR

		Page: 6			
14.2. UN proper shipping name					
Shipping name:	AEROSOLS				
14.3. Transport hazard class(es)					
Transport class:	2				
14.4. Packing group					
14.5. Environmental hazards					
Environmentally hazardous:					
14.6. Special precautions for us	ser				
Special precautions:	No special precautions.				
Tunnel code:	D				
Section 15: Regulatory information	ation				
15.1. Safety, health and enviror	mental regulations/legislation specific for the substance or mixture				
-					
15.2. Chemical Safety Assessm					
Section 16: Other information					
Other information					
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No				
	453/2010.				
	* indicates text in the SDS which has changed since the last revision.				
Phrases used in s.2 and s.3:	H272: May intensify fire; oxidiser.				
	H301: Toxic if swallowed.				
	H315: Causes skin irritation.				
	H318: Causes serious eye damage.				
	H319: Causes serious eye irritation.				
	H400: Very toxic to aquatic life.				
	H411: Toxic to aquatic life with long lasting effects.				
	R8: Contact with combustible material may cause fire.				
	R25: Toxic if swallowed.				
	R38: Irritating to skin.				
	R41: Risk of serious damage to eyes.				
	R50: Very toxic to aquatic organisms.				
Legend to abbreviations:	PNEC = predicted no effect level				
	DNEL = derived no effect level				
	LD50 = median lethal dose				
	LC50 = median lethal concentration				
	EC50 = median effective concentration				

P18 EVERBUILD GAS LEAK DETECTOR

Page: 7

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.