

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

Q-No Clean Rework wand

Revision 0 Revision date 2017-08-31

1.1. Product identifier

Product name Q-No Clean Rework wand

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Soldering.

1.3. Details of the supplier of the safety data sheet

Company Qualitek Europe Ltd

Address Unit 9 Apex Court
Bassendale Road

Bromborough Wirral

CH62 3RE

Web www.qualitek.com

Telephone + 44(0)151 334 0888 **Fax** + 44(0)151 334 1408

Fax + 44(0)151 334 1408
Email address of the sales@qualitek-europe.com

competent person

1.4. Emergency telephone number

Emergency telephone number | + 44(0)151 334 0888

9.00 am - 5.00 pm Mon -Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1	1.2.	Cla	ssif	icat	ion	-	EC
12	72/	วกก	Ω				

Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;

1272/2008

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement Flam

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Revision 0 Revision date 2017-08-31

2.2. Label elements

Precautionary Statement:	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
	lenses, if present and easy to do. Continue rinsing.		
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.		
	P337+P313 - If eye irritation persists: Get medical advice/attention.		
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.		
Storage	P405 - Store locked up.		

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7	01-2119457558-25	90 - 100%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
Other(not classified)					1 - 10%	STOT SE 3: H335;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.		
Eye contact	May cause irritation to eyes.		
Skin contact	May cause dermatitis.		
Ingestion	Seek medical attention.		
4.3. Indication of any immediate medical attention and special treatment needed			

Inhalation	Coughing, difficulty in breathing and in severe cases, loss of consciousness.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Avoid prolonged or repeated exposure.
Ingestion	DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon oxides. Alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

Revision Revision date 2017-08-31

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1.	Appropriate	engineering

controls

8.2.2. Individual protection measures

Eye / face protection Skin protection -

Handprotection Respiratory protection Ensure adequate ventilation of the working area.

Wear chemical protective clothing.

Approved safety goggles.

Chemical resistant gloves (PVC).

Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 0
Revision date 2017-08-31

9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Clear

Odour Alcoholic

Melting point Not applicable.

Freezing Point Not applicable.

Initial boiling point 81 - 83 °C

Flash point 12 °C

Evaporation rate 1.7 g/min

Flammability (solid, gas) Not applicable.

Upper Explosive Limit 12 9

Lower Explosive Limit 2 %

Vapour pressure 43 Pa

Tapour procedure 4011

Vapour density 2.1 g/cm³

Fat Solubility

Not applicable.

Partition coefficient (n-octanol/water)

re 425 °C

Autoignition temperature

Explosive properties Not relevant

Oxidising properties

No data available

0.05 log P oct/wat

Solubility

Miscible in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Isopropanol	Dermal Rat LD50: 13900 mg/kg	Oral Rat LD50: 5840 mg/kg
	Dermal Rabbit LD50: 12870 mg/kg	Inhalation Rat LC50/4 h: 72.6 mg/L

SECTION 12: Ecological information

12.1. Toxicity

Isopropanol	Algae EC50/120h: >1000 mg/L	Algae EC50/72h: >1000 mg/L
	Lepomis_Macrochirus LC50/96h: >14000000 ug/L	

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms

Revision 0 Revision date 2017-08-31

Hazard pictograms



14.1. UN number

UN1219

14.2. UN proper shipping name

ISOPROPANOL

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3

14.4. Packing group

Subsidiary risk

14.5. Environmental hazards

Environmental hazards	
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction	353
(Passenger)	
Maximum quantity	51

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

SECTION 16: Other information

Other information

Revision 0 Revision date 2017-08-31

Other information		
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT SE 3: H335 - May cause respiratory irritation.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	