

# SGS25 POWER SUPPLY



## SGS25



### Features:

- Low Cost, High Reliability
- Overload and Short Circuit Protection
- Free air cooling convection
- High operating temperature up to 60°C

### Description:

The 25W Enclosed power supply has been specially designed to offer high efficiency, long life and high reliability for use in a variety of applications. This range comprises of 5 models with outputs of either 5v, 12v, 15v, 24v, 48v. Each models is RoHS, CE, UL approved and come with a three year warranty.

MODEL		SGS25-5	SGS25-12	SGS25-15	SGS25-24	SGS25-48
Output	DC Voltage	5V	12V	15V	24V	48V
	Rated Current	5A	2.1A	1.7A	1.1A	0.57A
	Current Range	0~5A	0~2.1A	0~1.7A	0~1.1A	0~0.57A
	Rated Power	25W	25.2W	25.5W	26.4W	27.36W
	Ripple & Noise	100mVp-p	120mVp-p	150mVp-p	200mVp-p	240mVp-p
	Voltage Regulation Range	4.5~5.5V	10.8~13.2V	13.5~16.5V	21.6~26.4V	44~52V
	Voltage Accuracy	+/- 1.0%				
	Line Regulation	+/- 0.5%				
	Load Regulation	+/- 2.0 %	+/- 1.0%	+/- 1.0%	+/- 1.0%	+/- 1.0%
	Rise Time	2000ms, 50ms / 230Vac at 100% Load				
	Hold Up Time	20ms / 230Vac at 100% Load				
Input	Full Input Voltage Range	88-264Vac				
	Full Frequency Range	47-63Hz				
	AC Current	0.7A / 115Vac 0.4A / 230Vac				
	In Rush Current	40A / 230Vac				
	Leakage Current	<3.5mA / 230Vac				
Protection	Over Load	110~150% rated output power				
	Short Circuit	Hiccup Mode, auto-recovery after fault condition is removed				
Environment	Working Temp	-10°C ~ +60°C (230Vac) (Refer to output derating curve)				
	Working Humidity	20~90%RH non-condensing				
	Storage Temp	-20oC ~ +45°C				
	Storage Humidity	10 ~ 95%RH non-condensing				
	Temp. Co-efficiency	+/-0.03% / °C (0 ~ 50°C)				
	Vibration Resistance	10 ~ 500Hz, 2G, 10 minute cycle, X, Y, Z 60 minute in each direction				
Safety	Safety Standards	EN60950-1, UL60950-1, CSA-C22.2 No. 60950-1 Approved				
	Withstand Voltage	I/P-0/P: 3KVac   I/P-FG: 1.5KVac   O/P-FG: 0.5KVac				
	Isolation Resistance	I/P-0/P, I/P-FG, O/P-FG: >50M Ω / 500VDC/ 25°C / 70%RH				
	EMC Emission	Compliance to EN55022 Class B, EN61000-3-2, -3				
	EMC Immunity	Compliance to EN55024, EN61000-4-2, -3, -4, -5, -6, -8, -11				
Others	Lifetime	50,000 Hours (25°C)				
	Size	85mm x 58.5mm x 36.5mm (L x W x H)				
	Package	80pcs/ctn, 20KG, 0.25Kg/piece				
Notes	The power supply is considered a component which must be installed into final equipment. The final equipment must be re-confirmed that it meets all applicable directives.					

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Stontronics Ltd  
Chancerygate Business Centre, Cradock Road, Reading RG2 0AH, UK  
t: +44 (0) 118 931 1199