

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX Contractors Hand Held Foam
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park
Dodworth, Barnsley
South Yorkshire S75 3SP

Tel: 01226 771600 Fax: 01226 771601
www.siroflex.co.uk info.siroflex@bostik.com

E-mail address

1.4. Emergency telephone number

United Kingdom +44 (0) 1226 771600 (Office Hours Only)
Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Effects on or via lactation	Yes - (H362)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 4 - (H413)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Isocyanic acid, polymethylenepolyphenylene ester, Alkanes, C14-17, chloro

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL



Signal word
Danger

Hazard statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H362 - May cause harm to breast-fed children.
H373 - May cause damage to organs through prolonged or repeated exposure.
H413 - May cause long lasting harmful effects to aquatic life.
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P260 - Do not breathe mist/vapours/spray
P263 - Avoid contact during pregnancy and while nursing
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During transportation by car the cans should stand upright in the cargo space. When foaming the propellants are highly flammable. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Isocyanic acid, polymethylenepolyphenylene ester	618-498-9	9016-87-9	>25 - <40	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]
Alkanes, C14-17, chloro	287-477-0	85535-85-9	15 - 25	Lact. (H362) (H362) (EUH066) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119519269-33-XXXX
Dimethyl ether	204-065-8	115-10-6	5 - <10	Flam. Gas 1 (H220) Press. Gas		01-2119472128-37-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

Inhalation	May cause allergic respiratory reaction. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention. Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not use solvents or thinners to dissolve the material.
Ingestion	May produce an allergic reaction. Get immediate medical advice/attention. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water.
Self-protection of the first aider	Remove all sources of ignition. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid breathing vapours or mists. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. May cause sensitisation by inhalation and skin contact. Product is or contains a sensitiser. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. See section 8 for more information. Avoid breathing dust/fume/gas/mist/vapours/spray. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Avoid breathing vapours or mists. Use personal protective equipment as required.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. In case of rupture. Use personal protection equipment. Do not puncture or incinerate cans. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Provide extract ventilation to points where emissions occur. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. Avoid contact with skin, eyes or clothing. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.
General hygiene considerations	Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep in properly labelled containers. Protect from sunlight. Keep out of the reach of children. Keep from freezing. Protect from moisture.

7.3. Specific end use(s)

Specific use(s)

Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	-	TWA: 0.005 ppm TWA: 0.02 mg/m ³ STEL: 0.015 ppm STEL: 0.07 mg/m ³ (CAS 101-68-8)	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³ SEN; as -NCO
Isobutane 75-28-5	-	TWA: 1000 ppm (8hr) STEL: 1000 ppm	-
Dimethyl ether 115-10-6	TWA: 1000 ppm TWA: 1920 mg/m ³	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³	TWA: 400 ppm TWA: 766 mg/m ³ STEL: 500 ppm STEL: 958 mg/m ³
Propane 74-98-6	-	STEL: 3000 ppm	-
Butane 106-97-8	-	TWA: 1000 ppm STEL: 3000 ppm	TWA: 600 ppm TWA: 1450 mg/m ³ STEL: 750 ppm STEL: 1810 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.7 mg/m ³	
worker Systemic health effects Long term	Dermal	47.9 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1894 mg/m ³	

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2 mg/m ³	
Consumer Long term Systemic health effects	Dermal	28.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.58 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	471 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Alkanes, C14-17, chloro (85535-85-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 µg/l
Marine water	0.2 µg/l
Microorganisms in sewage treatment	80 mg/l
Freshwater sediment	13 mg/kg dry weight
Marine sediment	2.6 mg/kg dry weight
Soil	11.9 mg/kg dry weight

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Wear suitable gloves. Butyl rubber. Nitrile rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better. AX.

Environmental exposure controls No information available.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	Foam
Colour	Yellow
Odour	Characteristic Slight
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	No data available
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	Not applicable
Initial boiling point and boiling range	Not applicable, Aerosol	Not applicable, Aerosol
Flash point	Not applicable, Aerosol	Not applicable, Aerosol
Evaporation rate	Not applicable	
Flammability	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	18.6 Vol%	
Lower flammability or explosive limits	1.7 Vol%	
Vapour pressure	6 -7 bar	bar @ 23 °C
Relative vapour density	No data available	No data available
Relative density	No data available	
Water solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	No data available
Autoignition temperature	. °C	No data available
Decomposition temperature	No data available	No data available
Kinematic viscosity	No data available	No data available
Dynamic viscosity	No data available	No data available
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Density	0.95 g/cm ³
Minimum Ignition Temperature (°C)	235

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	Yes.
Sensitivity to static discharge	Yes.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Do not freeze. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause sensitisation in susceptible persons. May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Causes skin irritation. (based on components). Specific test data for the substance or mixture is not available.
Ingestion	May cause additional effects as listed under "Inhalation". Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	11,940.30 mg/kg
ATEmix (inhalation-vapour)	3.28 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid,	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg	=1.5 mg/L (Rattus) 4 h

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

polymethylenepolyphenylene ester 9016-87-9		(Oryctolagus cuniculus)	
Alkanes, C14-17, chloro 85535-85-9	>4000 mg/kg (Rattus)	> 2000 mg/kg (Rattus)	
Dimethyl ether 115-10-6			=164000 ppm (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitisation	May cause sensitisation by inhalation. May cause sensitisation by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.
Reproductive toxicity	Classification based on data available for ingredients. May cause harm to breast-fed children.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Alkanes, C14-17, chloro 85535-85-9	Lact.

STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties .

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity May cause long lasting harmful effects to aquatic life.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L (Danio rerio)	-	EC50 (24h) >1000 mg/L Daphnia magna		
Alkanes, C14-17, chloro 85535-85-9	-	LC50: >500mg/L (48h, Leuciscus idus)	-	EC50 (48h) = 0.0059 mg/l (Daphnia magna) OECD 202		10
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	> 4400 mg/L (Daphnia) (NEN 6501)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	-	< 14
Alkanes, C14-17, chloro 85535-85-9	6	-
Dimethyl ether 115-10-6	-0.18	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Alkanes, C14-17, chloro 85535-85-9	The substance is not PBT / vPvB PBT & vPvB
Dimethyl ether 115-10-6	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Alkanes, C14-17, chloro	Group III Chemical	-

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
European Waste Catalogue	08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous substances 17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, Environmentally Hazardous
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited Quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols (Alkanes, C14-17, chloro), Marine Pollutant
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols (Alkanes, C14-17, chloro), 2.1, Marine Pollutant
14.5 Marine pollutant	P
14.6 Special Provisions	63, 190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

14.5 Environmental hazards	Yes
14.6 Special Provisions	A145, A167, A802
Limited Quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

SAFETY DATA SHEET

SX Contractors Hand Held Foam
Date: 27.04.2021

Replaces: 15.02.2019
Ref: 0045.17.BR/DL

H351 - Suspected of causing cancer
H362 - May cause harm to breast-fed children
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 25-Jan-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet