



**Underwriters
Laboratories Inc.®**

455 East Trimble Rd
San Jose, CA 95131-1230 USA
www.ul.com
tel: 1 408 754 6500
fax: 1 408 689 6500

05CA43491
E203950 - YDPU2/YDPU8

January 23, 2006

SHENZHEN WOER HEAT SHRINKABLE MATERIAL CO LTD.
Shenzhen, CHINA

Attention: Mr. Yorway Shore
Subject: Flexible Heat Shrinkable Polyolefin tubing - Cat. No. RSFR-H, using modified grade EVA 14-2, rated 125C, 600V, All Colors Except Clear, VW-1 Flame, 2.36 to 75.0 mm recovered ID

Dear Mr. Shore:

NOTICE OF AUTHORIZATION TO APPLY THE UL RECOGNITION MARK

UL's investigation of your product has been completed under project number 05CA43491 and the product was determined to comply with the applicable requirements.

This fax temporarily supplements the UL Follow-Up Services Inspection Procedure and serves as authorization to apply the UL Recognized Marking only at the factories under UL's Follow-Up Service Program to the products which are constructed as described below:

Cat. No. RSFR-H, as described above and on the attached Description pages, which were submitted for this investigation. The UL Records covering the initial testing of this product can be found in the UL Follow-Up Services Inspection Procedure, E203950, Vol. 2, Sec. 1.

This authorization is effective from the date of this Notice and only for products at the indicated manufacturing locations. Records in the Follow-Up Services Procedure covering the product are now being prepared and will be sent to the indicated manufacturing locations in the near future. Please note that Follow-Up Services Procedures are sent to the manufacturers only unless the Applicant specifically requests this document.

Products that bear the UL Recognition Mark shall be identical to those that were evaluated by UL and found to comply with UL's requirements. If changes in construction are discovered, appropriate action will be taken for products not in conformance with UL's requirements and continued use of the UL Recognition Mark may be withdrawn.

Very truly yours,

CELESTE CAPULONG (x 32161)
Project Handler
Email: Celeste.Capulong@us.ul.com

Reviewed by:

JANEANN MATULICH (x 32536)
Lead Engineering Associate



EXTRUDED TUBING, ELECTRICAL (YDPU2/YDPU8)

Group	Cat. No.	Colors	Procedure Section	Compound	Oil Resistance Temperature Rating	VW-1 Rated
Flexible Heat Shrinkable Polyolefin -						
1	RSFR-x	BK	1	Beijing Chemical EVA (14-2)	None	Yes
	RSFR-x	WT	1	Beijing Chemical EVA (14-2)	None	Yes
	WKZM-x-yz	WT	1	Beijing Chemical EVA (14-2) with Huiyuan ChemicalCo., Ltd. KY-405	None	No
1	RSFR-H	All except CL	1	See Table II	None	Yes
Not Heat Shrinkable PTFE -						
2	WF	NC	2	See Table I	<u>None</u>	Yes

x - Designated tubing expanded ID.

Note: for RSFR-x only, Black color tubing - x represents expanded ID of 2 mm - 8 mm.

Note: for RSFR-x only, White color tubing - x represents expanded ID of 1 mm - 50 mm.

Note: for WKZM-x-yz, - x represents expanded ID of 1 mm - 50 mm and -yz represents any alpha and/or numeric combination for internal Client code

Recovery time and temperature:

RSFR-x: 1 minute at 100C air oven.

WKZM-x-yz and RSFR-H: 3 minutes at 200C air oven.