



Heat Shrinkable Tubing 2:1 - Flame retardant

TR27

TR27 is used in applications where toxic emissions evolved in a fire must be minimised, e.g. heavily populated buildings or safety sensitive areas like tunnels, hospitals, schools, theatres, mass transit vehicles and computer centres.

Features and Benefits

- Thin walled, flexible polyolefin tubing
- Optional available with adhesive or as thick walled version (SR27)
- Halogen free and excellent flame-retardant properties
- Meets various industrial standards

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-40 °C to +105 °C
Minimum Shrink Temperature	+115 °C
Longitudinal change after shrinkage	+5 %/-10 % max.
Dielectric Strength	15 kV/mm according to IEC 60684 P2
Flammability	Limited Fire Hazard, Halogen free, Low generation of toxic gases and corrosive acid, Low smoke generation
Specifications	DEF STAN 59-97 Type 8, EN 45545:2013, LUL Engineering Standard E1042:A6



TR27 is ideal for safety sensitive areas.



TR27 is mainly used in the railway industry.



Heat Shrinkable Tubing 2:1



Detailed Information about Heatguns please refer to page 529.

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TR27-3.2/1.6	3.2	1/8 "	1.6	0.51	150 m	Black (BK)	315-50320
TR27-4.8/2.4	4.8	3/16 "	2.4	0.51	60 m	Black (BK)	315-50480
TR27-6.4/3.2	6.4	1/4 "	3.2	0.64	60 m	Black (BK)	315-50640
TR27-9.5/4.8	9.5	3/8 "	4.8	0.64	60 m	Black (BK)	315-50950
TR27-12.7/6.4	12.7	1/2 "	6.4	0.64	60 m	Black (BK)	315-51270
TR27-19.1/9.5	19.1	3/4 "	9.5	0.76	60 m	Black (BK)	315-51900
TR27-25.4/12.7	25.4	1 "	12.7	0.89	60 m	Black (BK)	315-52540
TR27-38.1/19.1	38.1	1-1/2 "	19.1	1.02	60 m	Black (BK)	315-53810
TR27-50.8/25.4	50.8	2 "	25.4	1.14	60 m	Black (BK)	315-55100

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

DEF STAN

EN



For product specific approvals and specifications please refer to the Appendix.