

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by **Regulation (EU) 2020/878)**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Anti-freeze Refrigerant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

LIQUI MOLY UK 1310 Solihull Parkway Birmingham Business Park B37 7YB Solihull Tel: +44 121 796 5365

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Landspitali- The National University Hospital of Iceland, tel. +354 543 2222 or 112 (valid only for Iceland)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR) +1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP) Hazard class Hazard category **Hazard statement**

Acute Tox. 4 H302-Harmful if swallowed.



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

STOT RE

2

H373-May cause damage to organs through prolonged or repeated exposure if swallowed (kidneys).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Warning

H302-Harmful if swallowed. H373-May cause damage to organs through prolonged or repeated exposure if swallowed (kidneys).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours or spray.

P314-Get medical advice / attention if you feel unwell.

P501-Dispose of contents / container to an approved waste disposal facility.

Ethanediol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3 2 Mixtures

Ethanediol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119456816-28-XXXX
Index	603-027-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-473-3
CAS	107-21-1
content %	80-98
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	STOT RE 2, H373 (kidneys) (oral)
Specific Concentration Limits and ATE	ATF (oral): 1600 mg/kg

Methyl-1H-benzotriazole	
Registration number (REACH)	01-2119979081-35-XXXX
Index	613-351-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	249-596-6
CAS	29385-43-1
content %	0,1-<1



Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

١.		
	Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
П		Repr. 2, H361d
		Aquatic Chronic 2, H411
il	Specific Concentration Limits and ATE	ATE (oral): 720 mg/kg

Potassium (benzothiazol-2-yl)thioacetate	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	2532-53-8
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Eye Dam. 1, H318
	Repr. 2, H361
	Aquatic Chronic 3, H412
Specific Concentration Limits and ATE	ATE (oral): 500 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

cramps

drowsiness

Nausea

vomiting

lower abdominal pain

oedema of the lungs

Kidney damage

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media



Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.



Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Not to be stored in gangways or stair wells.

Store in a well ventilated place. Store at room temperature.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Ethanediol					
WEL-TWA: 10 mg/m3 (particulate)		WEL-STEL: 104 mg/m3 (vapour) (WEL-STEL), 40				
(vapour) (WEL-TWA), 20 ppm (52 m	g/m3) (EU)	ppm (104 mg/m3) (EU)				
Monitoring procedures:	-	Draeger - Ethylene Glycol 10 (5) (81 01 351)				
	-	Compur - KITA-232 SA (502 342)				
	-	Compur - KITA-232 SB (550 267)				
	-	- NIOSH 5500 (ETHYLENE GLYCOL) - 1993				
	-	NIOSH 5523 (GLYCOLS) - 1996				
		OSHA PV2024 (Ethylene glycol) - 1999 - EU project BC/CE	N/ENTR/000/2002-16 card			
	-	11-2 (2004)				
BMGV:		Other information: SI	(particulate, vapour)			

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
••	Environmental		•			
	compartment					
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sewage		PNEC	199,5	mg/l	
	treatment plant					
	Environment - water,		PNEC	10	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sediment,		PNEC	37	mg/kg dry	
	freshwater				weight	
	Environment - sediment,		PNEC	3,7	mg/kg dry	
	marine				weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m3	
Consumer	Human - dermal	Long term, systemic	DNEL	53	mg/kg	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	35	mg/m3	
Workers / employees	Human - dermal	Long term, systemic	DNEL	106	mg/kg bw/d	
		effects				

Methyl-1H-benzotriazole						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,008	mg/l	
	Environment - marine		PNEC	0,008	mg/l	
	Environment - sediment, freshwater		PNEC	0,003	mg/kg dw	
	Environment - sediment, marine		PNEC	0,003	mg/kg dw	



Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

	Environment - soil		PNEC	0,0187	mg/kg dw
	Environment - sewage treatment plant		PNEC	39,4	mg/l
	Environment - water, sporadic (intermittent) release		PNEC	0,086	mg/l
Consumer	Human - oral	Long term, systemic effects	DNEL	0,01	mg/kg bw/day
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,01	mg/kg bw/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,35	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	21,2	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/day

- United Kingdom | WEL-TWA = Workplace Exposure Limit Long-term exposure limit 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE).
- | WEL-STEL = Workplace Exposure Limit Short-term exposure limit 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU: (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective gloves in butyl rubber (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Protective nitrile gloves (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0,38

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If the workplace limit value is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid
Colour: Red, Turbid
Odour: Slightly
Melting point/freezing point: <-36,4 °C

Boiling point or initial boiling point and boiling range: >=163 °

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

pH:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: Relative vapour density:

Particle characteristics:

9.2 Other information

No information available at present.

<-36,4 °C >=163 °C There is no information available on this parameter.

There is no information available on this parameter. There is no information available on this parameter.

122 °C (Pensky-Martens, closed cup)

398 °C (Ethanediol)

There is no information available on this parameter.

8,5 (20°C, ASTM D 1287)

There is no information available on this parameter. There is no information available on this parameter.

Does not apply to mixtures.

There is no information available on this parameter.

1,1195 kg/l (20°C)

There is no information available on this parameter.

Does not apply to liquids.

SECTION 10: Stability and reactivity

10.1 Reactivity



Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

The product has not been tested. 10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Acids

Oxidizing agents

Chlorates

Nitrates

Peroxides

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Kuehlerfrostschutz KFS 12+						
Radiator Antifreeze KFS 12+						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1740	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1600	mg/kg	Human being		
Acute toxicity, by oral route:	ATE	1600	mg/kg			
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>2,5	mg/l/6h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin				Human being	(Patch-Test)	Negative
sensitisation:						
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Rat	in vivo	Negative
Carcinogenicity:	NOAEL	1500	mg/kg	Mouse		Male, Negative
						oral, 2 a
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat		Negative
•			bw/d			_
Reproductive toxicity	NOAEL	250	mg/kg	Rat		Negative
(Developmental toxicity):			bw/d			-



B.

Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	150	mg/kg bw/d		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	STOT RE 2, Target organ(s): kidneys
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg bw/d	Rat	OECD 452 (Chronic Toxicity Studies)	STOT RE 2, Target organ(s): kidneys
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>2200 - <4400	mg/kg bw/d	Dog		Negative
Symptoms:						ataxia, breathing difficulties, unconsciousness , cramps, fatigue

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	720	mg/kg	Rat	OECD 401 (Acute Oral	
• •					Toxicity)	
Acute toxicity, by oral route:	ATE	720	mg/kg			
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Reproductive toxicity				Rat	OECD 421	Negative,
(Developmental toxicity):					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion
					Test)	
Reproductive toxicity	LOAEL	30	mg/kg	Rat	OECD 414 (Prenatal	Positiveoral
(Developmental toxicity):			bw/d		Developmental Toxicity	
					Study)	
Reproductive toxicity (Effects				Rat	OECD 421	Negative,
on fertility):					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion
					Test)	
Specific target organ toxicity -	NOAEL	150	mg/kg	Rat	OECD 407 (Repeated	<u> </u>
repeated exposure (STOT-RE),					Dose 28-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

Potassium (benzothiazol-2-yl)thioacetate							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	ATE	500	mg/kg			calculated value	

11.2. Information on other hazards

Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.



ĸ.

Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Other information:			No other
			relevant
			information
			available on
			adverse effects
			on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complex
							ng organic
							substance)>=
							80%/28d: n.a.
Other information:	AOX						Does not contain
							any organically
							bound halogens
							which can
							contribute to the
							AOX value in
						1	waste water.

Ethanediol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales	IUCLID Chem.	
-					promelas	Data Sheet (ESIS)	
12.1. Toxicity to fish:	NOEC/NOEL	7d	15380	mg/l	Pimephales	U.S. EPA	
-					promelas	ECOTOX	
						Database	
12.1. Toxicity to daphnia:	NOEC/NOEL		8590	mg/l	Daphnia magna	U.S. EPA	
						ECOTOX	
						Database	
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	8590	mg/l	Ceriodaphnia	U.S. EPA	
					spec.	ECOTOX	
						Database	
12.1. Toxicity to algae:	EC50	96h	6500-	mg/l	Pseudokirchneriell	U.S. EPA	
_			13000		a subcapitata	ECOTOX	
						Database	



B.

Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878) Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

12.2. Persistence and degradability:		10d	90-100	%	activated sludge	OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	56	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
12.4. Mobility in soil:	Log Koc		0-1				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	>10000	mg/l	Pseudomonas putida	IUCLID Chem. Data Sheet (ESIS)	
Toxicity to bacteria:	EC20	30min	>1995	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other information:	BOD5		0,78	g/g		,,	IUCLID

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	180	mg/l	Brachydanio rerio	OECD 203 (Fish,	Analogous
						Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	8,58	mg/l		OECD 202	Analogous
						(Daphnia sp.	conclusion
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	EC10	21d	0,4	mg/l		OECD 211	Analogous
						(Daphnia magna	conclusion
						Reproduction Test)	
12.1. Toxicity to daphnia:	LC50	2d	55	mg/l	Acartia tonsa	ISO 14669	
12.1. Toxicity to daphnia:	EC10	21d	5,93	mg/l	Daphnia magna	OECD 211	
,						(Daphnia magna	
						Reproduction Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	18,4	mg/l	Daphnia magna	OECD 202	
•						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to daphnia:	EC50	21d	> 37,6	mg/l	Daphnia magna	OEĆD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	30	mg/l	Skeletonema	ISO 10253	
				_	costatum		
12.1. Toxicity to algae:	IC50	72h	75	mg/l	Pseudokirchneriell	OECD 201 (Alga,	Analogous
				_	a subcapitata	Growth Inhibition	conclusion
						Test)	
12.1. Toxicity to algae:	EC50	72h	53	mg/l	Skeletonema	ISO 10253	
, 5				_	costatum		



Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

12.2. Persistence and		28d	4	%	activated sludge	Regulation (EC)	Not readily
degradability:						440/2008 C.4-D	biodegradable
						(DETERMINATIO	
						N OF 'READY'	
						BIODEGRAD	
						MANOMETRIC	
						RESPIROMETRY	
						TEST)	
12.3. Bioaccumulative	Log Kow		1,079-			OECD 117	Low
potential:			1,083			(Partition	
						Coefficient (n-	
						octanol/water) -	
						HPLC method)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:	EC50	24h	330	mg/l	activated sludge	ISO 8192	Analogous
							conclusion

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 01 14 antifreeze fluids containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):

Not applicable
14.4. Packing group:

Not applicable

Factor:

14.5. Environmental hazards:

Tunnel restriction code:

Classification code:

Not applicable

Not applicable

LQ:

Not applicable

Transport category:

Not applicable

Transport by sea (IMDG-code)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):

Not applicable



Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

14.4. Packing group:Not applicable14.5. Environmental hazards:Not applicableMarine Pollutant:Not applicableEmS:Not applicable

Transport by air (IATA)

14.1. UN number or ID number: Not applicable

14.2. UN proper shipping name:

Not applicable

14.3. Transport hazard class(es):Not applicable14.4. Packing group:Not applicable14.5. Environmental hazards:Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

0 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

8

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Acute Tox. 4, H302	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral

STOT RE — Specific target organ toxicity - repeated exposure

Repr. — Reproductive toxicity

Aquatic Chronic — Hazardous to the aquatic environment - chronic



Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive



Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 17.09.2025 / 0004

Replacing version dated / version: 13.03.2025 / 0003

Valid from: 17.09.2025 PDF print date: 19.09.2025 Kuehlerfrostschutz KFS 12+ Radiator Antifreeze KFS 12+

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

Limited Quantities LQ

International Convention for the Prevention of Marine Pollution from Ships MARPOL

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

No-longer-Polymer NLP

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic org.

OSHA Occupational Safety and Health Administration (USA)

persistent, bioaccumulative and toxic PBT

PF Polyethylene

PNEC Predicted No Effect Concentration

parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

Total organic carbon TOC

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.