

AMPLIMITE | AMPLIMITE 0.50 Series

TE Internal #: 2-5174225-5

AMPLIMITE 0.50 Series, PCB D-Sub Connectors, Plug, Cable-to-

Board, 68 Position, 1.27mm [.05in] Centerline, 2 Row, Row-to-Row

Spacing 2.54 mm [.1 in]

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Plug Assembly: Standard, Right Angle, 1.27mm











Connector & Housing Type: Plug
Connector System: Cable-to-Board

Number of Positions: 68

Centerline (Pitch): 1.27 mm [.05 in]

Number of Rows: 2

All D-Sub Plug Assembly: Standard, Right Angle, 1.27mm (13)

Features

Product Type Features

Post Plate Material	Thermoplastic
Shell Type	Full Metal Shell
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Shielded	Yes
Connector Type	Connector Assembly
Product Type	Connector
Configuration Features	
Number of Positions	68
Number of Rows	2
PCB Mount Orientation	Right Angle



Body Features

Post Plating Material	Tin over Nickel
Connector Profile	Standard
Shield Material	Zinc
Shell Material	Zinc Die Cast
Shell Plating Material	Nickel over Copper
Shield Plating Material	Nickel over Copper

Contact Features

Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Shape & Form	Square
	30 μin

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Post Length	2.9 mm[.114 in]

Mechanical Attachment

PCB Mount Retention PCB Mount Retention Type Mounting Hole Mating Retention With Mating Retention Type Latch Connector Mounting Type Board Mount Mating Alignment With	PCB Mount Alignment	Without
Mating Retention Mating Retention Type Latch Connector Mounting Type Board Mount	PCB Mount Retention	With
Mating Retention Type Latch Connector Mounting Type Board Mount	PCB Mount Retention Type	Mounting Hole
Connector Mounting Type Board Mount	Mating Retention	With
3 71	Mating Retention Type	Latch
Mating Alignment Without	Connector Mounting Type	Board Mount
	Mating Alignment	Without
Mounting Hole Diameter 2.7 mm	Mounting Hole Diameter	2.7 mm

Housing Features

Centerline (Pitch)	1.2/ mm[.05 in]
Housing Material	PBT
Housing Color	Black

Dimensions

Usage Conditions



Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Post Plate Flammability Rating	UL 94V-0
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray
Packaging Quantity	4

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Angle, 1.27mm



Also in the Series | AMPLIMITE 0.50 Series



D-Sub Backshells & Clamps(31)



D-Sub Covers(20)



D-Sub Locking & Mounting(8)



IDC D-Sub Connectors(77)



Insertion & Extraction Tools(1)



PCB D-Sub Connectors(196)

Customers Also Bought





BNC Ins R/A PCB Skt 500hm White




















Documents

Product Drawings

AMPLIMITE 050-2B HOR 68P M2.5

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-5174225-5_A_c-2-5174225-5-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-5174225-5_A_c-2-5174225-5-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-5174225-5_A_c-2-5174225-5-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_2-5174225-5_122020162346_dmtec

English

MD_2-5174225-5_122020162346_dmtec

English

Agency Approvals

UL Report

English