2-5530843-7 ACTIVE

TE Internal #: 2-5530843-7

Card Edge Power Connectors, Board-to-Board, 36 Position, 2.54 mm [.1in] Centerline, Printed Circuit Board, 3A Contact Current Rating (Max)


View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Card Edge Power Connectors











Connector System: Board-to-Board

Number of Positions: 36

Centerline (Pitch): 2.54 mm [.1 in]

Connector & Contact Terminates To: Printed Circuit Board

Contact Current Rating (Max): 3A

Features

Product Type Features

Receptacle
Connector Assembly
Board-to-Board
Socket
Printed Circuit Board
30

Configuration Features

Keying & Polarized Position Locations	0
PCB Mount Orientation	Vertical
Number of Positions	36
Number of Power Positions	36
Number of Signal Positions	0
Number of Dual Positions	18
Row-to-Row Spacing	4.85 mm[.191 in]

Electrical Characteristics



Operating Voltage	400 V
Contact Features	
Contact Termination Area Plating Finish	Matte
Contact Mating Area Plating Material Thickness	.38 μm[15 μin]
Contact Underplating Material	Nickel
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	3 A
Contact Mating Area Plating Material	Gold
Contact Termination Area Plating Material	Tin
Contact Termination Area Plating Thickness	2.54 μm
Termination Features	
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment	Without
PCB Mount Retention	With
PCB Mount Retention Type	Solder Tail
Connector Mounting Type	Board Mount
Mating Alignment	With
Mating Retention	Without
Mating Alignment Type	Keyed
Housing Features	
End Caps	Without
Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Black
Housing Material	Polyester GF
Dimensions	
Card Slot Depth	7.63 mm[.309 in]
Power Contact Centerline	2.54 mm[.1 in]
Height	15.63 mm[.75 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]



Operation/Application

Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box
Packaging Quantity	180
Other	
Position Locations Omitted	0
For Use With	Printed Circuit Board

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





















Documents

Product Drawings
CONN SEC II 18 POS 100C/L

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_2-5530843-7_F.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_2-5530843-7_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-5530843-7_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English