Timer Connector System

TE Internal #: 282190-5

TE Internal Description: SPLASH PROOF CONN. W.S.L.

View on TE.com >





Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUL 2017 (174) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts






TE Part # 828904-1 SINGLE WIRE SEAL FOR J.P.T.CON



TE Part # CAT-T4827-T273 TIMER, RECEPTACLE AND TAB




TE Part # 106462-1 2P.FASTIN-ON HSG.



SINGLE-WIRE-SEAL(5MM HOLE)



TE Part # 828906-2 BLINDSTOPFEN 1,5SYS



TE Part # 282536-1 S.WAY SEAL F.JPT CONTACT 2.5MM



TE Part # 828906-1 CAVITY PLUG (5MM HOLE)



TE Part # 1-929937-1 JPT REC 2.8 Contact SWS Au

Also in the Series | Timer Connector System



Automotive Connector Caps & Covers Automotive Connector Locks &



Position Assurance(16)





Automotive Housings(212)



Automotive Seals & Cavity Plugs(31)



Automotive Terminals(143)



Crimp Terminal Housings(13)



Insertion & Extraction Tools(20)



Other Automotive Connector Accessories(1)



Quick Disconnects(4)

Documents



Product Drawings

SPLASH PROOF CONN. W.S.L.

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_282190-5_M_c-282190-5-m.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_282190-5_M_c-282190-5-m.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_282190-5_M_c-282190-5-m.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Timer Interconnection System

English

Product Specifications

Product Specification

English

Instruction Sheets

2-7 positions junior power timer splash proof connectors

English

Instruction Sheet (non U.S.)

English