# 4-1564412-1 ACTIVE

### AMP | Heavy Duty Sealed Connector Series

TE Internal #: 4-1564412-1

Housing for Male Terminals, Wire-to-Wire, 18 Position, .157 in [4 mm] Centerline, Sealable, Blue, Signal, Heavy Duty Sealed

Connector Series

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Heavy Duty Sealed Connector Series Housings











Connector & Housing Type: Housing for Male Terminals

Mating Tab Width: 1.6 mm [.063 in ]
Connector System: Wire-to-Wire

Number of Positions: 18

Centerline (Pitch): 4 mm [ .157 in ]

Nominal Voltage Architecture

All Heavy Duty Sealed Connector Series Housings (204)

## **Features**

#### **Product Type Features**

Product Type Features	
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	18
Number of Rows	2
Electrical Characteristics	
Operating Voltage	60 VDC

12 V, 24 V, 42 V, 60 V



# **Body Features**

Cable Exit Angle	Other
Primary Product Color	Blue
Connector Code	D

#### **Contact Features**

Contact Size	1.6mm
Contact Type	Tab
Mating Tab Width	1.6 mm[.063 in]
Contact Current Rating (Max)	20 A

### Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Panel Mount

# **Housing Features**

Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]

## Dimensions

Connector Height	46.7 mm[1.839 in]
Product Width	27 mm[1.063 in]
Product Length	52.6 mm[2.071 in]
Row-to-Row Spacing	6 mm[.236 in]

# **Usage Conditions**

Operating Temperature (Max)	70 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]

# Operation/Application

Circuit Application	Signal

# **Industry Standards**

Degree of Protection	IP67	



UL Flammability Rating	UL 94V-0
o E i i ai i i i i a i i i j	0 - 7 1 7 0

#### **Packaging Features**

Packaging Quantity	200
Packaging Method	Carton

#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # CAT-H3399-B128

Heavy Duty Sealed Connector Series

Backshells



TE Part # 2112297-1
PROTECTION CAP,GROUP E,ASSY



TE Part # 964972-1
EINZELLEITERDICHTNG





TE Part # CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



# Also in the Series | Heavy Duty Sealed Connector Series



Automotive Connector Caps & Covers (25)



Automotive Housings(207



Automotive Seals & Cavity Plugs(5)




Data Connectivity Headers(2)



Data Connectivity Housings(18)



Other Automotive Connector Accessories(34)



PCB Headers & Receptacles(1)

# Customers Also Bought





Heavy Duty Sealed Connector Series
Housings











### **Documents**

## **Product Drawings**

18POS,TAB 1.6X0.6,TAB HSG,ASSY

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_4-1564412-1\_G.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_4-1564412-1\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1564412-1\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

# Datasheets & Catalog Pages

**HDSCS Catalog** 

English

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English

**Product Specifications** 

**Application Specification** 

English

**Application Specification** 

English