

CONTACT ORIENTATION ON ROLL

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

1.1. CONTACT BODY: COPPER ALLOY.
1.2. OUTER SPRING: STAINLESS STEEL.

2. SPECIFICATIONS:

2.1 CURRENT RATING: 13A MAX. 2.2 TERMINATION TYPE: CRIMPING. 2.3 WIRE RANGE: 16~18AWG.

2.4 WIRE INSULATION DIA(MAX): Ø3.2mm.

3. ROHS COMPLIANT.

4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

5. AVAILABLE TOOLS:

5.1 HAND CRIMPER: MFX-3954. 5.2 CRIMP APPLICATOR: MFX-3957. 5.3 EXTRACTION TOOL: QXRT16.

	-
P/N	CONTACT PLATING(MATING AREA)
SS16M1T	TIN PLATING OVER NICKEL.
SS16M1F	GOLD FLASH PLATING OVER NICKEL.
SS16M1G10	10μ"GOLD PLATING OVER NICKEL.
SS16M1G15	15µ"GOLD PLATING OVER NICKEL.
SS16M1G30	30µ"GOLD PLATING OVER NICKEL.



REVISIONS

TITLE: ECO-MATE, SOCKET CONTACT, STAMPED, 16-18AWG, SIZE 16

SS16M1XX

REV: B1 SH:





