

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 25/05/2023 Revision date: 15/03/2023 Supersedes version of: 24/03/2022 Version: 1.2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : KONTAKT WL

UFI : 6J1X-Y8VX-M002-FKV3

Product code : BDS000542AE
Type of product : Detergent
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Cleaners - Precision

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

#### Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele Belgium

T +32(0)52/45.60.11 - F +32(0)52/45.00.34

hse@crcind.com - www.crcind.com

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Contains : propan-2-ol; isopropyl alcohol; isopropanol; Hydrocarbons, C6-C7, n-alkanes, isoalkanes,

cyclics, <5% n-hexane; 1-methoxy-2-propanol; monopropylene glycol methyl ether; butan-2-

ol; butanone; ethyl methyl ketone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation. H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Other information

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514- 35	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butan-2-ol substance with national workplace exposure limit(s) (BE)	CAS-No.: 78-92-2 EC-No.: 201-158-5 EC Index-No.: 603-127-00-5 REACH-no: 01-2119475146- 36	10 – 25	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H336 STOT SE 3, H335
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
Carbon dioxide (CO2) (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	1-5	Press. Gas (Comp.), H280
butanone; ethyl methyl ketone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	1-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.

First-aid measures after skin contact

: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after eye contact

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.

attention in initiation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung oedema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

15/03/2023 (Revision date) BE - en 3/18

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial

hygiene and safety procedures.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use.

15/03/2023 (Revision date) BE - en 4/18

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 7.3. Specific end use(s)

No additional information available

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

# 8.1.1 National occupational exposure and biological limit values

STIT MALICINAL COCUPALICINAL EXPOSURE AND STOLEGICAL MINIC VALACE		
Carbon dioxide (CO2) (124-38-9)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Carbon dioxide	
IOEL TWA	9000 mg/m³	
IOEL TWA [ppm]	5000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Belgium - Occupational Exposure Limits		
Local name	Carbone (dioxyde de) # Koolstofdioxide	
OEL TWA	9131 mg/m³	
OEL TWA [ppm]	5000 ppm	
OEL STEL	54784 mg/m³	
OEL STEL [ppm]	30000 ppm	
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
propan-2-ol; isopropyl alcohol; isopropanol (	67-63-0)	
Belgium - Occupational Exposure Limits		
Local name	Alcool isopropylique # Isopropylalcohol	
OEL TWA	500 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1000 mg/m³	
OEL STEL [ppm]	400 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	1-Methoxypropanol-2	
IOEL TWA	375 mg/m³	
IOEL TWA [ppm]	100 ppm	
IOEL STEL	568 mg/m³	
IOEL STEL [ppm]	150 ppm	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits	· 3	
Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol	
OEL TWA	184 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	369 mg/m³	
OEL STEL [ppm]	100 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
butan-2-ol (78-92-2)		
Belgium - Occupational Exposure Limits	S	
Local name	Alcool sec-butylique # sec-Butanol	
OEL TWA	307 mg/m³	
OEL TWA [ppm]	100 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
butanone; ethyl methyl ketone (78-9	3-3)	
EU - Indicative Occupational Exposure L	imit (IOEL)	
Local name	Butanone	
IOEL TWA	600 mg/m³	
IOEL TWA [ppm]	200 ppm	
IOEL STEL	900 mg/m³	
IOEL STEL [ppm]	300 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	2-Butanone # 2-Butanon	
OEL TWA	600 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	900 mg/m³	
OEL STEL [ppm]	300 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	

## 8.1.2. Recommended monitoring procedures

No additional information available

# 8.1.3. Air contaminants formed

No additional information available

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 8.1.4. DNEL and PNEC

8.1.4. DNEL and PNEC	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
PNEC (Soil)	
PNEC soil	28 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	160 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	2251 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	cyclics, <5% n-hexane
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m³
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day
1-methoxy-2-propanol; monopropylene glyco	I methyl ether (107-98-2)
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	553,5 mg/m³
Acute - local effects, inhalation	553,5 mg/m³
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	369 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	43,9 mg/m³
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l	
PNEC aqua (marine water)	1 mg/l	
PNEC aqua (intermittent, freshwater)	100 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	52,3 mg/kg dwt	
PNEC sediment (marine water)	5,2 mg/kg dwt	
PNEC (Soil)		
PNEC soil	4,59 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
butan-2-ol (78-92-2)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	405 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	600 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	15 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	213 mg/m³	
Long-term - systemic effects, dermal	203 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	47,1 mg/l	
PNEC aqua (marine water)	47,1 mg/l	
PNEC aqua (intermittent, freshwater)	47,1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	196,19 mg/kg dwt	
PNEC sediment (marine water)	196,19 mg/kg dwt	
PNEC (Soil)		
PNEC soil	11,58 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	1000 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	761 mg/l	
butanone; ethyl methyl ketone (78-93-3)  DNEL/DMEL (Workers)		
		Long-term - systemic effects, dermal
Long-term - systemic effects, inhalation	600 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	31 mg/kg bodyweight/day	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone; ethyl methyl ketone (78-93-3)	
Long-term - systemic effects, inhalation	106 mg/m³
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	55,8 mg/l
PNEC aqua (marine water)	55,8 mg/l
PNEC aqua (intermittent, freshwater)	55,8 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	284,74 mg/kg dwt
PNEC sediment (marine water)	284,7 mg/kg dwt
PNEC (Soil)	
PNEC soil	22,5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	1000 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	709 mg/l

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):





#### 8.2.2.1. Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless.

Appearance : CO2 propelled liquid.

Odour: Solvent.Odour threshold: Not availableMelting point: Not applicableFreezing point: Not availableBoiling point: 60 - 120 °C

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : Not available
Lower explosion limit : Not available
Upper explosion limit : Not available
Flash point : -20 °C (closed cup)

Auto-ignition temperature : > 200 Decomposition temperature : Not available Hq : Not applicable Viscosity, kinematic  $< 20,5 \text{ mm}^2/\text{s}$ Solubility : insoluble in water. Partition coefficient n-octanol/water (Log Kow) : Not applicable Vapour pressure : Not available Vapour pressure at 50°C : Not available : 0,77 g/cm3 at 20 °C

Density : 0,77 g/cm³ at 2 Relative density : 0,77 at 20 °C Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 75 - 100 %

9.2.2. Other safety characteristics

Relative evaporation rate (ether=1) : 9
VOC content : 740 g/l

Additional information : For aerosols data for the product without propellant.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

#### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

propan-2-ol; isopropyl	alcohol; isopropanol	(67-63-0)
------------------------	----------------------	-----------

LD50 oral rat 5840 mg/kg bodyweight

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LD50 oral rat	5841 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 25,2 mg/l/4h

#### 1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25,8 mg/l

#### butan-2-ol (78-92-2)

Serious eye damage/irritation

LD50 oral rat	2193 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight

#### butanone; ethyl methyl ketone (78-93-3)

LD50 oral rat	> 2193 mg/kg bodyweight
LD50 dermal	6400 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 5000 mg/l/4h

# Skin corrosion/irritation : Causes skin irritation. pH: Not applicable

: Causes serious eye irritation.

pH: Not applicable

Respiratory or skin sensitisation: Not classified (Based on available data, the classification criteria are not met)Germ cell mutagenicity: Not classified (Based on available data, the classification criteria are not met)Carcinogenicity: Not classified (Based on available data, the classification criteria are not met)Reproductive toxicity: Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

STOT-single exposure May cause drowsiness or dizziness.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hudraankana CC 07 - Harray 1	lleanes evelies 450/ m bevens
Hydrocarbons, C6-C7, n-alkanes, isoal	
STOT-single exposure	May cause drowsiness or dizziness.
1-methoxy-2-propanol; monopropylen	e glycol methyl ether (107-98-2)
STOT-single exposure	May cause drowsiness or dizziness.
butan-2-ol (78-92-2)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
butanone; ethyl methyl ketone (78-93-	3)
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
1-methoxy-2-propanol; monopropylen	e glycol methyl ether (107-98-2)
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight
Aspiration hazard	: May be fatal if swallowed and enters airways.
KONTAKT WL	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm²/s
Hydrocarbons, C6-C7, n-alkanes, isoal	lkanes, cyclics, <5% n-hexane
Viscosity, kinematic	0,7 mm²/s
1-methoxy-2-propanol; monopropylen	e glycol methyl ether (107-98-2)
Viscosity, kinematic	1,848 mm²/s
butan-2-ol (78-92-2)	
Viscosity, kinematic	5,185 mm²/s

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2. Other information

No additional information available

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general

: Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term (acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propan-2-ol; isopropyl alcohol; isoprop	panol (67-63-0)
LC50 - Fish [1]	10000 mg/l
LC50 - Fish [2]	9640 mg/l
Hydrocarbons, C6-C7, n-alkanes, isoall	kanes, cyclics, <5% n-hexane
LC50 - Fish [1]	11,4 mg/l
EC50 - Crustacea [1]	3 mg/l
EC50 72h - Algae [1]	10 mg/l
LOEC (chronic)	0,32 mg/l
NOEC (chronic)	0,17 mg/l
NOEC chronic fish	2,04 mg/l
NOEC chronic crustacea	1 mg/l
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)
LC50 - Fish [1]	6812 mg/l
LC50 - Fish [2]	20800 mg/l
EC50 - Crustacea [1]	21100 – 25900 mg/l
EC50 - Other aquatic organisms [1]	2954 mg/l
ErC50 algae	> 1000 mg/l
butan-2-ol (78-92-2)	
LC50 - Fish [1]	2993 mg/l
EC50 - Crustacea [1]	308 mg/l
EC50 72h - Algae [1]	1972 mg/l
EC50 96h - Algae [1]	2029 mg/l
butanone; ethyl methyl ketone (78-93-3	6)
LC50 - Fish [1]	2993 mg/l
EC50 - Crustacea [1]	308 mg/l
EC50 - Other aquatic organisms [1]	308 mg/l
EC50 72h - Algae [1]	1972 mg/l
EC50 96h - Algae [1]	2029 mg/l

# 12.2. Persistence and degradability

No additional information available

# 12.3. Bioaccumulative potential

KONTAKT WL			
Partition coefficient n-octanol/water (Log Kow)	Not applicable		
Carbon dioxide (CO2) (124-38-9)			
Partition coefficient n-octanol/water (Log Pow)	0,83		
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)			
Bioconcentration factor (BCF REACH)	< 100		
Partition coefficient n-octanol/water (Log Pow)	0,37		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butan-2-ol (78-92-2)	
Partition coefficient n-octanol/water (Log Pow)	0,65
butanone; ethyl methyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0,3

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

KONTAKT WL	
Results of PBT assessment	Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

#### 12.7. Other adverse effects

Additional information : No other effects known

Global warming potential (GWP) : 0 (Fluorinated greenhouse gases - (EC) No 517/2014)

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW) code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	umber				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper shippin	g name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS	
Transport document descr	iption				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	
14.3. Transport hazard class(es)					
2.1	2.1	2.1	2.1	2.1	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
2		2	2	
4.4. Packing group	<u> </u>	•	•	<u> </u>
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.5. Environmental haza	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
environment: No	Marine pollutant: No	environment: No	environment: No	environm

## 14.6. Special precautions for user

#### Overland transport

: 5F Classification code (ADR)

: 190, 327, 344, 625 Special provisions (ADR)

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9 Transport category (ADR) 2 Special provisions for carriage - Packages (ADR) : V14 Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 : D Tunnel restriction code (ADR)

#### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

: SW1, SW22

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 : P207, LP200 Packing instructions (IMDG) Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None

Stowage and handling (IMDG) Segregation (IMDG) : SG69

#### Air transport

: E0 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) Y203 PCA limited quantity max net quantity (IATA) 30kgG PCA packing instructions (IATA) 203 PCA max net quantity (IATA) 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### Inland waterway transport

Classification code (ADN) : 5F

190, 327, 344, 625 Special provisions (ADN)

Limited quantities (ADN) : 1L Excepted quantities (ADN) : E0

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Equipment required (ADN) : PP, EX, A Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

## **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### VOC Directive (2004/42)

VOC content : 740 g/l

### Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	15-30%

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acr	onyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.