Yuvolt - Valve Regulated Lead Acid Battery

Y10-6

Specifications		
Nominal voltage	6	Tv
20-hr rate capacity to 1.75VPC at 20°C	10	Ah
10-hr rate capacity to 1.75VPC at 20°C	9.26	Ah
Dimensions	9.20	All
	454 (14)	T
Length	151 (±1)	mm
Width	51 (±1)	mm
Height (Height over terminals)	94 (±1) 100 (±2)	mm
Mass (typical)	1.7	kg
Terminal type	1.7	<u> </u>
**	1 75	Imm
Faston (quickfit / release)	4.75	mm
Operating temperature range	1 2000	
Storage	-20°C to +60°C	
Charge	-15°C to +50°C	
Discharge	-20°C	to +60°C
Storage	1 0	To:
Capacity loss per month at 20°C (approx)	3	%
Case material	1 ABC (LIL OA-LID)
Standard option	ABS (UL.94:HB)	
Flame retardant option (FR)	ABS (UL94:V0)	
Charge voltage		
Float charge voltage at 20°C	13.65 (±1%) 2.275 (±1%)	V V/cell
Float charge voltage temperature correction factor (for variations from the standard 20°C)	-3	mV/cell/°C
Cyclic (or boost) charge at 20°C	14.5 (±3%)	V
, , ,	2.42 (±3%)	V/cell
Cyclic charge voltage temperature correction factor (for variations from the standard 20°C)	-4	mV/cell/°C
Charge current		
Float charge current limit	No limit	A
Cyclic (or boost) charge current limit	2.5	A
Maximum discharge current		
1 minute	75	A
Short-circuit current & internal resistance		
(According to EN IEC 60896-21)		
Internal resistance	N/A	mΩ
Short-circuit current	N/A	А
Impedance		
Measured at 1 kHz	18	mΩ
Performance & characteristics		
Refer to the technical manual	Yuvolt	I
Design life		
EUROBAT Classification: Standard Commercial	3 to 5	years
Yuasa design life @ 20°C	up to 5	years

SAFETY

Installation

Can be installed and operated in any orientation except permanently inverted

Handles

Batteries must not be suspended by their handles (where fitted)

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal

Gas release


VRLA batteries release hydrogen gas which can form explosive mixtures in air. Do not place inside a sealed container

Recycling

Yuasa's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations

Data sheet





Third party certifications

ISO 9001 - Quality Management Systems
ISO 14001 - Environmental Management Systems
EN 18001 - OHSAS Management Systems
Underwriters Laboratories Inc.



Standards

IEC61056







ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE Issue No.: V.1 / Issue date: June 2023



GS Yuasa Battery Sales UK Ltd. Unit 8 Ignition Park Swindon SN3 5FB UK