

USB 3.0 to DVI / VGA External Video Card Multi Monitor Adapter – 2048x1152

StarTech ID: USB32DVIPRO



The USB32DVIPRO USB 3.0 to DVI Adapter turns an available USB 3.0 port into a DVI output, with high resolution 2048x1152 video support - a convenient external video solution that makes it easy to add multimonitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter functions as a external graphics card to deliver smooth, high-resolution content to your DVI or VGA-capable display (DVI to VGA Adapter included). The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher



Applications

- Add a secondary DVI or VGA display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Use the adapter to connect your PC to your DVI or VGA-equipped TV, for showing family pictures and movies
- Great for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other
- Increase productivity by running multiple applications on different screens, check your e-mail on one display and search the web on the other
- View large or multiple spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using laptop PCs, enabling connection to a secondary display/projector

Features

- SuperSpeed USB 3.0 (5 Gbps) Interface and backwards compatible with USB 2.0
- Quick, easy installation
- DVI to VGA adapter included
- Supports resolutions up to 2048x1152
- USB-powered No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the Windows® Aero interface
- Supports the use of multiple USB32DVIPRO adapters on a single system (up to 5)





Technical Specifications

2 Years Warranty Audio Yes

Chipset ID DisplayLink - DL3100 512MB DDR2 SDRAM Memory Output Signal DVI-I (DVI Digital/Analog)

USB Pass-No

Through

General This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a Specifications computer along with additional USB video adapters or docking stations, please avoid using

devices with a Trigger or Fresco family chipset.

2048x1152 Maximum

Analog Resolutions

2048x1152 Maximum

Digital Resolutions

Note If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software.

10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.

Supported Widescreen(16/32 bit):

Resolutions 2048x1152, 1920x1200, 1920x1080, 1680x1050, 1366x768, 1280x800, 1280x768, 1280x720

Standard(16/32 bit):

1600x1200, 1400x1050, 1280x1024, 1024x768, 800x600, 640X480

Wide Screen Yes

Supported

Connector A 1 - USB Type-A (9 pin) USB 3.0 Male

Connector B 1 - DVI-I (29 pin) Female

OS Windows® 10 (32/64), 8/8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64), 2000 (Aero 3D

Compatibility interface supported)

Apple® OSX El Capitan (10.11), Yosemite (10.10), Mavericks (10.9) Mountain Lion (10.8), Lion

(10.7), Snow Leopard (10.6)

Note Connect a maximum of five USB32DVIPRO adapters on a single PC - See manual for system

requirements

System and 1~2 USB Displays Cable Office Application:

Requirements CPU: i3 Dual core 2.8GHz

RAM: 2GB or higher





Hard-to-find made easy®

Full HD Video:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Power Source

USB-Powered

Uumidit.

Humidity <85% RH Non-Condensing Operating 10°C to 40°C (50°F to 194°F)

Temperature

Storage -10°C to 80°C (14°F to 167°F)

Temperature

Color Black Enclosure Plastic

Туре

Product 0.6 in [15.5 mm]

Height

Product 3.1 in [78 mm]

Length

Product 10.6 oz [300 g]

Weight

Product 1.7 in [43.5 mm]

Width

Shipping 0.5 lb [0.2 kg]

(Package) Weight

Included in 1 - USB 3.0 to DVI Adapter

Package

Included in 1 - DVI to VGA Adapter

Package

Included in 1 - Driver CD

Package

Included in 1 - Installation guide

Package





Certifications, Reports and Compatibility











