Rapid

G2058 Polycarbonate Enclosure
360 x 200 x 150mm

Order code: **30-4072**

Features:

Light grey polycarbonate box, 360 x 200 x 150mm with tongue-and-groove sealing system plus neoprene gasket giving sealing to **IP65**.

- Wall mounting holes and lid fixing screws are outside the sealed area preventing ingress of dust and moisture
- Internal guide slots for mounting PCBs vertically
- Bosses with threaded brass inserts in base for horizontal mounting of PCBs or terminals
- Non-magnetic M4 lid fixing screws
- Temperature range –40 to +125°C

360mm
349.28mm
340mm
90mm
170mm
250mm
302mm
331mm
165.50mm
Ø 5mm
80mm
100mm
172.50mm
180mm
189.28mm
200mm

360mm
340mm
B
180mm
200mm
B

50mm
3.50mm
180mm
200mm

SECTION B-B
SCALE 1 : 3

340mm
156mm
Ø 6.40mm
100mm
9.78mm
3.50mm

SECTION A-A
SCALE 1 : 3

6mm
4.50mm
150mm

ASSEMBLY

According to ISO 2768-m	
Measuring DIM=L	Tolerances
0.5<L<=3.0mm	±0.1mm
3.0<L<=6.0 mm	±0.1mm
6.0<L<=30.0 mm	±0.2mm
30.0<L<=120.0 mm	±0.3mm
120.0<L<=400.0 mm	±0.5mm
400.0<L<=1000.0 mm	±0.8mm

www.rapidonline.com