

## Datasheet

Manufacturer Part No.: T24C029

## Crimp connector assortment 850 pcs

Fork connectors, ring terminals, ferrules, blade receptables, isolating sleeves, flat plugs



This crimp connectors guarantee optimal results in conjunction with fitting crimping tools. This product series includes the most common parts used in practice. The assortment is especially suitable for hobbyists, craftsmen, field service, service workshops, electronics technicians and laboratory needs. Connection only by qualified electricians!

| Content | Description                         | Material           | Cross section          |
|---------|-------------------------------------|--------------------|------------------------|
| 25 pcs  | Fork connector red, holeØ 3.1 mm    | Copper, tin plated | 0.51.5 mm <sup>2</sup> |
| 25 pcs  | Fork connector blue, holeØ 4.1 mm   | Copper, tin plated | 0.51.5 mm <sup>2</sup> |
| 20 pcs  | Fork connector red, holeØ 5.2 mm    | Copper, tin plated | 1.52.5 mm <sup>2</sup> |
| 25 pcs  | Ring terminal red, holeØ 3.1 mm     | Copper, tin plated | 0.51.5 mm <sup>2</sup> |
| 25 pcs  | Ring terminal blue, holeØ 4.1 mm    | Copper, tin plated | 0.51.5 mm <sup>2</sup> |
| 20 pcs  | Ring terminal yellow, holeØ 5.2 mm  | Copper, tin plated | 1.52.5 mm <sup>2</sup> |
| 80 pcs  | Ferrules white, length 14 mm        | Copper, tin plated | 0.5 mm <sup>2</sup>    |
| 75 pcs  | Ferrules green, length 14.3 mm      | Copper, tin plated | 1.0 mm <sup>2</sup>    |
| 55 pcs  | Ferrules yellow, length 14.3 mm     | Copper, tin plated | 1.5 mm <sup>2</sup>    |
| 40 pcs  | Ferrules black, length 17.4 mm      | Copper, tin plated | 2.5 mm <sup>2</sup>    |
| 25 pcs  | Ferrules blue, length 19.4 mm       | Copper, tin plated | 4.0 mm <sup>2</sup>    |
| 15 pcs  | Ferrules red, length 20.5 mm        | Copper, tin plated | 6.0 mm <sup>2</sup>    |
| 60 pcs  | Blade receptacle 2.8 mm             | Copper, tin plated | 0.5 mm <sup>2</sup>    |
| 50 pcs  | Blade receptacle 4.8 mm             | Copper, tin plated | 0.5 mm <sup>2</sup>    |
| 30 pcs  | Blade receptacle 6.3 mm             | Copper, tin plated | 1.5 mm <sup>2</sup>    |
| 60 pcs  | Flat plug 2.8 mm                    | Copper, tin plated | 0.5 mm <sup>2</sup>    |
| 50 pcs  | Flat plug 4.8 mm                    | Copper, tin plated | 0.5 mm <sup>2</sup>    |
| 30 pcs  | Flat plug 6.3 mm                    | Copper, tin plated | 1.5 mm <sup>2</sup>    |
| 60 pcs  | Isolating sleeve transparent 2.8 mm | PVC                | //                     |
| 50 pcs  | Isolating sleeve transparent 4.8 mm | PVC                | //                     |
| 30 pcs  | Isolating sleeve transparent 6.3 mm | PVC                | //                     |

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval of the editor. Reprinting, also in part, is prohibited. The publication represents the technical status at the time of printing. All statements without guarantee.