

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

Revision date: 1/17/2017

Supersedes: 8/11/2016

Version: 10.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Name : TIPP-EX® RAPID
Product code : WQ-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Use of the substance/mixture : Correction fluid

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

SOCIETE BIC
14, Rue Jeanne d'Asnières
92611 CLICHY Cédex
T +33 01 45 19 52 00 - F +33 01 45 19 52 99
Bic.Contact@bicworld.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	-

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes skin irritation. Vapours may cause drowsiness and dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

Naphtha (petroleum), hydrotreated light

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261 - Avoid breathing vapours
P273 - Avoid release to the environment

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

Labelling according to: exemption for packages of a capacity of 125ml or less

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :

H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) :

P261 - Avoid breathing vapours

Hazardous ingredients :

Naphtha (petroleum), hydrotreated light

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium dioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	< 50	Not classified
Naphtha (petroleum), hydrotreated light (Note P)	(CAS-No.) 64742-49-0 (EC-No.) 265-151-9 (EC Index-No.) 649-328-00-1 (REACH-no) 01-2119475133-43	30 - 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Naphtha (petroleum), light alkylate (Note P)	(CAS-No.) 64741-66-8 (EC-No.) 265-068-8 (EC Index-No.) 649-276-00-X	< 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7	< 1	Flam. Liq. 3, H226
carbon black substance with national workplace exposure limit(s) (GB)	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 1	Not classified

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If the person feels unwell : Seek medical advice.
- First-aid measures after skin contact : Wash immediately with plenty of soap and water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If irritation persists, consult an eye specialist.
- First-aid measures after ingestion : Do not induce vomiting. Seek medical advice (show the label where possible).

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Drowsiness. Giddiness.
- Symptoms/effects after skin contact : Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Fire hazard : On heating or during combustion : Toxic vapours may be released.

Explosion hazard : The vapours are denser than air and may travel along the ground. Distance ignition possible.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate the danger area. Cool down the containers exposed to heat with a water spray. Contain the extinguishing fluids by bunding (the product is hazardous for the environment). Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. Do not breathe smoke. No flames, no sparks. Eliminate all sources of ignition. Do not smoke. In case of important spillage : Mark out the contaminated area with signs and prevent access to unauthorized personnel. Prevent the product from entering drains or confined areas. Ventilate spillage area. Stop leak if safe to do so. Use only non-sparking tools.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Contain the spilled material by bunding (product is hazardous for the environment). Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spillage with: inert absorbent material. Sand/earth.

Methods for cleaning up : Sweep up or vacuum up the product. Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Vapour exhaust preferably at emission point. Use non-sparking tools. Avoid contact with skin and eyes. Do not breathe smoke. No flames, no sparks. Eliminate all sources of ignition. Smoking is forbidden. Take precautionary measures against static discharges. Do not overheat the product.

Hygiene measures : Do not drink, eat or smoke in the workplace. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : The floor of the depot must be impermeable, non-combustible and designed to form a basin, in order that stored flammable liquids should not, under any circumstances, be released outside.

Storage conditions : Store in a cool, well-ventilated place. Keep container tightly closed. Avoid ignition sources. Keep away from naked flames/heat.

Incompatible materials : Strong oxidizing agents. Oxidizing materials.

Packaging materials : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)		
United Kingdom	Local name	Titanium dioxide
United Kingdom	WEL TWA (mg/m ³)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
2-methoxy-1-methylethyl acetate (108-65-6)		
EU	Local name	2-Methoxy-1-methylethylacetate
EU	IOELV TWA (mg/m ³)	275 mg/m ³
EU	IOELV TWA (ppm)	50 ppm

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

2-methoxy-1-methylethyl acetate (108-65-6)		
EU	IOELV STEL (mg/m ³)	550 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
United Kingdom	Local name	1-Methoxypropyl acetate
United Kingdom	WEL TWA (mg/m ³)	274 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	548 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
carbon black (1333-86-4)		
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m ³)	3.5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	7 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Extraction to remove vapours at their source.

Hand protection:

Impermeable protective gloves. The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN 374. Breakthrough time : refer to the recommendations of the supplier

Eye protection:

Safety glasses

Respiratory protection:

If vapour is released : Aerosol filter type : A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: Solvent.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 95 - 114 °C (760 mmHg)
Flash point	: -9 °C (NF EN ISO 13736)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 26 - 49 mm Hg (20 °C)
Relative vapour density at 20 °C	: No data available
Relative density	: 1.25 (25°C)
Solubility	: Water: 0.1 g/l Practically insoluble
Log Pow	: No data available
Viscosity, kinematic	: > 60 mm ² /s (40°C)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: 1.7 - 12.3 vol %

9.2. Other information

Additional information	: Volatile component : 0.89 - 1.08 %
------------------------	--------------------------------------

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

To our knowledge, the product does not present any particular risk, under normal conditions of use.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

None to our knowledge.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Ignition sources.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

On combustion or on thermal decomposition (pyrolysis) releases : Carbon oxides (CO, CO₂). Various hydrocarbon fragments.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Naphtha (petroleum), light alkylate (64741-66-8)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	> 5.04 ppm/4h

Naphtha (petroleum), hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3160 mg/kg
LC50 inhalation rat (mg/l)	> 12 mg/l/6h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg (OECD 425 method)
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (mg/l)	> 3.56 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: Titanium dioxide (powder) is listed as being potentially carcinogenic (group 2B) by the CIRC, based on studies on animals However, studies on human epidemiology do not suggest links between the occupational exposure to titanium dioxide and the risk of cancer
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Naphtha (petroleum), light alkylate (64741-66-8)	
LC50 fish 1	8.3 mg/l/96h (Pimephales promelas)

Naphtha (petroleum), hydrotreated light (64742-49-0)	
EC50 Daphnia	2.6 mg/l

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

12.2. Persistence and degradability

TIPP-EX® RAPID

Persistence and degradability Mixture based on substances which are not readily biodegradable.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Discharging into rivers and drains is forbidden. Dispose of in accordance with relevant local regulations. Destroy at an authorised site.

Additional information : The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal.

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
1139	1139	1139
14.2. UN proper shipping name		
COATING SOLUTION	COATING SOLUTION (Naphtha (petroleum), hydrotreated light)	Coating solution
Transport document description		
UN 1139 COATING SOLUTION, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1139 COATING SOLUTION (Naphtha (petroleum), hydrotreated light), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1139 Coating solution, 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640D
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E

- Transport by sea

Limited quantities (IMDG) : 5 L
Limited quantities (IMDG) : 5L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B
MFAG-No : 127;128

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

This sheet was updated (refer to the date at the top of this page). (see section(s) : 3).

Other information : Safety data sheet established by : LISAM SERVICES - TELEGIS
17 rue de la Couture F-60400 Passel
www.lisam-telegis.fr.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2

TIPP-EX® RAPID

Safety Data Sheet

according to Regulation (EC) No. 2015/830

Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	On basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product