

DATA SHEET

Box Fans

Order code	Manufacturer code	Description
37-0750	n/a	24V 60X60X25MM COOLING FAN

Box Fans	Page 1 of 2
The enclosed information is believed to be correct, Information may change 'without notice' due to	Revision A
product improvement. Users should ensure that the product is suitable for their use. E. & O. E.	04/07/2003

Sales: 01206 751166 Sales@rapidelec.co.uk Technical: 01206 835555 Tech@rapidelec.co.uk Fax: 01206 7551188 www.rapidelectronics.co.uk

60mm Low Voltage Axial Fan

Adda - AD0624HS-A70GL

Specifications

Model No.: AD0624HS-A70GL Dimensions: 60 x 60 x 25mm

Bearing Type: Sleeve, Oil Impregnated

Rated Voltage: 24.0V DC

Operating Voltage Range: 21.6 to 26.4 V DC Start-up Voltage: 17.0 V DC Nominal Ratted Current: 0.150 A +10% Max.

Rated Power: 3.6 Watt

 $\begin{array}{lll} \mbox{Rated Speed:} & 4,500 \ \mbox{RPM} \pm 10\% \\ \mbox{Air Flow:} & 23.2 \ \mbox{CFM Nominal} \\ \mbox{Static Air Pressure:} & 0.188 \ \mbox{Inch Water} \\ \mbox{Noise Level:} & 32.3 \ \mbox{dB Nominal} \\ \mbox{Motor Protection:} & \mbox{By Impedance} \end{array}$

Connection Lead Type: Wire, UL1007, AWG #24, Length 320 ±10mm (Red +, Black -)

Life Expectancy: 31,000 Hours at 25°C

Net Weight: 68 Gram.

Insulation Resistance: $>10M\Omega$ @500V DC Dielectric Strength: 1,500V AC for 60 sec.

Operating Temperature: -10°C to +70°C Storage Temperature: -40°C to +70°C

Humidity: 95% RH, 40 ±2°C per MIL-STD-202F

Material

Housing: UL94V-0 Glass Filled Polyester (P.B.T.) Fan Blade: UL94V-0 Glass Filled Polyester (P.B.T.)

Approvals: UL, CUL, CSA, TUV & CE



