

162 iS PH/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Phillips/slotted), PH/S # 2 x 100 mm
Kraftform Plus – Series 100 VDE



EAN/GTIN:	4013288160225	Dimension:	205x37x37 mm
Part no.:	05006456001	Weight:	85 g
Article no.:	162 iS PH/S	Country of origin:	CZ
		Customs tariff number:	82054000

- Insulated VDE blades for secure work at 1,000 volts
- Smooth hard zones for high speed turning, soft grip zones for high torque transfer
- Handle markings simplify finding and sorting of tools
- Hexagonal anti-roll feature against rolling away
- Reduced shaft diameter: combination profile - Phillips / slotted

Reduced blade diameter with integrated insulation protection so that even low-lying screw and spring elements can be accessed and actuated. Combination profile - slotted and Phillips particularly for jobs on terminal blocks, fuse boxes, switches and relays. Kraftform Plus handle for pleasant, ergonomic working that makes blisters and calluses a thing of the past. Hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. The anti-roll feature prevents any bothersome rolling away at the workplace.

Weblink

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_162_is_ph_s.html

Wera - 162 iS PH/S
05006456001 - 4013288160225

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de


**162 iS PH/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Phillips/slotted), PH/S # 2 x 100 mm
Kraftform Plus – Series 100 VDE**



VDE-insulated screwdriver with reduced blade diameter




Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Impact strength test



Impact strength tested at -40°C , guaranteeing safety even under extreme conditions.

Multicomponent Kraftform handle




Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces – resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any “sticking” of the hand to the handle, making rapid repositioning of the hand possible.

Prevents hand injuries



The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.

Identification marking



The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case or at the workplace.

Weblink

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_162_is_ph_s.html

Wera - 162 iS PH/S
05006456001 - 4013288160225

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

162 iS PH/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Phillips/slotted), PH/S # 2 x 100 mm
Kraftform Plus – Series 100 VDE



More variants of this product family:



mm



mm



inch

	mm	mm	inch
05006455001	1	80	98
05006456001	2	100	105

Weblink

http://products.wera.de/en/vde_tools_kraftform_plus_series_100_vde_162_is_ph_s.html

Wera - 162 iS PH/S
05006456001 - 4013288160225

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de