#### Bits for TORX® Screws







**EAN/GTIN:** 4013288034045 **Dimension:** 25x7x7 mm

Part no.: 05066102001 Weight: 4 g Article no.: 867/1 TORX® BDC Country of origin: CZ

Customs tariff 82079030

number:



- BiTorsion zone to absorb peak loads
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- 1/4" hexagon drive (Wera connecting series 1)
- "Take it easy" Tool Finder: colour coding according to profile and size

Bits for recessed TORX® screws with tiny diamond particles on the bit tip. This ensures a secure fit of the bit in the screw, reduces the contact pressure required and lowers the risk of slipping. Come with a Torsion zone — where kinetic energy is diverted from peak loads — and softer BiTorsion zone to prevent the bit tip from twisting under peak loads. This greatly extends the product service life. ¼" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.







#### Bits for TORX® Screws



#### **BiTorsion Bits**






Particularly when applications involve sensitive materials or high quality surfaces are involved, bits with a diamond coating ensure that work is done safer, faster and at lower cost.



Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill. Screwdriving become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is extended and the productivity of applications power tool significantly increased.

### Above-average service life



Even the service life of conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.

### **Diamond-coated Bits**




One of the greatest problems with power tool applications is that the conventional bit easily slips out of the head of the screw (cam-out). This often destroys both the head of the screw and the tool. High resulting costs are incurred e.g. from damaged surfaces and screw connections that can no longer be Screwdriving loosened. become safer and more economic if this problem of slipping can be minimised.

## Secure fit in the screw head




Today, the Wera diamond bit manufactured with the technology specifically developed by Wera for this application - still sets the standard in terms of resilience and functionality. Wera bits with a diamond coating ensure a secure fit of the bit in the screw head.

#### Reduced cam-out forces



The minute diamond particles applied to the tip of the tool literally "bite" into the screw and ensure an exact, anti-slip fit in the head of the screw. This secure fit protects the screw. The cam-out forces which compel the user to apply greater pressure to the screw are considerably reduced.

#### Perfect fit



Ideal for sensitive materials

#### "Take it easy" tool finder



"Take it easy" tool finder with colour coding according to profiles and size stamp - for simple and rapid accessing of the required tool.

http://products.wera.de/en/bits\_holders\_adaptors\_the\_range\_of\_wera\_bits\_bits\_for\_torx\_screws\_867\_1\_torx\_bdc.html

# 867/1 BDC TORX® bits, TX 15 x 25 mm

## Bits for TORX® Screws



## More variants of this product family:

	$\odot$	∏ Å ∀	
		mm	inch
05066100001	TX 10	25	1
05066102001	TX 15	25	1
05066104001	TX 20	25	1
05066106001	TX 25	25	1
05342920001	TX 27	25	1
05066108001	TX 30	25	1
05066110001	TX 40	25	1