


## 4mm Stackable Plug Connector Test Leads



### DESCRIPTION

A range of 4mm Stackable Plug Connector Test Leads.

### DISTINCTIVE FEATURES

- Available in Black, Red, Yellow, Green & Blue colours
- Stackable connectors
- 500mm lead length
- Nickel plated banana plug connector at each end

### APPLICATIONS

Suitable for a wide range of test applications, including connection of Test and Electrical equipment where multiple connections to the same terminal are required.

500  
mm

18  
AWG

0.75  
mm<sup>2</sup>

STACKABLE





## GENERAL SPECIFICATION

Series	Test Leads
Type	4mm Stackable Plug Test Leads
Quantity	1
Wire size/type	0.75mm <sup>2</sup>



## ELECTRICAL SPECIFICATION

Rated Voltage	30VAC/60VDC
Rated Current	Max 15A
Contact Resistance	≤0.005Ω
Insulating Resistance	≥500MΩ



## MATERIALS

Material (Contact)	Nickel plated brass
Material (Insulator)	PE
Material (Spring)	Steel
Material (Cable Insulation)	PVC





## ENVIRONMENTAL/OPERATING SPECIFICATION

Flame Retardancy (cable & plugs)	U1581L VW-1
Operating Temperature (cable & plugs)	-10°C - 80°C
RoHS	Yes



## DIMENSIONS/DRAWINGS

Units	mm - unless stated otherwise
Length (cable)	500mm
Length (overall)	589mm
Length (stackable plug)	44.5mm
Cable gauge	18 AWG
Cable outside diameter	2.8mm
Weight	16.7g



## PART NUMBER TABLE

Part number	Insulator or Body Colour	Cable Colour	EAN	UNSPSC	Country of Origin
52-4591	Black	Black	5053556006038	39121435	China
52-4592	Red	Red	5053556006045	39121435	China
52-4593	Yellow	Yellow	5053556006052	39121435	China
52-4594	Green	Green	5053556006069	39121435	China
52-4595	Blue	Blue	5053556006076	39121435	China

# R-TECH

Tried & trusted technology

**Important Notice:** This data sheet and its contents (the "Information") belong to Rapid Electronics Limited or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Rapid Electronics Limited assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Rapid Electronics Limited were aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict Rapid Electronics Limited's liability for death or personal injury resulting from its negligence.