

L-Keys for Hexagon Socket Screws



EAN/GTIN:	4013288117281	Dimension:	274x122x40 mm
Part no.:	05022721001	Weight:	715 g
Article no.:	3950/9 Hex-Plus Imperial Stainless 1	Country of origin:	CZ
		Customs tariff number:	82054000

- Solution to the extraneous rust problem: fasten stainless screws with stainless tools
- Hex-Plus allows socket head screws to live longer
- Stainless L-keys prevent extraneous rust on stainless screws
- L-keys are quickly to hand thanks to their size markings
- In a robust belt pouch

High quality L-key set out of stainless steel for imperial hexagonal socket screws by Wera. Stainless steel prevents the formation of extraneous rust. The Hex-Plus profile offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. Hexagonal ballpoint end on the long arm: the ballpoint drive profile means that it is possible to swivel the tool axis away from the screwdriving axis, thus enabling "round the corner" screwdriving. Includes a practical belt pouch.

Weblink

http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_imperial_stainless_1.html

Wera - 3950/9 Hex-Plus Imperial Stainless 1
05022721001 - 4013288117281

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Content:



3950 PKL inch	
05022710001	1 x 3/32x112
05022711001	1 x 7/64x119
05022712001	1 x 1/8x123
05022713001	1 x 9/64x130
05022714001	1 x 5/32x137
05022715001	1 x 3/16x154
05022716001	1 x 1/4x185
05022717001	1 x 5/16x195
05022718001	1 x 3/8x224

L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened – and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

Stainless L-keys



Stainless L-keys are hardened to the same strength as conventional (carbon) steel tools, and prevent extraenous rust forming.

Vacuum ice-hardened



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Weblink

http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_imperial_stainless_1.html

Wera - 3950/9 Hex-Plus Imperial Stainless 1
05022721001 - 4013288117281

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Size identification



The size of each L-keys has been engraved by a laser. In addition SPKL L-keys have a colour coding according to sizes – for simple and rapid accessing of the required tool. Making it easy to find the right tool.

Weblink

http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_3950_9_hex-plus_imperial_stainless_1.html

Wera - 3950/9 Hex-Plus Imperial Stainless 1
05022721001 - 4013288117281

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de