



EAN/GTIN:	4013288108333	Dimension:	185x37x37 mm
Part no.:	05029464001	Weight:	104 g
Article no.:	395 H0	Country of origin:	CZ
		Customs tariff number:	82054000

- Nutsetter for hexagon head screws
- Multi-component Kraftform handle for fast and ergonomic screwdriving
- Handle markings simplify finding and sorting of tools
- Hexagonal anti-roll feature against rolling away
- Hollow shaft for protruding threaded rods, chrome-plated

High quality nutsetter with hollow shaft by Wera. Hollow shaft for the fastening of threaded rods; only then can the threaded rod with nut slip into the hollow shaft. Multi-component Kraftform handle for high working speeds and particularly ergonomic screwdriving. Kraftform Plus: hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. Hexagonal anti-roll feature prevents any rolling away and handle markings make for simplified finding and sorting of the tool; for hexagon head screws.

Weblink

http://products.wera.de/en/screwdrivers_kraftform_plus__series_300_395_ho.html


Wera - 395 H0
05029464001 - 4013288108333

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Hollow shaft for protruding threaded rods



Kraftform Plus screwdrivers – ergonomics you can grasp. They relieve the entire hand-arm system even when used intensively. Along with other technical and product advantages such as the Lasertip for a secure fit in the screw head, Kraftform screwdrivers are the ideal choice whenever manual screwdriving jobs are concerned.



A screwdriver with a hollow shaft is needed whenever there are screwdriving jobs involving threaded rods i.e. the threaded rod through the nut can slip into the hollow shaft of the screwdriver.

Kraftform



The basic idea for the prototype of the Kraftform handle – that the hand should dictate the design – has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.

Large contact area



The large contact area – with particularly high friction to the soft zones – results in high torque transfer without any bruising from the edges.

Non-roll feature



The hexagonal non-roll feature prevents any rolling away at the workplace.

Identification marking



The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case or at the workplace.

Weblink

http://products.wera.de/en/screwdrivers_kraftform_plus_series_300_395_ho.html

Wera - 395 H0

05029464001 - 4013288108333

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de

More variants of this product family:

						
	mm	inch	mm	mm	mm	inch
05029460001	5.0		90	98	7.2	3 35/64
05029461001	5.5		90	98	7.2	3 35/64
05029462001	6.0		90	98	7.2	3 35/64
05029463001	7.0		90	105	7.2	3 35/64
05029464001	8.0		90	105	9.3	3 35/64
05029465001	10.0		90	112	9.3	3 35/64
05029466001	13.0		90	112	11.0	3 35/64
05029501001		3/16"	90	98	7.2	3 35/64
05029502001		1/4	90	98	7.2	3 35/64
05029503001		5/16"	90	105	9.3	3 35/64
05029504001		11/32"	90	105	9.3	3 35/64
05029505001		3/8"	90	112	9.3	3 35/64
05029506001		7/16"	90	112	11.0	3 35/64
05029507001		1/2"	90	112	11.0	3 35/64

Weblink

http://products.wera.de/en/screwdrivers_kraftform_plus__series_300_395_ho.html

Wera - 395 H0

05029464001 - 4013288108333

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de