Series Soft-Faced Hammers





EAN/GTIN: 4013288001351 **Dimension:** 250x75x22 mm

 Part no.:
 05000305001
 Weight:
 208 g

 Article no.:
 101
 Country of origin:
 CZ

Customs tariff 82052000

number:

- Powerful hammering with surface protection
- Soft-face hammers with hammer head out of nylon
- Suitable for sheet metal and renovation work as well as for tent, hall and fair booth construction jobs
- Inseparable and secure connection between the hammer handle and head
- High-quality ashwood handle

Wera soft-face hammers. Double-sided conical design for a secure, inseparable connection between the hammer handle and head. The hammer head is made out of nylon; the handle out of high quality ash wood. Diverse applications thanks to the interchangeable soft-face hammer heads. Suitable for sheet metal and renovation work as well as for tent, hall and fair booth construction jobs.

Series Soft-Faced Hammers



Soft-faced hammers







High quality ash wood





Powerful hammering with surface protection.

They come in soft, medium and hard designs for a wide range of applications from universal use to splinter-free applications on sharpedged work pieces.



Powerful work is ensured with handles out of high quality ash wood.

Colour guidance system




Colour guidance system • Yellow = Repair/maintenance work with high demands • Red = Suitable for hammering sharp-edged work pieces; bodyshops, automotive, engineering • White = Suitable for metal processing and removal of dents; tent, large building and exhibition stand construction

Secure



The double-sided conical design creates an unbreakable and secure link between the handle and head of the hammer.

Versatile



Versatile use thanks to the soft faced heads that can retrospectively fitted.

101 Soft-faced hammer with nylon head sections, # 1 x 22 mm

Series Soft-Faced Hammers



More variants of this product family:







nm

n	m	

05000305001	1	22	75	250.0
05000310001	2	27	90	265.0
05000315001	3	32	95	280.0
05000320001	4	35	105	290.0
05000325001	5	40	110	320.0
05000330001	6	50	115	340.0
05000335001	7	60	135	380.0