



# tesa® Professional 53988

## Soft PVC Insulation Tape

### Product Information

Soft PVC Insulation Tape for insulating and marking wires

### Product Description

The electric insulation tape tesaflex 53988 is a reliable helper for electricians, mechanics and other handymen. It is characterised by its relatively thick base material, a high degree of flexibility and a very good adhesive performance (even on steel and at low temperatures). The PVC insulation tape is not only suited for insulating and marking wires but also for repairs and bundling. Since it is available in many colours – red, blue, brown, black, white, grey, green, yellow and yellow-green - it can also be used as a marking adhesive tape. tesaflex 53988 is certified according to all relevant standards and can be used easily.

### Application Fields

- Ideally suited for electrical applications, e.g. insulating or marking wires
- Certified according to IEC 60454-3-1 (VDE, IMQ, SEMKO), VOC-certified, RoHS 2.0 and REACH conform
- Thick backing material (150 µm)
- High dielectric breakdown voltage (7.000 V)
- Heat-resistant up to +90° C
- Available in many different colours and dimensions

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | soft PVC       | • Total thickness | 150 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                       |         |                       |      |
|-----------------------|---------|-----------------------|------|
| • Elongation at break | 240 %   | • Humidity resistance | good |
| • Tensile strength    | 25 N/cm |                       |      |



# tesa® Professional 53988 Soft PVC Insulation Tape

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53988>