


Evolution XPC OFC Professional 1 Pair



PRODUCT OVERVIEW

Part Number:	301-031 / 301-032 / 301-033 / 301-035
Product Description:	Evolution XPC OFC Professional 1 Pair


CABLE CONSTRUCTION

Conductor:	1 Pair Construction 7 x 0.2 mm 24AWG
Insulation:	Material: XLPE Insulation Colour: Red & Blue
Shield:	Layer 1 Aluminium /Polyester Tape Construction Z Fold Braiding Coverage 100% Construction (stranded) TC 7 0.2 mm
Jacket:	Material : Soft Flexible PVC Composite Thickness: 0.8 mm Diameter: 3.5 mm Jacket Colour : Black , Blue, Red & White
Marking:	Black: Evolution XPC OFC Professional 1 Pair 301-031 Blue: Evolution XPC OFC Professional 1 Pair 301-032 Red: Evolution XPC OFC Professional 1 Pair 301-033 White: Evolution XPC OFC Professional 1 Pair 301-035
Reel Lengths :	100 m / 500 m Wooden Drum



Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd, Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom
tel • +44 (0)208 238 7800 fax • +44 (0)208 238 7801 email • sales@directcablesystems.com Registered in UK No. 3409274



ELECTRICAL CHARACTERISTICS at 20°C

Conductor Resistance:	85 Ω /m @ 20°C
Insulation Resistance:	10 G Ω /Km
Operating Temperature	-20°C to +70°C
Capacitance (pF/m):	85 pF/m core to core 130 pF/m core to screen



Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd, Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom
tel • +44 (0)208 238 7800 fax • +44 (0)208 238 7801 email • sales@directcablesystems.com Registered in UK No. 3409274