Fax: 0049-(0)7223-284-245



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU por
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0 email: info@uhu.boltongroup.de

- · Further information obtainable from: CRD
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cyclene

· Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

· Dangerous components:		
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-005	Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cyclene  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	50-80%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41-XXXX	cyclohexane Flam. Liq. 2, H225; S Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	<1,0%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

(Contd. of page 2)

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
  Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

	· Ingredients with limit values that require monitoring at the workplace:		
Γ	110-82-7 cyclohexane		
	IOELV (EU)	Long-term value: 700 mg/m³, 200 ppm	
	AGW (Germany)	Long-term value: 700 mg/m³, 200 ppm 4(II);DFG, EU	
Ī	· DNELs		

Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cyclene		
Oral	Verbraucher, Verschlucken Langzeitige Exposition	149 mg/kg bw/day (-)
Dermal	Verbraucher, Hautkontakt Langzeitiege Exposition	149 mg/kg bw/day (-)
Inhalative	Verbraucher, Einatmen Langzeitige Exposition	477 mg/m³ (-)

(Contd. on page 4)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

	(Contd. of page 3)
· PNECs	
Kohlenwass	erstoffe, C7, n-Alkane, Isoalkane, Cyclene
Süßwasser	(-)
Meerwasser	(-)
Boden	(-)
· Ingredients	with biological limit values:
110-82-7 cyc	clohexane
BGW (Germa	any) 150 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: bei Langzeitexposition: Nach mehreren vorangegangenen Schichten, Expositionsende bzw. Schichtende Parameter: 1,2-Cyclohexandiol (nach Hydrolyse)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical a	nnd chemical properties	
· Appearance:		
Form:	Fluid	
Colour:	Yellowish	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 83 °C	
· Flash point:	-1 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	0 °C	
· Decomposition temperature:	Not determined.	
		(Contd. on page 5)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

	(Contd. of page	
· Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
Explosion limits:		
Lower:	0,0 Vol %	
Upper:	0,0 Vol %	
· Vapour pressure at 20 °C:	48 hPa	
Density at 20 °C:	0,80529 g/cm³	
Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic at 20 °C:	13000 mPas	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	69,2 %	
VOC (EC)	69,19 %	
Solids content:	30,8 %	
9.2 Other information	All relevant physical data were determined for th	
	mixture. All non determined data are not measurably	
	not relevant for the characterization of the mixture.	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### 110-82-7 cyclohexane

Oral LD50 | 12705 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

(Contd. of page 5)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

•	waste catalogue
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1133
· 14.2 UN proper shipping name	
ADR	1133 ADHESIVES, ENVIRONMENTALLY
	HAZARDOUS, special provision 640H 1133 KLEBSTOFFE, UMWELTGEFÄHRDEND
	1133 KLEBSTÖFFE, UMWELTGEFÄHRDEND
	Sondervorschrift 640H
· IMDG	ADHESIVES
·IATA	Adhesives

(Contd. on page 7)



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR · Class 3 Flammable liquids. · Label · IMDG, IATA 3 Flammable liquids. · Class · Label · 14.4 Packing group III· ADR, IMDG, IATA · 14.5 Environmental hazards: Yes · Marine pollutant: · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Flammable liquids. · Danger code (Kemler): · EMS Number: F-E,S-D · Stowage Category · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 · Transport category Tunnel restriction code Ε · IMDG · Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 · UN "Model Regulation": UN 1133 ADHESIVES, SPECIAL PROVISION 640H, 3, III, ENVIRONMENTALLY HAZARDOUS



Printing date 04.02.2016 Version number 25 Revision: 04.02.2016

Trade name: UHU por

(Contd. of page 7)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing MSDS: CRD

#### · Contact:

Frau A. Liar,

Herr Dr. C. Hanf

## Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.