

METSEPM5111

PM5111 powermeter w modbus - upto 15th H - 1DO
33alarms - flush - MID



Main

Range	PowerLogic
Product name	PowerLogic PM5000
Device short name	PM5111
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 15th harmonic
Device application	Power monitoring
Type of measurement	Voltage Current Frequency Power factor Energy Active and reactive power
[Us] rated supply voltage	100...415 V AC (45...65 Hz) 125...250 V DC
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
Poles description	1P + N 3P 3P + N
Power consumption in VA	10 VA at 415 V
Display type	Backlit LCD
Display resolution	128 x 128 pixels
Sampling rate	64 samples/cycle
Measurement current	10 mA...9 A
Analogue input type	Current (impedance 0.3 mOhm) Voltage (impedance 5 MOhm)
Measurement voltage	35...690 V AC 45...65 Hz between phases 20...400 V AC 45...65 Hz between phase and neutral
Frequency measurement range	45...65 Hz
Number of inputs	0
Measurement accuracy	+/- 0.5 % active energy +/- 2 % reactive energy +/- 0.5 % active power +/- 0.5 % apparent power +/- 0.05 % frequency +/- 0.005 % power factor +/- 0.5 % current +/- 0.5 % voltage
Accuracy class	Class 0.5S (active energy according to IEC 62053-22)
Number of outputs	1 digital
Communication port protocol	Modbus RTU and ASCII 2 wires, : 9.6, 19.2 and 38.4 kbauds, even/odd or none, insulation: 2500 V JBUS
Communication port support	RS485
Data recording	Min/max of instantaneous values

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

	Time stamping
Mounting mode	Flush-mounted
Mounting support	Framework
Standards	IEC 60529 IEC 61557-12 IEC 62053-22 EN 50470-1 EN 50470-3 UL 61010-1 IEC 62053-24
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 MID conforming to EN 50470-1 MID conforming to EN 50470-3
Width	96 mm
Depth	72 mm
Height	96 mm
Product weight	380 g

Environment

electromagnetic compatibility	<ul style="list-style-type: none"> • conducted and radiated emissions class class B, conforming to EN 55022 • limits for harmonic current emissions class class A, conforming to IEC 61000-3-2 • electrostatic discharge class level 4, conforming to IEC 61000-4-2 • conducted RF disturbances class level 3, conforming to IEC 61000-4-6 • magnetic field at power frequency class level 4, conforming to IEC 61000-4-8
IP degree of protection	IP52 (front) conforming to IEC 60529 IP30 (body) conforming to IEC 60529
relative humidity	5...95 % 50 °C
pollution degree	2
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...85 °C
operating altitude	2000 m

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available