

Safety data sheet

according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

SECTION 1: IDENTIFICATION OF SUBSTANCE/MIXTURE AND OF COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Under Seal Spray 500ml

ref: SGUS1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Surface protection

Aerosol coating

1.3. Details of the supplier of the safety data sheet

Silverhook Ltd
Unit 14 Bates Road
Harold Wood, Romford, London
RM3 0JH
Tel.: +44 (0) 1708330500
Fax.: +44 (0) 1708330504
Email: 522@silverhook.co.uk
Responsible person email: 522@silverhook.co.uk

1.4. Emergency telephone number

+44 (0) 1708330500 (during office hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1
H304 May be fatal if swallowed and enters airways.

2.2. Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02



GHS07



GHS09

Signal word Danger

Hazard-determining components of labelling

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

butanone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

2.3. Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Description: Mixture of active substance with propellant

Dangerous components:		
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Consisting of: 98-82-8 isopropylbenzene (<0.099%); 71-43-2 benzene (<0.1%)	10-<25%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 8052-42-4 EINECS: 232-490-9 Reg.nr.: 01-2119480172-44	Asphalt	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane	10-<25%
	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	10-<25%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: UK-01-1376353405-7-0007	butanone	2.5-<10%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	

Safety data sheet

according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	2.5-<10%
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K)	2.5-<10%
	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	1-<2.5%
	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol	0.1-<1%
	Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	

Additional information

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

After inhalation

Supply fresh air; consult doctor in case of complaints.

After skin contact

Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water.

After swallowing

Do not induce vomiting; call for medical help immediately.

Information for doctor

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing agents

Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

Protective equipment

Mount respiratory protective device.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3. Methods and material for containment and cleaning up

Ensure adequate ventilation.

6.4. Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Safety data sheet

according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility

Observe official regulations on storing packagings with pressurised containers.

Further information about storage conditions

Store in cool, dry conditions in well-sealed receptacles.

Protect from heat and direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see Section 7.

· Ingredients with limit values that require monitoring at the workplace:

8052-42-4 Asphalt

WEL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³
-----	--

74-98-6 propane

OEL	Long-term value: 1800 mg/m ³ , 1000 ppm Additioneel ingevuld tbv klant voor Hfdst3 SDS
-----	--

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

OEL	Long-term value: 2400 mg/m ³ , 1000 ppm Additioneel ingevuld obv klant voor Hfdst 3 SDS
-----	---

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

· Regulatory information WEL: EH40/2020

· DNELs

128601-23-0 Hydrocarbons,C9,aromatics

Oral	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
		25 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	32 mg/m ³ (Consumer)

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

		100 mg/m ³ (Worker)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	208 mg/kg bw/day (Worker)
		185 mg/m ³ (Consumer)
		871 mg/m ³ (Worker)
78-93-3 butanone		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	1161 mg/kg bw/day (Worker)
		106 mg/m ³ (Consumer)
		600 mg/m ³ (Worker)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	773 mg/kg bw/day (Worker)
		608 mg/m ³ (Consumer)
		2035 mg/m ³ (Worker)
Ingredients with biological limit values:		
78-93-3 butanone		
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	

Regulatory information BMGV: EH40/2011

Additional information: The lists valid during the making were used as basis.

Personal protective equipment

General protective and hygienic measures

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- General ventilation

Respiratory protection

- Use suitable respiratory protective device in case of insufficient ventilation.
- Filter A2/P2

Protection of hands



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance glove material cannot be calculated in advance and has therefore to be checked prior to the application of the

Nitrile rubber, NBR

Recommended thickness of the material: □ 0.5 mm

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection

Safety glasses



Tightly sealed goggles

Body protection

Use protective suit. (EN-13034/6)

Fully skin-covering anti-static, chemical- and oil-resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

Limitation and supervision of exposure into the environment

Use an appropriate container to avoid environmental pollution.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

General Information

Colour	According to product specification
Odour	Characteristic
Odour threshold	Not determined.
pH-value	Mixture is non-polar/aprotic.
Melting point/freezing point	Undetermined.
Initial boiling point and boiling range	-44.5 °C
Flash point	-97 °C
Flammability	Not applicable.
Ignition Temperature	270 °C
Ignition temperature	Product is not selfigniting.
Explosive properties	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits	
Lower	0.6 Vol %
Upper	11.5 Vol %
Vapour pressure at 20 °C	4900 hPa
Vapor Pressure at 50 °C	8500 hPa
Density at 20 °C	0.748 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with water	Fully miscible.
Partition coefficient: n-octanol/water	Not determined.
Viscosity	
Dynamic	7.500 - 10.500 Brookfield sp3 6 rpm 4.000 - 6000 Brookfield sp3 12 rpm
Kinematic	Not determined.
Organic solvents	74.8 %
Solids content	25.2 %

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No further relevant information available.

10.2. Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

128601-23-0 Hydrocarbons,C9,aromatics

Oral	LD50	3492 mg/kg (Rat)
Dermal	LD50	>3160 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>6193 mg/l (Rat) (Acute Inhalation Toxicity)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5000 mg/kg (Rat) (Acute Oral Toxicity)
Dermal	LD50	3160 mg/kg (Rabbit) (Acute Dermal Toxicity)
Inhalative	LC50 (4h)	>4951 mg/l (Rat)
	LC50 (4h)	4951 mg/m3 (Rat)

78-93-3 butanone

Oral	LD50	>2193 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit)
		5000 mg/kg (Rabbit)
Inhalative	LC50 (4h)	34 mg/l (Rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes,cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (Rat)
Dermal	LD50	>2920 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>25 mg/l (Rat)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Aquatic toxicity:

128601-23-0 Hydrocarbons,C9,aromatics

NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3.2 mg/l (Daphnia magna)
LL50 (96h)	9.2 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

EL0 (48h)	1000 mg/l (Daphnia magna)
NOELR (72h)	100 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata)

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

LL50 (96h)	>1000 mg/l (Onc)
78-93-3 butanone	
LC50 (96h)	2993 mg/l (Pimephales promelas)
EC50 (48h)	308 mg/l (Daphnia magna)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11.4 mg/l (Oncorhynchus mykiss)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)

12.2. Persistence and degradability

Not easily biodegradable

Behaviour in environmental systems

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

Ecotoxicological effects

Remark Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5. Results of PBT and vPvB assessment

PBT Not applicable.

vPvB Not applicable.

12.6. Other adverse effects

No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging

Recommendation

Disposal must be made according to official regulations.

Recommended cleansing agents

Water, if necessary together with cleansing agents.

SECTION 14: TRANSPORT INFORMATION

UN-Number

ADR, ADN, IMDG, IATA

UN1950

UN proper shipping name

ADR, ADN

IMDG

IATA

UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS






AEROSOLS, MARINE POLLUTANT

AEROSOLS, flammable

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

Transport hazard class(es) ADR <div style="display: flex; align-items: center; gap: 10px;">   </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div>Class Label</div> <div>2 5F Gases. 2.1</div> </div>	
ADN ADN/R Class: 2 5F	
IMDG <div style="display: flex; align-items: center; gap: 10px;">   </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div>Class Label</div> <div>2.1 Gases. 2.1</div> </div>	
IATA <div style="display: flex; align-items: center; gap: 10px;">  </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div>Class Label</div> <div>2.1 Gases. 2.1</div> </div>	
Packing group ADR, IMDG, IATA Void	
Environmental hazards Marine pollutant Special marking (ADR)	
Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)	
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code Segregation Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.	

B

Safety data sheet according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

Transport/Additional information:		
ADR		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	Not permitted as Excepted Quantity
Transport category	2	
Tunnel restriction code	D	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

Regulated explosives precursors
None of the ingredients is listed.
Regulated poisons
None of the ingredients is listed.
Reportable explosives precursors
None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations:

Breakdown regulations:

Class	Share in %
NK	50-<75

VOC-CH 74.76 %

VOC-EU 559.2 g/l

Danish MAL Code 5-3

15.2. Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

Safety data sheet

according to UK REACH

Printing date: 26.11.2024

Revision: 14.11.2024

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards,
Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code: Måleteknisk Arbejdshygienisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Gas 1A: Flammable gases –
Category 1A Aerosol 1: Aerosols –
Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Disclaimer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.