

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML
- **Article number:** MX6002
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Coatings and paints, thinners and paint removers
- **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
European Aerosols B.V.*
Wolfraamweg 2
NL-8471 XC Wolvega
The Netherlands
Tel : +31 (0)561 694400
e-mail: sds-nl@european-aerosols.com

European Aerosols Ltd.
Wilberforce House
Station Road
London NW4 4QE,
phone no. +44 1223 790332

*Formerly known as Motip Dupli B.V.
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

acetone

ethyl acetate

n-butyl acetate

2-methoxy-1-methylethyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	Flam. Liq. 2, H225	
Index number: 606-001-00-8	Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49	EUH066	

(Contd. on page 3)

GB

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 2)

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	20-<25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 9004-70-0	cellulose nitrate ⚠ Expl. 1.1, H201	<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide substance with a Community workplace exposure limit	<2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥1-<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%

Additional information:

CAS 9004-70-0: GB CLP Note T

In accordance with the current Annex II of UK REACH, the concentration of the substances contained in the mixture are specified. For the classification of aerosols, the values used for calculation may differ. For the wording of the listed hazard phrases refer to section 16.

*

SECTION 4: First aid measures**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³
*total inhalable **respirable

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm
Sk

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

· DNELs

67-64-1 acetone

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m ³ (Worker, acute local)
	DNEL	1210 mg/m ³ (Worker, longterm systemic)
	DNEL	200 mg/m ³ (Consumer, longterm systemic)
	DNEL	60 mg/m ³

141-78-6 ethyl acetate

Oral	DNEL	4.5 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	63 mg/kg /per day (Worker, longterm systemic)
	DNEL	37 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	734 mg/m ³ /200 ppm (Worker, longterm systemic)
	DNEL	1468 mg/m ³ /400 ppm (Worker, acute systemic)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 5)

	DNEL	734 mg/m3 /200 ppm (Worker, longterm local)
	DNEL	1468 mg/m3 /400 ppm (Worker, acute local)
	DNEL	367 mg/m3 /100 ppm (Consumer, longterm systemic)
	DNEL	734 mg/m3 /200 ppm (Consumer; acute systemic)
	DNEL	367 mg/m3 /100 ppm (Consumer, longterm local)
	DNEL	734 mg/m3 /200 ppm (Consumer, acute local)

123-86-4 n-butyl acetate

Oral	DNEL	2 mg/kg /per day (Consumer, longterm systemic)
	DNEL	2 mg/kg /per day (Consumer, acute systemic)
Dermal	DNEL	11 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Worker, acute systemic)
	DNEL	6 mg/kg /per day (Consumer, longterm systemic)
	DNEL	6 mg/kg /per day (Consumer, acute systemic)
Inhalative	DNEL	300 mg/m3 (Worker, longterm systemic)
	DNEL	600 mg/m3 (Worker, acute systemic)
	DNEL	300 mg/m3 (Worker, longterm local)
	DNEL	600 mg/m3 (Worker, acute local)
	DNEL	35.7 mg/m3 (Consumer, longterm systemic)
	DNEL	300 mg/m3 (Consumer; acute systemic)
	DNEL	35.7 mg/m3 (Consumer, longterm local)

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m3 (Worker, longterm systemic)
	DNEL	33 mg/m3 (Consumer, longterm systemic)

71-36-3 butan-1-ol

Oral	DNEL	3.125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	310 mg/m3 (Worker, longterm local)
	DNEL	55 mg/m3 (Consumer, longterm local)

67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	888 mg/kg /per day (Worker, longterm systemic)
	DNEL	319 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	500 mg/m3 (Worker, longterm systemic)
	DNEL	89 mg/m3 (Consumer, longterm systemic)

· PNECs**67-64-1 acetone**

PNEC	10.6 mg/l (Freshwater)
PNEC	1.06 mg/l (Seawater)
PNEC	21 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 6)

123-86-4 n-butyl acetate

PNEC	0.18 mg/l (Freshwater)
PNEC	0.018 mg/l (Seawater)
PNEC	0.36 mg/l (Sporadic release)
PNEC	35.6 mg/l (Sewage treatment plant)
PNEC	0.981 mg/kg (Freshwater sediment)
PNEC	0.0981 mg/kg (Seawater sediment)
PNEC	0.0903 mg/kg (Soil)

108-65-6 2-methoxy-1-methylethyl acetate

PNEC	0.635 mg/l (Freshwater)
PNEC	0.064 mg/l (Seawater)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	3.29 mg/kg (Freshwater sediment)
PNEC	0.329 mg/kg (Seawater sediment)
PNEC	0.29 mg/kg (Soil)

71-36-3 butan-1-ol

PNEC	0.082 mg/l (Freshwater)
PNEC	0.0082 mg/l (Seawater)
PNEC	2.25 mg/l (Sporadic release)
PNEC	2476 mg/l (Sewage treatment plant)
PNEC	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
PNEC	0.015 mg/kg (Soil)

67-63-0 propan-2-ol

PNEC	140.9 mg/l (Freshwater)
PNEC	140.9 mg/l (Seawater)
PNEC	140.9 mg/l (Sporadic release)
PNEC	2251 mg/l (Sewage treatment plant)
PNEC	552 mg/kg (Freshwater sediment)
PNEC	552 mg/kg (Seawater sediment)

• **Additional information:** The lists valid during the making were used as basis.

• **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the eyes and skin.
 - Avoid contact with the eyes.

• **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 7)

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Aerosol

· Colour:

Different according to colouring

· Odour:

Solvent-like

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

· Flammability

Not applicable.

· Lower and upper explosion limit

· Lower:

2.6 Vol % (67-64-1 acetone)

· Upper:

26.2 Vol % (115-10-6 dimethyl ether)

· Flash point:

Not applicable, as aerosol.

· Auto-ignition temperature:

240 °C (464 °F)

· Decomposition temperature:

Not determined.

· pH

Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity

Not determined.

· Dynamic:

Not determined.

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure at 20 °C (68 °F):

4000 hPa (3000.2 mm Hg)

· Density and/or relative density

· Density at 20 °C (68 °F):

0.7 g/cm³ (5.8 lbs/gal)

· Relative density

Not determined.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 8)

· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	90.2 %
· Water:	0.3 %
· VOC (EC)	---
	676.0 g/l
· VOC-EU%	90.20 %
· Solids content:	10.5 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 10)

GB

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 9)

· LD/LC50 values relevant for classification:**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)

141-78-6 ethyl acetate

Oral	LD50	>18000 mg/kg (rab)
Dermal	LD50	5620 mg/kg (rat)
Inhalative	LC50 / 4 h	1600 mg/m3 (rat)

123-86-4 n-butyl acetate

Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)

71-36-3 butan-1-ol

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****67-64-1 acetone**

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 10)

LC50 / 96 h	>4000 mg/l (fish)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)
71-36-3 butan-1-ol	
LC50 / 96 h	1376 mg/l (fish)
67-63-0 propan-2-ol	
LC50/96h	9640 mg/l (pimephales promelas; 96h)
LC50 / 24 h	9714 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

*

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.

(Contd. on page 12)

GB

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 11)

· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases.
· **Label** 2.1

· **14.4 Packing group**
· **ADR, IMDG, IATA** not regulated

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Gases.
· **Hazard identification number (Kemler code):** -
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
Code: E0
Not permitted as Excepted Quantity
· **Transport category** 2
· **Tunnel restriction code** D

· **IMDG**
· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
Code: E0
Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

GB

(Contd. on page 13)

Safety data sheet according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 12)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

67-64-1 acetone

Listed

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P3a** FLAMMABLE AEROSOLS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

The propellant gas is not taken into account when determining the classification of the mixture for health and the environment.

- **Department issuing SDS:** R&D legislation and regulatory advisor

- **Contact:** e-mail: sds-nl@european-aerosols.com

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 14)

Safety data sheet
according to UK REACH

Printing date 05.11.2025

Version number 11 (replaces version 10)

Revision: 08.04.2025

Trade name: MAXI COLOR SPRAY PAINT RAL 6002 GL 400 ML

(Contd. of page 13)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Expl. 1.1: Explosives – Division 1.1
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

GB