

Epson EB-PU2116W Large venue projector 16000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA64940

Product name : EB-PU2116W

3LCD, 1,03 inch, WUXGA, 4K, 16:10, 1.083 W, 24,3 kg

Epson EB-PU2116W Large venue projector 16000 ANSI lumens 3LCD WUXGA (1920x1200) White:

Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

Flexibility

The EB-PU2116W's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes improved dustproofing as the hermetically sealed optical engine, and laser light source unit, prevent dust contamination to ensure enhanced durability.



Projector		Features	
Smart projector *	✗	Noise level (economic mode)	34 dB
Projector brightness *	16000 ANSI lumens	Projection modes	Ceiling
Projection technology *	3LCD	On Screen Display (OSD)	✓
Projector native resolution *	WUXGA (1920x1200)	Noise level *	38 dB
Contrast ratio (typical) *	2000:1	Country of origin	China
Native aspect ratio *	16:10	High Dynamic Range (HDR) supported	✓
Number of colours	1.07 billion colours	Password protection	✓
Projector brightness (economic mode)	11200 ANSI lumens	Multimedia	
Keystone correction, horizontal	18°	Built-in speaker(s) *	✗
Keystone correction, vertical	60°	Design	
Matrix size	2.62 cm (1.03")	Product type *	Large venue projector
White light output	16000 ANSI lumens	Product colour *	White
Colour light output	16000 ANSI lumens	Placement	Ceiling, Desktop, Flying frame
Heat dissipation	3682 BTU/h	Cable lock slot	✓
Light source		Cable lock slot type	Kensington
Light source type *	Laser	Display	
Service life of light source *	20000 h	Built-in display *	✗
Service life of light source (economic mode)	30000 h	Power	
Light source brightness	16000 lm	Power source *	AC
Lens system		Power consumption (typical) *	1083 W
Focus *	Auto	Power consumption (standby) *	0.4 W
Focal length range	varies by lens	Power consumption (economy mode)	773 W
Zoom capability	✓	AC input voltage	200-240 V
Zoom type	Auto	AC input frequency	50 - 60 Hz
Zoom ratio	1.6:1	Software	
Throw ratio	0.35 - 7.41:1	Software support	via: AMX, Crestron (Network), Extron
Vertical lens shift range	-60 - 60%		
Lens position memory	10		
Interchangeable lens	✓		

Video		Operational conditions	
Full HD *	✓	Storage temperature (T-T)	-10 - 60 °C
3D *	✗	Operating relative humidity (H-H)	20 - 80%
Video processing	10 bit	Storage relative humidity (H-H)	10 - 90%
Video colour modes	Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709	Weight & dimensions	
Ports & interfaces		Width	586 mm
HDBaseT port	✓	Depth	492 mm
Service port type	USB Type-B	Height	218 mm
USB 2.0 ports quantity	2	Weight *	24.3 kg
USB 2.0 Type-A ports quantity	2	Package weight	0 g
Serial interface type *	RS-232C	Packaging content	
VGA (D-Sub) ports quantity *	1	Remote control included *	✓
HDMI ports quantity *	1	Batteries included	✓
DVI port *	✓	Cables included	AC
AC (power) in	✓	Manual	✓
Network		Warranty card	✓
Smart TV *	✗	WLAN adapter included	✓
Ethernet LAN *	✓	Packaging content	Cable cover, Lens connector cap, Power cable, Remote control incl. batteries, User manual, Warranty document
Wi-Fi *	✓	Bundled software	Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Content Manager, Epson Projektor Management, Epson Projektor Professional Tool
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Logistics data	
Storage		Quantity per pack	1 pc(s)
Card reader integrated *	✗	Harmonized System (HS) code	85286200
Features		Other features	
Interactive *	✗	Supported network protocols	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946703176

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.