

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013

PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

RACING CHAIN LUBE 250ML

Art.: 1508

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

PROC13 - Treatment of articles by dipping and pouring

PROC17 - Lubrication at high energy conditions and in partly open process

PROC18 - Greasing at high energy conditions

PROC19 - Hand-mixing with intimate contact and only PPE available

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 2 - Formulation of preparations

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 5 - Industrial use resulting in inclusion into or onto a matrix

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8c - Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

ERC 8f - Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr

Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

SECTION 2: Hazards identification



Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

F+,Extremely flammable

R66

R67

N, Dangerous for the environment, R51-53

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)





Symbols: F+/N Indications of danger: Extremely flammable

Dangerous for the environment

R-phrases:

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

23 Do not breathe vapour/spray.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additions:

Pressurized container:

protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC)

Danger of bursting (explosion) when heated

When using: development of explosive vapour/air mixture possible.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a. 3.2 Mixture

Pentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-006-00-1
EINECS, ELINCS, NLP	203-692-4
CAS	CAS 109-66-0



Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

content %	10-20
Classification according to Directive 67/548/EEC	Extremely flammable, F+, R12
	Dangerous for the environment, N, R51
	Dangerous for the environment, R53
	Harmful, Xn, R65
	R66
	R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 2, H411
	Asp. Tox. 1, H304
	STOT SE 3, H336
	Flam. Liq. 2, H225

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP	921-024-6 (REACH-IT List-No.)
CAS	CAS
content %	10-<20
Classification according to Directive 67/548/EEC	Highly flammable, F, R11
	Irritant, Xi, R38
	Dangerous for the environment, N, R51
	Dangerous for the environment, R53
	Harmful, Xn, R65
	R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Asp. Tox. 1, H304
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	270-128-1
CAS	CAS 68411-46-1
content %	0,1-<1
Classification according to Directive 67/548/EEC	Dangerous for the environment, N, R51
	Dangerous for the environment, R53
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 2, H411

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Keep Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing



Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Headaches

Effects/damages the central nervous system

With long-term contact:
Dermatitis (skin inflammation)

Drying of the skin. Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Water jet spray

CO2

Extinction powder

Foam

Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.



Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Pentane					Content %:10-20
WEL-TWA: 600 ppm (1800 mg/	m3) (WEL), 1000	WEL-STEL:				
ppm (3000 mg/m3) (EU)						
BMGV:				Other information:	-	
Chemical Name	Hydrocarbons, C6-	.C7 n-alkanes i	snalkanes cyclics	< 5% n-hexane		Content %:10-<20
WEL-TWA: 800 mg/m3	Trydrodarbone, Co	WEL-STEL:	<u>, , , , , , , , , , , , , , , , , , , </u>	C 0 /0 II HEXAIIC	Τ	OOMON 70.10 \20
		WLL-SILL.				
BMGV:				Other information:	-	
Chemical Name	Propane					Content %:
WEL-TWA: 1000 ppm (ACGIH)		WEL-STEL:				
BMGV:				Other information:	-	
Chemical Name	Butane					Content %:
WEL-TWA: 600 ppm (1450 mg/	m3)	WEL-STEL:	750 ppm (1810 m	g/m3)		
BMGV:				Other information:	-	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
Workers / employees	Human - dermal	Long term, systemic	DNEL	300	mg/kg	
		effects			bw/day	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	2035	mg/m3	
		effects				



(GR)

Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Consumer	Human - dermal	Long term, systemic effects	DNEL	149	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	447	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	149	mg/kg bw/day	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

n.a.

9.1 Information on basic physical and chemical properties

Physical state: Aerosol, Substance: Liquid

Not determined Colour: Odour: Characteristic Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Not determined

Initial boiling point and boiling range:

Flash point:

Evaporation rate: Not determined



Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: Not determined Bulk density: Not determined Not determined Solubility(ies): Water solubility: Insoluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Viscosity: n.a. Explosive properties: Not determined Oxidising properties: Nο

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Not determined Surface tension: Solvents content: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

RACING CHAIN LUBE 250ML Art.: 1508						
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.



Page 8 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 02.04.2013 / 0008
Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013

PDF print date: 02.04.2013 RACING CHAIN LUBE 250ML Art.: 1508

Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-RE):		
Aspiration hazard:		n.d.a.
Respiratory tract irritation:		n.d.a.
Repeated dose toxicity:		n.d.a.
Symptoms:		n.d.a.
Other information:		Classification according
		to calculation procedure.

Pentane						
Toxicity/effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>100	mg/l/4h	Rat		
Skin corrosion/irritation:						Mild irritant, Repeated
						exposure may cause skin
						dryness or cracking.
Serious eye damage/irritation:						Mild irritant
Respiratory or skin sensitisation:						Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Aspiration hazard:						Yes
Respiratory tract irritation:						Mild irritant
Symptoms:						dizziness, vomiting,
						cramps, drowsiness,
						mucous membrane
						irritation

	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
Toxicity/effect	Endpoin t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>25,2	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Analogous conclusion, No (inhalation and skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Carcinogenicity:						Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes
Respiratory tract irritation:						Not irritant



Page 9 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Symptoms:		dizziness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Symptoms:		headaches, fatigue, dizziness, nausea, cramps, itching
Symptoms:		dizziness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene								
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes		
	t							
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat				
Skin corrosion/irritation:						Not irritant		
Serious eye damage/irritation:						Not irritant		
Respiratory or skin sensitisation:						Not sensitizising		

Propane	Propane									
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes				
	t									
Germ cell mutagenicity					OECD 471 (Bacterial	Negative				
(bacterial):					Reverse Mutation Test)	_				
Symptoms:						breathing difficulties,				
						unconsciousness,				
						frostbite, headaches,				
						cramps, mucous				
						membrane irritation,				
						dizziness, nausea and				
						vomiting.				

Butane						
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Symptoms:						ataxia, breathing difficulties, dizziness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

RACING CHAIN LUBE 250ML

	Toxicity/offoct	Endnoint	Time	Va
	Art.: 1508			
- 1	10101110 010 1111 2002			

Toxicity/effect End	point Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:						n.d.a.



Page 10 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 02.04.2013 / 0008
Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013

PDF print date: 02.04.2013 RACING CHAIN LUBE 250ML Art.: 1508

Toxicity to daphnia:			n.d.a.
Toxicity to algae:			n.d.a.
Persistence and			n.d.a.
degradability:			
Bioaccumulative			n.d.a.
potential:			
Mobility in soil:			n.d.a.
Results of PBT and			n.d.a.
vPvB assessment:			
Other adverse effects:			n.d.a.
Other information:			According to the recipe,
			contains no AOX.

Pentane									
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Toxicity to fish:	LC50	96h	9,87	mg/l	Oncorhynchus mykiss				
Toxicity to fish:	LC50	96h	9,87	mg/l	Salmo gairdneri				
Toxicity to fish:	LC50	96h	9,99	mg/l	Lepomis macrochirus				
Toxicity to daphnia:	EC50	48h	9,74	mg/l	Daphnia magna				
Persistence and degradability:		8d	70	%					
Bioaccumulative potential:	Log Pow		3,39				calculated value		

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus	OECD 203 (Fish,	
-				_	mykiss	Acute Toxicity	
						Test)	
Toxicity to daphnia:	NOEC/NO	21d	1	mg/l	Daphnia magna	OECD 211	
	EL					(Daphnia magna	
						Reproduction	
						Test)	
Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
Persistence and		28d	81	%			Analogous conclusion
degradability:							
Bioaccumulative potential:	Log Pow		3,4-5,2				
Bioaccumulative	BCF		242-				
potential:			253				
Results of PBT and							No PBT substance, No
vPvB assessment:							vPvB substance
Other information:	DOC						DOC-elimination
							degree(complexing
							organic substance)>=
							80%/28d:, n.a.
Water solubility:							Insoluble

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene									
Endpoint	Time	Value	Unit	Organism	Test method	Notes			
LC50	96h	>71	mg/l						
EC50	48h	1,1	mg/l						
						Not readily biodegradable			
EC50	3h	>100	mg/l						
	Endpoint LC50 EC50	Endpoint Time LC50 96h EC50 48h	Endpoint Time Value LC50 96h >71 EC50 48h 1,1	Endpoint Time Value Unit LC50 96h >71 mg/l EC50 48h 1,1 mg/l	Endpoint Time Value Unit Organism LC50 96h >71 mg/l EC50 48h 1,1 mg/l	Endpoint Time Value Unit Organism Test method LC50 96h >71 mg/l EC50 48h 1,1 mg/l			



Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Propane								
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).	
Results of PBT and							No PBT substance, No	
vPvB assessment:							vPvB substance	

Butane									
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Bioaccumulative	Log Pow		2,98				A notable biological		
potential:							accumulation potential is		
							not to be expected		
							(LogPow 1-3).		
Results of PBT and							No PBT substance, No		
vPvB assessment:							vPvB substance		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations

Recommendation:

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name: UN 1950 AEROSOLS

Transport hazard class(es): 2.1 Packing group: Classification code: 5F LQ (ADR 2013): 1 L

LQ (ADR 2009): 2 Environmental hazards: environmentally hazardous Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name: AEROSOLS (PENTANES)

2.1 Transport hazard class(es): Packing group:

F-D. S-U EmS: Marine Pollutant: Environmental hazards: environmentally hazardous

Transport by air (IATA)

UN proper shipping name:















(GR)

Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

Aerosols, flammable

Transport hazard class(es): 2.1

Packing group:

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Yes

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Regulation (EC) No 1907/2006, Annex XVII

VOC 1999/13/EC ~ 67% w/w

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 3, 11, 12, 15

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

11 Highly flammable.

- 12 Extremely flammable.
- 38 Irritating to skin.
- 51 Toxic to aquatic organisms.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Flam. Liq. — Flammable liquid Skin Irrit. — Skin irritation

Any abbreviations and acronyms used in this document:

Article Categories

according, according to acc., acc. to

ACGIH American Conference of Governmental Industrial Hygienists

Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds



(GB)

Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

approx. approximately

Article number Art., Art. no.

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

body weight bw

CAS Chemical Abstracts Service

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and CLP mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance

e.g. EC **European Community European Chemicals Agency** ECHA European Economic Area EEA European Economic Community EEC

European Inventory of Existing Commercial Chemical Substances **EINECS**

ELINCS European List of Notified Chemical Substances

ΕN **European Norms**

EPA United States Environmental Protection Agency (United States of America)

FRC **Environmental Release Categories**

ES Exposure scenario

etc. et cetera

EU **European Union**

EWC European Waste Catalogue

Fax. Fax number gen. general

Globally Harmonized System of Classification and Labelling of Chemicals GHS

Global warming potential **GWP**

HET-CAM Hen's Egg Test - Chorionallantoic Membrane **HGWP Halocarbon Global Warming Potential**

IARC International Agency for Research on Cancer IATA International Air Transport Association

Intermediate Bulk Container IBC

IBC (Code) International Bulk Chemical (Code) IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

lethal concentration LC

LC50 lethal concentration 50 percent kill lowest published lethal concentration LCLo

Lethal Dose of a chemical ΙD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ **Limited Quantities**

MARPOL International Convention for the Prevention of Marine Pollution from Ships



(GR

Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 02.04.2013 / 0008

Replaces revision of / Version: 19.01.2011 / 0007

Valid from: 02.04.2013 PDF print date: 02.04.2013

RACING CHAIN LUBE 250ML Art.: 1508

n.a. not applicable not available n.av. n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP

Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development

org. organic

polycyclic aromatic hydrocarbon PAH **PBT** persistent, bioaccumulative and toxic

РС Chemical product category

PΕ Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

Structure Activity Relationship SAR

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF

VOC Volatile organic compounds

very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WÉL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average)

reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.