

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Glanz-Politur 600ML

Art.: 1533

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Polish

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC31 - Polishes and wax blends

Process category [PROC]:

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC19 - Hand-mixing with intimate contact and only PPE available

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

#### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr

Telephone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

#### 1.4 Emergency telephone

**Emergency information services / official advisory body:** 

#### Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

#### 2.2 Label elements

#### 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## REGULATION (EC) No 648/2004

15 % or over but less than 30 % aliphatic hydrocarbons less than 5 % non-ionic surfactants

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

## n.a. 3.2 Mixture

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	
Registration number (REACH)	01-2119456810-40-XXXX
Index	
EINECS, ELINCS, NLP	920-901-0 (REACH-IT List-No.)
CAS	(90622-58-5)
content %	10-20
Classification according to Directive 67/548/EEC	Harmful, Xn, R65
	R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	CAS 64742-55-8
content %	1-5
Classification according to Directive 67/548/EEC	Harmful, Xn, R65
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion



Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the eyes with long-term contact:

Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c

#### **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Formaldehyde

Toxic pyrolysis products.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid build up of dust.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.



Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

## 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Protect from direct sunlight and warming.

#### 7.3 Specific end use(s)

No information available at present.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons, C11	-C13, isoalkan	es, <2% aromatics		Content %:10-20
WEL-TWA: 1200 mg/m3 (>=C7 no	ormal and branched	WEL-STEL:	2(II) (AGW)		
chain alkanes)					
BMGV:				Other information:	
Chemical Name	Aluminium oxide				Content %:
WEL-TWA: 10 mg/m3 (total inhal.	dust), 4 mg/m3	WEL-STEL:			
(resp. dust) (aluminium oxides)					
BMGV:				Other information:	
Chemical Name	ganaral duat limit				Content %:
	general dust limit				 Content %.
WEL-TWA: 10 mg/m3 (inhal. dust	), 4 mg/m3 (respir.	WEL-STEL:			
dust)					
BMGV:				Other information:	
Chemical Name	Paraffin wax, fume				Content %:
WEL-TWA: 2 mg/m3		WEL-STEL:	6 mg/m3		
BMGV:				Other information:	

<sup>\*\* =</sup> The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Aluminium oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term	DNEL	6,22	mg/kg bw/day	
Industrial	Human - inhalation	Long term	DNEL	3	mg/m3	
Commercial	Human - inhalation	Long term	DNEL	3	mg/m3	
	Environment - sewage treatment plant		PNEC	20	mg/l	

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.



Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,35

Permeation time (penetration time) in minutes:

>= 480

Protective PVC gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

Green

Characteristic

Not determined

pH-value: 6,83

Melting point/freezing point:

Initial boiling point and boiling range:

Flash point:

Evaporation rate:

Not determined

>65 °C

Evaporation rate:

Not determined



Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Upper explosive limit:

Vapour pressure:

Vapour density (air = 1):

Density:

Bulk density:

Solubility(ies):

Water solubility:

Not determined
Not determined
Not determined
Not determined
Mixable

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Explosive properties:

Oxidising properties:

Not determined

Not determined

Not determined

Not determined

Not determined

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

See also Subsection 10.2 to 10.6.

The product has not been tested.

#### 10.2 Chemical stability

See also Subsection 10.1 to 10.6.

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6. No decomposition if used as intended.

#### 10.4 Conditions to avoid

See also section 7.

#### 10.5 Incompatible materials

See also section 7.

No dangerous reactions are known.

#### 10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

No decomposition when used as directed.

## **SECTION 11: Toxicological information**

Possibly more information on health effects, see Section 2.1 (classification).

Glanz-Politur 600ML						
Art.: 1533						
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes
	t					
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						



Page 7 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 06.08.2013 / 0005
Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Respiratory tract irritation:	n.d.a.
Repeated dose toxicity:	n.d.a.
Symptoms:	n.d.a.
Other information:	Classification according
	to calculation procedure.

Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes
Aguta taviaity by and route	t LD50	>5000	ma/ka	Rat	OFCD 404 (Aquita Oral	
Acute toxicity, by oral route:			mg/kg		OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	24h
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:					,	No indications of such an effect.
Germ cell mutagenicity (in vitro):				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity (in vitro):				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity (in vivo):				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity (in vivo):				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						Analogous conclusion, Negative
Aspiration hazard:						Yes
Symptoms:						headaches, dizziness

Distillates (petroleum), hydrotreated light paraffinic									
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes			
	t								
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat					
Aspiration hazard:						Yes			

Aluminium oxide							
Toxicity/effect	Endpoin t	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)		
Acute toxicity, by inhalation:	LC50	7,6	mg/l/1h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol	
Skin corrosion/irritation:				Rabbit		Not irritant	
Serious eye damage/irritation:				Rabbit		Not irritant	



Page 8 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Respiratory or skin sensitisation:		Guinea pig	Not sensitizising
Symptoms:			constipation

Paraffin wax, fume								
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes		
	τ							
Symptoms:						diarrhoea		

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Art.: 1533							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and							The surfactant(s)
degradability:							contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents., Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent
D: 1.4							manufacturer.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus	OECD 203 (Fish,	
				_	mykiss	Acute Toxicity	
						Test)	
Toxicity to fish:	NOELR	28d	0,32	mg/l	Oncorhynchus	QSAR	
					mykiss		
Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	
Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell	OECD 201	
					a subcapitata	(Alga, Growth	
						Inhibition Test)	



Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Persistence and degradability:	28d	31	%	Not readily but inherent biodegradable.
Results of PBT and				No PBT substance, No
vPvB assessment:				vPvB substance
Water solubility:				Insoluble

Aluminium oxide							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	218,6	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50		>100	mg/l	Daphnia magna		
Toxicity to algae:	EC50		>100	mg/l	Selenastrum capricornutum		
Results of PBT and vPvB assessment:							No PBT substance

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

12 01 09 machining emulsions and solutions free of halogens

12 01 12 spent waxes and fats

Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

#### **General statements**

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2013):

LQ (ADR 2009):

n.a.

n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

## Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Marine Pollutant:

n.a.

Environmental hazards: Not applicable

#### Transport by air (IATA)



Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

UN proper shipping name:

Transport hazard class(es):

Packing group:

n.a.

n.a.

Environmental hazards: Not applicable

#### Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: n.a. VOC (1999/13/EC): 12% w/w

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

These details refer to the product as it is delivered.

Revised sections: 2, 8, 9

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

#### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques



Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (RÉGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and

mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario etc. et cetera EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level

ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic



Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 06.08.2013 / 0005

Replaces revision of / Version: 10.06.2011 / 0004

Valid from: 06.08.2013 PDF print date: 06.08.2013 Glanz-Politur 600ML Art.: 1533

Chemical product category

PF Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

parts per million ppm ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

Structure Activity Relationship SAR

SU Sector of use

SVHC Substances of Very High Concern

Telephone Tel.

ThOD Theoretical oxygen demand

Total organic carbon TOC

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) **UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VhF

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

## These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.