

Page 1 of 8  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 15.03.2011 / 0009  
Replaces revision of / Version: 19.01.2011 / 0008  
Valid from: 15.03.2011  
PDF print date: 16.03.2011  
LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**LM 47 LANGZEITFETT+MOS2 400G**

**Art.: 3520**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Use in closed process, no likelihood of exposure.

PROC 2 - Use in closed, continuous process with occasional controlled exposure

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 - Heat and pressure transfer fluids in dispersive, professional use but closed systems

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 9a - Wide dispersive indoor use of substances in closed systems

ERC 9b - Wide dispersive outdoor use of substances in closed systems

Article Categories [AC]:

AC99 - Not required.

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr

Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de)

#### 1.4 Emergency telephone

##### Advisory office in case of poisoning:

##### Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

##### 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments).

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

#### 2.2 Label elements

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 15.03.2011 / 0009  
 Replaces revision of / Version: 19.01.2011 / 0008  
 Valid from: 15.03.2011  
 PDF print date: 16.03.2011  
 LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

## 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

## 2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments).

Symbols: Not applicable

Indications of danger: --

R-phrases:

S-phrases:

Additions: n.a.

## 2.3 Other hazards

The mixture contains no vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains no PBT substance (PBT = persistent, bioaccumulative, toxic).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

--	
Registration number (ECHA)	-
Index	-
EINECS, ELINCS	-
CAS	-
content %	
Symbol	-
R-phrases	-
Classification categories / Indications of danger	---
Hazard class/Hazard category	Hazard statement
---	---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Drying of the skin.

With long-term contact:

Irritation of the skin.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

Page 3 of 8  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 15.03.2011 / 0009  
Replaces revision of / Version: 19.01.2011 / 0008  
Valid from: 15.03.2011  
PDF print date: 16.03.2011  
LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>  
Foam  
Dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Oxides of sulphur  
Toxic pyrolysis products.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.  
Or:

Pick up mechanically and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

Avoid formation of oil mist.  
Avoid contact with eyes.  
Avoid long lasting or intensive contact with skin.  
Do not carry cleaning cloths soaked in product in trouser pockets.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 15.03.2011 / 0009  
 Replaces revision of / Version: 19.01.2011 / 0008  
 Valid from: 15.03.2011  
 PDF print date: 16.03.2011  
 LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

(GB) Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
BMGV: ---	Other information: ---	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,3

Permeation time (penetration time) in minutes:

> 120

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A - P2 EN 14387

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

Page 5 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 15.03.2011 / 0009  
 Replaces revision of / Version: 19.01.2011 / 0008  
 Valid from: 15.03.2011  
 PDF print date: 16.03.2011  
 LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Pastelike
Colour:	Black
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	190 °C (Drop point )
Initial boiling point and boiling range:	Not determined
Flash point:	>100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~0,9 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	>20,5 mm <sup>2</sup> /s (40°C)
Explosive properties:	No
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

See also Subsection 10.4 to 10.6.  
 The product has not been tested.

### 10.2 Chemical stability

See also Subsection 10.4 to 10.6.  
 Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

See also Subsection 10.4 to 10.6.  
 No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.  
 Protect from humidity.

### 10.5 Incompatible materials

See also section 7.  
 Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

See also Subsection 10.4 to 10.6.  
 See also section 5.3

Page 6 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 15.03.2011 / 0009  
 Replaces revision of / Version: 19.01.2011 / 0008  
 Valid from: 15.03.2011  
 PDF print date: 16.03.2011  
 LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

No decomposition when used as directed.

## SECTION 11: Toxicological information

The product was not tested.  
 Classification according to calculation procedure.

### LM 47 LANGZEITFETT+MOS2 400G

Art.: 3520

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:				---		n.d.a.
Acute toxicity, by dermal route:				---		n.d.a.
Acute toxicity, by inhalation:				---		n.d.a.
Skin corrosion/irritation:				---		n.d.a.
Serious eye damage/irritation:				---		n.d.a.
Respiratory or skin sensitisation:				---		n.d.a.
Germ cell mutagenicity:				---		n.d.a.
Carcinogenicity:				---		n.d.a.
Reproductive toxicity:				---		n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):				---		n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):				---		n.d.a.
Aspiration hazard:				---		n.d.a.
Respiratory tract irritation:				---		n.d.a.
Repeated dose toxicity:				---		n.d.a.
Symptoms:				---		n.d.a.

## SECTION 12: Ecological information

The product has not been tested.

### LM 47 LANGZEITFETT+MOS2 400G

Art.: 3520

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

07 06 99 wastes not otherwise specified

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

20 01 26 oil and fat other than those mentioned in 20 04 25

Recommendation:

Page 7 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 15.03.2011 / 0009  
 Replaces revision of / Version: 19.01.2011 / 0008  
 Valid from: 15.03.2011  
 PDF print date: 16.03.2011  
 LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

Pay attention to local and national official regulations  
 E.g. dispose at suitable refuse site.  
 E.g. suitable incineration plant.

### For contaminated packing material

Pay attention to local and national official regulations  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

UN number: n.a.

### Transport by road/by rail (ADR/RID)

UN proper shipping name:  
 Transport hazard class(es): n.a.  
 Packing group: n.a.  
 Classification code: n.a.  
 LQ (ADR 2011): n.a.  
 LQ (ADR 2009): n.a.  
 Environmental hazards: Not applicable  
 Tunnel restriction code:

### Transport by sea (IMDG-code)

UN proper shipping name:  
 Transport hazard class(es): n.a.  
 Packing group: n.a.  
 Marine Pollutant: n.a.  
 Environmental hazards: Not applicable

### Transport by air (IATA)

UN proper shipping name:  
 Transport hazard class(es): n.a.  
 Packing group: n.a.  
 Environmental hazards: Not applicable

### Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: n.a.

### 15.2 Chemical safety assessment

No information available at present.

## SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 2, 3, 7, 8, 10

### Legend:

n.a. = not applicable / n.v., n.av. = not available / n.g., n.c. = not checked / k.D.v., n.d.a. = no data available  
 WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL =  
 Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40  
 AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

Page 8 of 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 15.03.2011 / 0009

Replaces revision of / Version: 19.01.2011 / 0008

Valid from: 15.03.2011

PDF print date: 16.03.2011

LM 47 LANGZEITFETT+MOS2 400G Art.: 3520

VbF = Regulations for flammable liquids (Austria)

VOC = Volatile organic compounds

AOX = Adsorbable organic halogen compounds

ATE = Acute Toxicity Estimates according to Regulation (EC) 1272/2008 (CLP)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.