

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Schrauben-Sicherung mittelfest 50GR Art.: 3802

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr

Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de)

#### 1.4 Emergency telephone

##### Emergency information services / official advisory body:

##### Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

##### 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

#### 2.2 Label elements

##### 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Page 2 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

Not applicable

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

--	
<b>Registration number (REACH)</b>	--
<b>Index</b>	-
<b>EINECS, ELINCS, NLP</b>	-
<b>CAS</b>	-
<b>content %</b>	
<b>Classification according to Directive 67/548/EEC</b>	---
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

Never pour anything into the mouth of an unconscious person!

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Cool container at risk with water.

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

GB

Page 3 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

Toxic gases

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
 Protective respirator with independent air supply.  
 According to size of fire  
 Full protection, if necessary  
 Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.  
 Avoid contact with eyes or skin.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
 Flush residue using copious water.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Store in a well-ventilated place.  
 Protect from direct sunlight and warming.  
 Protect from humidity.  
 Protect from frost.  
 Recommended storage temperature:  
 20°C

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Chemical Name	Diethyl phthalate		Content %:
WEL-TWA:	5 mg/m3	WEL-STEL:	10 mg/m3
BMGV:	---	Other information:	---

GB

Page 4 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Diethyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	52,8	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	52,8	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,017	mg/cm2	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10,56	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10,56	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,0084	mg/cm2	
Consumer	Human - oral	Short term, systemic effects	DNEL	3,75	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	13	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	3,75	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	13	mg/m3	
Consumer	Human - dermal	Short term, local effects	DNEL	0,0084	mg/cm2	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,75	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	2,6	mg/m3	
Consumer	Human - dermal	Long term, local effects	DNEL	0,0042	mg/cm2	
	Environment - freshwater		PNEC	12	µg/l	
	Environment - marine		PNEC	1,2	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	120	µg/l	
	Environment - soil		PNEC	0,137	mg/kg dw	
	Environment - sediment, freshwater		PNEC	0,137	mg/kg dw	
	Environment - sediment, marine		PNEC	0,0137	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2000	µg/l	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Page 5 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 Recommended  
 Safety gloves made of fluorocarbon rubber (EN 374).  
 Minimum layer thickness in mm:  
 0,4  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:  
 Normally not necessary.  
 In aerosol misting:  
 Filter A P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	<0,15 hPa (25°C, DIN 51616)
Vapour density (air = 1):	Not determined
Density:	1,08 g/ml (25°C, DIN 53217)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble

Page 6 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	>300 °C (Ignition temperature )
Decomposition temperature:	>200 °C
Viscosity:	1000 mPas (23°C)
Explosive properties:	n.a.
Oxidising properties:	No

## 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Strong heat

### 10.5 Incompatible materials

See also section 7.

Alkali metals

Peroxides

Oxidizing agents

Reducing agent

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

### Schrauben-Sicherung mittelfest 50GR

Art.: 3802

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Page 7 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

Diethyl phthalate						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	8600	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>10	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Mild irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity (in vitro):					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity (in vitro):					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity (in vitro):					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:	NOAEL	1015	mg/kg bw/d	Rat	OECD 451 (Carcinogenicity Studies)	
Reproductive toxicity:	NOAEL	15000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	150	mg/kg	Rat		
Symptoms:						abdominal pain, unconsciousness, diarrhoea, coughing, watering eyes, nausea and vomiting.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Schrauben-Sicherung mittelfest 50GR Art.: 3802							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Diethyl phthalate							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	48h	61	mg/l	Leuciscus idus		

Page 8 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

Toxicity to fish:	LC50	96h	12	mg/l	Oncorhynchus mykiss		
Toxicity to daphnia:	LC50	24h	52	mg/l	Daphnia magna		
Toxicity to daphnia:	NOEC/NOEL	21d	25	mg/l	Daphnia magna		
Toxicity to algae:	EC50	72h	23	mg/l	Scenedesmus subspicatus	DIN 38412 T.9	
Persistence and degradability:		28d	94,6	%		U.S. EPA ECOTOX Database	Completely biodegradable.
Bioaccumulative potential:	BCF		13,14				
Bioaccumulative potential:	Log Pow		2,2				41°C, pH 7,5
Mobility in soil:	Log Koc		2,34			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	21°C
Toxicity to bacteria:	EC20	30min	400	mg/l	activated sludge	ISO 8192	
Other organisms:	EC50	7d	106	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	
Other organisms:	LC50	48h	0,85	mg/cm2	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)  
 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

UN number: n.a.

#### Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2011): n.a.



Page 9 of 11  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 20.11.2012 / 0008  
 Replaces revision of / Version: 20.04.2012 / 0007  
 Valid from: 20.11.2012  
 PDF print date: 05.12.2012  
 Schrauben-Sicherung mittelfest 50GR Art.: 3802

LQ (ADR 2009): n.a.  
 Environmental hazards: Not applicable  
 Tunnel restriction code:

### Transport by sea (IMDG-code)

UN proper shipping name:  
 Transport hazard class(es): n.a.  
 Packing group: n.a.  
 Marine Pollutant: n.a.  
 Environmental hazards: Not applicable

### Transport by air (IATA)

UN proper shipping name:  
 Transport hazard class(es): n.a.  
 Packing group: n.a.  
 Environmental hazards: Not applicable

### Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: n.a.  
 VOC (1999/13/EC): < 1%

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 2

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

## Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)

BOD	Biochemical oxygen demand
BSEF	Bromine Science and Environmental Forum
bw	body weight
CAS	Chemical Abstracts Service
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration

Page 11 of 11  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 20.11.2012 / 0008  
Replaces revision of / Version: 20.04.2012 / 0007  
Valid from: 20.11.2012  
PDF print date: 05.12.2012  
Schrauben-Sicherung mittelfest 50GR Art.: 3802

NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.