

A Dimensions: [mm]





Scale - 1:1

Optical Properties:

| Properties | Value |
|-----------------|------------|
| Chip Technology | InGaN |
| Emitting Color | Blue |
| Lens Type | Waterclear |

B Recommended hole pattern: [mm]




Scale - 1:1



D Absolute Maximum Ratings (Ambient Temperature 25°C):

| Properties | Test conditions | | Value | Unit |
|----------------------------------|-----------------|----------------------|-------|------|
| Power dissipation | | P _{Diss} | 108 | W |
| Peak Forward Current | duty/10@1kHz | I _{F Peak} | 100 | mA |
| Continuous Forward Current | | ΙF | 30 | mA |
| Reverse Voltage | | V _{Rev} | 5 | V |
| ESD Threshold/ Human Body Modell | | V _{ESD} HBM | 1000 | V |

C Schematic:



E General information:

- •Operating temperature: -40°C to +85°C
- •Storage temperature (on tape & reel): -40°C to +85°C; 60% RH max.

| | | | | Projection ———————————————————————————————————— |
|-----|------------|-----|---------|---|
| | | | | Würth Elektronik eiSos GmbH & Co. KG |
| 1.3 | 2013-09-10 | SSt | SSt | EMC & Inductive Solutions Max-Eyth-Str. 1 |
| 1.2 | 2013-04-10 | SSt | SSt | 74638 Waldenburg |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 |
| 1.0 | 2011-09-01 | SSt | PLD | www.we-online.com eiSos@we-online.com |
| REV | DATE | BY | CHECKED | Oloco Wo Orinino.com |

DESCRIPTION

WL-TMRW THT LED round mono-color waterclear

Order.- No.

151033BS03000



SIZE

A4

ize: 3 mm

SIZE

A4




D Electrical & Optical Properties:

| Properties | Test conditions | | Value | | | Unit | |
|---------------------|-----------------|---------------------------|-------|----------------|-----|------|--|
| Troporado | Tool containing | | min. | min. typ. max. | | 0 | |
| Peak Wavelength | 20 mA | λ_{Peak} | | 465 | | nm | |
| Dominant wavelength | 20 mA | λ _{Dom} | | 470 | | nm | |
| Luminous Intensity | 20 mA | lV | 1100 | 3800 | | mcd | |
| Forward voltage | 20 mA | V _F | | 2.8 | 3.6 | V | |
| Spectral Bandwidth | 20 mA | Δλ | | 20 | | nm | |
| Reverse Current | 5 V | I _{Rev} | | | 50 | μА | |
| Viewing angle | 20 mA | 2 θ _{50%} | | 30 | | 0 | |


| | | | | Projection ———————————————————————————————————— | | DESCRIPTION | | |
|-----|------------|-----|---------|---|------------|----------------------|------------------------|---|
| | | | | | | WL-TMRW THT LE | ED round mono-colo | r |
| | | | | Würth Elektronik eiSos Gmbl | 1 & Co. KG | waterclear | | |
| 1.3 | 2013-09-10 | SSt | SSt | EMC & Inductive Solutions Max-Eyth-Str. 1 | | Trator oroa: | | |
| 1.2 | 2013-04-10 | SSt | SSt | 74638 Waldenburg | | Order No. | COMPLIANT | |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 | | 454000000000 | ROHS&REACH HALOGENFREE | |
| 1.0 | 2011-09-01 | SSt | PLD | www.we-online.com eiSos@we-online.com | | 151033BS03000 | T TIVLES GET TITLE | |
| REV | DATE | BY | CHECKED | CIOOSSWC OMMIC.COM | | Size: 3 mm | | |



F Viewing Angle:




F Spectral:




| | | | | Projection - | | WL-TMRW THT LED rou | nd mono-colo | r |
|-----|------------|-----|---------|--|------------|---------------------|---------------------------|------|
| 1.3 | 2013-09-10 | SSt | SSt | Würth Elektronik eiSos Gmbl EMC & Inductive Solutions | H & Co. KG | waterclear | | |
| 1.2 | 2013-04-10 | SSt | SSt | Max-Eyth-Str. 1 74638 Waldenburg | | Order No. | COMPLIANT | SIZF |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 | | 45400000000 | ROHS&REACH HALOGENFREE | SIZE |
| 1.0 | 2011-09-01 | SSt | PLD | www.we-online.com eiSos@we-online.com | | 151033BS03000 | 2 1 // (ESGENTTEE | A4 |
| REV | DATE | BY | CHECKED | CIOO3@WC OIIIIIC.COIII | | Size: 3 mm | | |



F Forward Current vs. Forward Voltage:




F Luminous Intensity vs. Forward Current:



| | | | | Projection ———————————————————————————————————— | | DESCRIPTION WL-TMRW THT LE | D round mono-colo | r |
|-----|------------|-----|---------|--|------------|-----------------------------|------------------------|------|
| 1.3 | 2013-09-10 | SSt | SSt | Würth Elektronik eiSos Gmbl EMC & Inductive Solutions | H & Co. KG | waterclear | | |
| 1.2 | 2013-04-10 | SSt | SSt | Max-Eyth-Str. 1 74638 Waldenburg | | Order No. | COMPLIANT | SIZE |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 | | 4E4000D00000 | ROHS&REACH HALOGENFREE | SIZL |
| 1.0 | 2011-09-01 | SSt | PLD | www.we-online.com eiSos@we-online.com | | 151033BS03000 | I III LOGENTILL | A4 |
| REV | DATE | BY | CHECKED | GIOCOSTO OTIMIC.COM | | Size: 3 mm | | |




F Derating Curve:







| | | Packaging | Packaging |
|------|-----------|-----------|-----------|
| | | Туре | Unit |
| | 151031xx | Bulk | 500 |
| | 151032xx | Bulk | 500 |
| size | 151033xxx | Bulk | 500 |
| S. | 151051xx | Bulk | 250 |
| | 151052xx | Bulk | 250 |
| | 151053xxx | Bulk | 500 |



| | | | | Projection Projection |
|-----|------------|-----|---------|---|
| | | | | |
| | | | | Würth Elektronik eiSos GmbH & Co. KG |
| 1.3 | 2013-09-10 | SSt | SSt | EMC & Inductive Solutions Max-Eyth-Str. 1 |
| 1.2 | 2013-04-10 | SSt | SSt | 74638 Waldenburg |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 |
| 1.0 | 2011-09-01 | SSt | PLD | www.we-online.com eiSos@we-online.com |
| RFV | DATE | RY | CHECKED | Globawa Gilling.com |

DESCRIPTION

WL-TMRW THT LED round mono-color waterclear

Order.- No.

Size: 3 mm

151033BS03000

ROHS&REACH HALOGENFREE

SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.


SIZE

A4

H Soldering Specifications:



H1: Classification Wave Soldering Profile for THT components:



H2: Classification Wave Profile

| Profile Feature | Pb-Free Assembly | Sn-Pb Assembly |
|---|------------------|------------------|
| Preheat | | |
| - Temperature Min (T _{s min}) | 100°C | 100°C |
| - Temperature Typical (Tetypical) | 120°C | 120°C |
| - Temperature Max (T _{s max}) | 130°C | 130°C |
| - Time (t _s) from (T _{s min} to T _{s max}) | 70 seconds | 70 seconds |
| Δ preheat to max Temperature | 150°C max. | 150°C max. |
| Peak temperature (T _p) | 245°C - 260°C | 235°C - 260°C |
| Time of actual peak temperature (t _p) | 5-8 seconds max. | 3-6 seconds max. |
| Ramp-down rate | | |
| - Min | ~ 2 K/s | ~ 2 K/s |
| - Typical | ~ 3.5 K/s | ~ 3.5 K/s |
| - Max | ~ 5 K/s | ~ 5 K/s |
| Time 25°C to 25°C | 4 minutes | 4 minutes |
| Applied cycles | 1 cycle max. | 1 cycle max. |

| | | | | Projection ———————————————————————————————————— | | WL-TMRW THT LED round mono-color | | |
|-----|------------|-----|---------|--|--|----------------------------------|--|---------------|
| 1.3 | 2013-09-10 | SSt | SSt | Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions | | waterclear | | |
| 1.2 | 2013-04-10 | SSt | SSt | Max-Eyth-Str. 1 74638 Waldenburg | | Order No. | | |
| 1.1 | 2012-12-10 | SSt | SSt | Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | ROHS&REACH HALOGENEREE | | |
| 1.0 | 2011-09-01 | SSt | PLD | | | | | 151033BS03000 |
| REV | DATE | BY | CHECKED | | | Size: 3 mm | | |

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WL-TMRW of Würth Elektronik eiSos GmbH & Co. KG:

General:

All recommendations according to the general technical specifications of the data-sheet have to be complied with.

The disposal and operation of the product within ambient conditions which probably alloy or harm the component surface has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. Accordingly to this the product is exposed to the pressure of the potting material with the effect that the LED body, pins or termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endanger to be affected. After the potting material is cured, the LED body, pins or termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply for customer specific products.

Washing varnish agent that is used during the production to clean the application might damage or change the characteristics of the LED body, pins or termination. The washing varnish agent could have a negative effect on the long term function of the product.

Direct mechanical impact to the product shall be prevented as the material of the LED body, pins or termination could flake or in the worst case it could break.



Product specific:

Follow all instructions mentioned in the datasheet, especially:

- The solder profile has to be complied with according to the technical reflow/ or wave soldering specification, otherwise no warranty will be sustained.
- •All products shall be used before the end of the period of 12 months based on the product date-code, if not a 100% solderability can't be warranted.
- Violation of the technical product specifications such as exceeding the absolute maximum ratings will result in the loss of warranty.
- •It is also recommended to return the LEDs to the original moisture proof bag and reseal the moisture proof bag again.
- Certain LED surfaces consist of soft material. Pressure on the top surface has to be handeled carefully to prevent negative influence to the function and reliability of the LEDs.
- •ESD prevention methods need to be applicated for manual handling and processing by machinery.
- Resistors for protection are obligatory.
- •LED products in operation could harm human vision, therefore direct light impact has to be avoided.



J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications.

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.


7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.



DESCRIPTION

WL-TMRW THT LED round mono-color waterclear

Order.- No

Size: 3 mm

151033BS03000



SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard and reliability standard and reliability standard and reliability standard is especially required or where a failure of the products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.