

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020

Revision date 30-Nov-2020 Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK ALL PURPOSE CLEAR ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

| Serious eye damage/eye irritation | Category 2 - (H319) |
|--|---------------------|
| Specific target organ toxicity (single exposure) | Category 3 - (H336) |
| Flammable liquids | Category 2 - (H225) |

2.2. Label Elements

Contains: Acetone, Methyl ethyl ketone





Signal word Danger

Hazard statements

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H225 - Highly flammable liquid and vapour.

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves and eye/face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P405 - Store locked up.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

| Chemical name | EC No. | CAS No | Weight-% | Classification according to Regulation (EC) No. 1272/2008 [CLP] | Specific concentration limit (SCL) | REACH Registration Number |
|---------------------|-----------|---------|----------|---|--|---------------------------------|
| Acetone | 200-662-2 | 67-64-1 | 40 - <80 | Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225) | | 01-2119471330- 49-XXXX |
| Methyl ethyl ketone | 201-159-0 | 78-93-3 | 10 - <20 | Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225) | | 01-2119457290- 43-XXXX |

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation IF exposed or concerned: Get medical advice/attention. Remove to fresh air.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

Revision date 30-Nov-2020

persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020

Personal precautions See section 8 for more information. Keep people away from and upwind of spill/leak.

> ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Revision date 30-Nov-2020

Revision Number 1.02

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open Advice on safe handling

> flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment.

Contaminated work clothing should not be allowed out of the workplace. Regular **General hygiene considerations**

cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when

using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights,

electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

Specific Use(s)

Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

| Chemical name | European Union | Ireland | United Kingdom |
|---------------------|-----------------------------|------------------------------|------------------------------|
| Acetone | TWA: 500 ppm | TWA: 500 ppm | TWA: 500 ppm |
| 67-64-1 | TWA: 1210 mg/m ³ | TWA: 1210 mg/m ³ | TWA: 1210 mg/m ³ |
| | | STEL: 1500 ppm | STEL: 1500 ppm |
| | | STEL: 3630 mg/m ³ | STEL: 3620 mg/m ³ |
| Methyl ethyl ketone | TWA: 200 ppm | TWA: 200 ppm | TWA: 200 ppm |
| 78-93-3 | TWA: 600 mg/m ³ | TWA: 600 mg/m ³ | TWA: 600 mg/m ³ |
| | STEL: 300 ppm | STEL: 300 ppm | STEL: 300 ppm |
| | STEL: 900 mg/m ³ | STEL: 900 mg/m ³ | STEL: 899 mg/m ³ |
| | | Sk* | Sk* |
| Polyvinyl chloride | - | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ |
| 9002-86-2 | | TWA: 1 mg/m ³ | TWA: 4 mg/m ³ |
| | | STEL: 30 mg/m ³ | STEL: 30 mg/m ³ |
| | | STEL: 3 mg/m ³ | STEL: 12 mg/m ³ |

| Chemical name | European Union | Ireland | United Kingdom |
|---------------------|----------------|---------|-----------------|
| Methyl ethyl ketone | - | - | 70 µmol/L urine |
| 78-93-3 | | | · |

Derived No Effect Level (DNEL) No information available

| Derived No Effect Level (DN | Derived No Effect Level (DNEL) | | | | |
|--|--------------------------------|--------------------------------|---------------|--|--|
| Acetone (67-64-1) | | | | | |
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor | | |
| Long term Systemic health effects worker | Dermal | 186 mg/kg bw/d | | | |
| Short term Local health effects worker | Inhalation | 2420 mg/m³ | | | |
| Long term Systemic health effects worker | Inhalation | 1210 mg/m³ | | | |

| Methyl ethyl ketone (78-93-3) | | | |
|--|----------------|--------------------------------|---------------|
| Туре | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Long term Systemic health effects | Dermal | 1161 mg/kg bw/d | |
| worker Long term Systemic health effects | Inhalation | 600 mg/m³ | |

| Derived | No | Effect | Level | (DNEL) |
|---------|-----|-----------------|-------|--------|
| Acetone | (67 | '-64-1) | | |

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Revision date 30-Nov-2020 Supercedes Date: 24-Apr-2020 **Revision Number** 1.02

| Туре | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
|--|----------------|--------------------------------|---------------|
| Consumer Long term Systemic health effects | Inhalation | 200 mg/m³ | |
| Consumer Long term Systemic health effects | Dermal | 62 mg/kg bw/d | |
| Consumer Long term Systemic health effects | Oral | 62 mg/kg bw/d | |

| Methyl ethyl ketone (78-93-3) | Methyl ethyl ketone (78-93-3) | | | | |
|---|-------------------------------|--------------------------------|---------------|--|--|
| Туре | Exposure route | Derived No Effect Level (DNEL) | Safety factor | | |
| Consumer Long term Systemic health effects | Dermal | 412 mg/kg bw/d | | | |
| Consumer Long term Systemic health effects | Inhalation | 106 mg/m³ | | | |
| Consumer Local health effects Systemic health effects | Oral | 31 mg/kg bw/d | | | |

Predicted No Effect Concentration No information available. (PNEC)

| Predicted No Effect Concentration (PNEC) | |
|--|--|
| Acetone (67-64-1) | |
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 10.6 mg/l |
| Freshwater - intermittent | 21 mg/l |
| Marine water | 1.06 mg/l |
| Microorganisms in sewage treatment | 100 mg/l |
| Freshwater sediment | 30.4 mg/kg dry weight |
| Marine water | 3.04 mg/kg dry weight |
| Soil | 29.5 mg/kg dry weight |

| Methyl ethyl ketone (78-93-3) | | | |
|-------------------------------|--|--|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) | | |
| Freshwater | 55.8 mg/l | | |
| Marine water | 55.8 mg/l | | |
| Freshwater sediment | 287.74 mg/l | | |
| Marine sediment | 287.7 mg/l | | |
| Soil | 22.5 mg/l | | |

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be **Engineering controls**

exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the Hand protection breakthrough time of the glove material is not exceeded. Refer to glove supplier for

information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective

Skin and body protection

In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

Respiratory protection

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Liquid

Colour No information available

Odour Solvent

Odour threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point No data available

Boiling point / boiling range 56 °C Flash point -20 °C

Evaporation rate No data available

Flammability (solid, gas) Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available No data available Relative vapour density Relative density No data available No data available Water solubility Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available **Explosive properties** No data available **Oxidising properties** No data available

9.2. Other information

Solid content (%)

VOC Content (%)

Density

No information available
No information available
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 30-Nov-2020

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute toxicity

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------------|----------------------|--------------------------------------|-------------------------|
| Acetone 67-64-1 | =5800 mg/kg (Rattus) | >15800 mg/Kg (Rattus) | =79 mg/l(Rattus) 4 h |
| Methyl ethyl ketone 78-93-3 | =2483 mg/kg (Rattus) | = 5000 mg/kg (Oryctolagus cuniculus) | =11700 ppm (Rattus) 4 h |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

| Chemical name | Algae/aquatic | Fish | Toxicity to | Crustacea | M-Factor | M-Factor |
|---------------------|-----------------|----------------|----------------|----------------|----------|-------------|
| | plants | | microorganisms | | | (long-term) |
| Acetone | - | LC50 96 h 4.74 | EC50 = 14500 | EC50 48 h | | |
| 67-64-1 | | - 6.33 mL/L | mg/L 15 min | 10294 - 17704 | | |
| | | (Oncorhynchus | | mg/L (Daphnia | | |
| | | mykiss) | | magna Static) | | |
| Methyl ethyl ketone | EC50=1972 | LC50: 3130 - | EC50 = 3403 | EC50 48 h > | | |
| 78-93-3 | mg/l | 3320mg/L (96h, | mg/L 30 min | 308 mg/L | | |
| | (Pseudokirchner | Pimephales | EC50 = 3426 | (Daphnia magna | | |
| | iella | promelas) | mg/L 5 min |) | | |
| | subcapitata) | | | | | |

12.2. Persistence and degradability

Persistence and degradability No information available.

| Component Information | | | |
|-----------------------|---------------|----------------|----------------------------|
| Acetone (67-64-1) | | | |
| Method | Exposure time | Value | Results |
| | 28 days | biodegradation | 91 % Readily biodegradable |

| ethyl ethyl ketone (78-93-3) | | | |
|--------------------------------------|---------------|----------------|----------------------------|
| Method | Exposure time | Value | Results |
| OECD Test No. 301D: Ready | 28 days | biodegradation | 98 % Readily biodegradable |
| Biodegradability: Closed Bottle Test | - | - | |
| (TG 301 D) | | | |

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

Component Information

| Chemical name | Partition coefficient | Bioconcentration factor (BCF) |
|---------------------|-----------------------|-------------------------------|
| Acetone | -0.24 | 0.69 |
| 67-64-1 | | |
| Methyl ethyl ketone | 0.3 | - |
| 78-93-3 | | |

12.4. Mobility in soil

No information available. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or

vPvR

| Chemical name | PBT and vPvB assessment |
|--------------------------------|---------------------------------|
| Acetone 67-64-1 | The substance is not PBT / vPvB |
| Methyl ethyl ketone 78-93-3 | The substance is not PBT / vPvB |

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to Note:

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number UN1133 Adhesives 14.2 Proper Shipping Name

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group Ш

UN1133, Adhesives, 3, II, (D/E) Description

14.5 Environmental hazards Not applicable

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

14.6 Special Provisions 640D
Classification code F1
Tunnel restriction code (D/E)
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler 33

Number)

IMDG

14.1 UN number or ID number 14.2 Proper Shipping NameUN1133
Adhesives

14.3 Transport hazard class(es) 3 14.4 Packing group

Description UN1133, Adhesives, 3, II, (-20°C c.c.)

 14.5 Marine pollutant
 NP

 14.6 Special Provisions
 None

 Limited Quantity (LQ)
 5 L

 EmS-No
 F-E, S-D

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number 14.2 Proper Shipping NameUN1133
Adhesives

14.3 Transport hazard class(es) 3
14.4 Packing group

Description UN1133, Adhesives, 3, II

14.5 Environmental hazards Not applicable

14.6 Special Provisions A3 Limited Quantity (LQ) 1 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Revision date 30-Nov-2020

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Nov-2020

Indication of changes

Revision note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaime

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of

BOSTIK ALL PURPOSE CLEAR ADHESIVE

Supercedes Date: 24-Apr-2020 Revision Number 1.02

its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet