

PUSH BUTTON – RED EMERGENCY STOP

KEY SWITCH – RED EMERGENCY STOP



1DE.01.01AG

2DE.01.01AG

According to EN418

REGISTERED DESIGN



1DE.01.03AB

2DE.01.03AB



1DE.01.01AB



2DE.01.01AB



1DE.01.03AG



2DE.01.03AG

DPB22-R CONTROL STATIONS




Non-illuminated push button control station with reset red mushroom head (40Ø), contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Complies with EN418
- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Yellow (Y)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “EM. STOP” function legend

DPB22-K CONTROL STATIONS

Non-illuminated key switch control station, red mushroom head (40Ø) with key, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Complies with EN418
- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Yellow (Y)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “EM. STOP” function legend



NEW SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN

PUSH BUTTON – RED FLUSH HEAD

PUSH BUTTON – GREEN FLUSH HEAD



1DE.01.04AB

2DE.01.04AB

IP66

REGISTERED DESIGN



1DE.01.06AG

2DE.01.06AG



1DE.01.04AG



2DE.01.04AG



1DE.01.06AG



2DE.01.06AG

DPB22-L CONTROL STATIONS



Non-illuminated push button control station with a red flush head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP66
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver "STOP" function legend

DPB22-F CONTROL STATIONS

Non-illuminated push button control station with a green flush head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP66
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver "START" function legend



See Accessories for SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN

SELECTOR SWITCH – STANDARD LEVER

SELECTOR SWITCH WITH KEY



1DE.01.08AB

2DE.01.08AB

REGISTERED DESIGN



1DE.01.09AG

2DE.01.09AG



1DE.01.08AG



2DE.01.08AB



1DE.01.09AB



2DE.01.09AB

DSS22-S2 CONTROL STATIONS




Non-illuminated standard lever selector switch control station, normal shaft, two positions, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “O I” function legend

DSS22-K2 CONTROL STATIONS

Non-illuminated selector switch control station with a two position key, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “O I” function legend



NEW SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN

PUSH BUTTON – PUSH TO RELEASE HEAD

PUSH BUTTON – PALM/FOOT SWITCH



1DE.01.10AG

2DE.01.10AG

REGISTERED DESIGN



IP66


1DE.SP21NB



1DE.01.10AB



2DE.01.10AB



DPB22-D CONTROL STATIONS





Non-illuminated double push button control station, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver "O I" function legend

DFP-B CONTROL STATIONS

Non-illuminated foot/palm switch control station with a large domed head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
Button: Red (R), black (B) or green (G)
- Sealed up to IP66
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts



See Accessories for SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN

EMERGENCY STOP & PUSH BUTTON



1DE.02.01AG



2DE.02.01AG

REGISTERED DESIGN

“EM STOP”
According to EN418
IP56/66

EMERGENCY STOP & PUSH BUTTONS



1DE.03.01AG



2DE.03.01AG



1DE.02.01AB



2DE.02.01AB



1DE.03.01AB



2DE.03.01AB

DPB22-RF CONTROL STATIONS



Non-illuminated push button control station with reset red mushroom head (40Ø) and a green flush head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Complies with EN418
- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Yellow (Y)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “EM. STOP and START” function legend

DPB22-RFF CONTROL STATIONS

Non-illuminated push button control station with reset red mushroom head (40Ø) and two green flush heads, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Complies with EN418
- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Yellow (Y)
- Sealed up to IP56
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver “EM. STOP, UP and DOWN” function legend



NEW SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN

PUSH BUTTON – PUSH TO RELEASE HEAD

PUSH BUTTON – FLUSH HEAD



1DE.02.02AG

REGISTERED DESIGN

IP66



2DE.02.02AG



1DE.03.02AB



2DE.03.02AB



1DE.02.02AB



2DE.02.02AB



1DE.03.02AG



2DE.03.02AG

DPB22-LF CONTROL STATIONS



Non-illuminated push button control station with a push to release red flush head and one green flush head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP66
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver "STOP and START" function legend

DPB22-FLF CONTROL STATIONS

Non-illuminated push button control station with two green flush heads and a push to release red flush head, contact blocks 1x N.O. and 1x N.C., choice of base depths and colours.

- Standard Base (DE01S): H80 x W73 x D53mm suitable for 2x contact blocks per switch
- Deep Base (DE01D): H80 x W73 x D78mm suitable for 4x contact blocks per switch
- Materials: Flame retardant ABS UL94-HB (A) or Polycarbonate UL94-V0 (P)
- Colours – Base: Black (B) or grey (G)
Cover With Switch: Grey (G)
- Sealed up to IP66
- Complete with 2x M20 threaded and 1x M20 non-threaded cable entry knockouts
- Snap-on flange and din rail brackets, optional
- With black on silver "FWD, STOP and REV" function legend



See Accessories for SNAP-ON* Flange & DIN Rail Brackets



*REGISTERED DESIGN



DE01S-A-GB-1-PB22-L with optional flange brackets



DE01S-A-YG-1-PB22-R with optional DIN rail brackets

REGISTERED DESIGN

IP65/7

This unique range of robust, sealed control stations have been specially designed and manufactured for use in the electrical and electronic engineering markets.

MAIN FEATURES

- Enclosure sealed up to IP67
- Unique snap-on DIN rail and flange brackets
- Dust and waterproof for short-term submersion with integrated moulded seals
- Enclosure available in three flame retardant materials: Polycarbonate – UL94-V0 for improved resistance to shock, ABS – UL94-HB and ABS – UL94-V0
- 2x threaded M20 cable entry and knockout – premoulded area that can be pushed out for use with M20 size male cable gland
- Additional non-threaded M20 knockout on base
- Captive plastic screws to lid fixing for corrosion resistant, increase torque and insulation
- Elongated integral chassis fixing holes retaining IP rating
- Common threaded hole mounts cover to base and base to chassis
- Accepts both “D” and location lug for push button barrels
- Selector and key switches can be mounted centre or at 90°
- PCB mounting posts and slots as standard
- 2x PCB mounting location studs
- 8-22x vertical PCB mounting slots, as standard
- 4-8x self-tapping screw fixings for mounting PCB
- 10 sizes available accepting 1 to 6 push button switches
- All bases available in two depths, 53mm and 78mm

- Standard base with only 47mm internal depth measurement
- Standard base suitable for 2x contact blocks per switch
- Deep base suitable for 4x contact blocks per switch

MOUNTING OPTIONS

- 4x elongated integral mounting holes
- Snap-on chassis mounting flange
- Snap-on DIN rail mounting brackets

COLOURS

- Base: Black (B) or grey (G)
- Cover: Black (B), grey (G) or yellow (Y)

ACCESSORIES

- Wall mounting brackets
- Combi foot - TS32 and TS35 DIN rail mounting clip
- M20 cable glands for use in knock-outs
- Component mounting bracket

SWITCH MATERIALS

- **Body:** PA66 + 15%GF-VO
- Illuminated types Polycarb VO
- Lever types POM polyacetal
- Push button types PA66 V2
- Contact block bracket PA66 V2 + 15%gf
- Contact Block PA66 VO
- Contact block plunger PA66 VO + 15%gf
- Rubber boot silicone rubber
- Push/pull button PA66 V2
- Panel seal PVC
- Panel nut PA66 V2 + 15%gf
- Key brass, nickel plate
- Legend holder PA66 V2
- Legend PP

Contacts:

- Copper alloy/nickel silver
- AgCdO silver, gold plated
- Bifurcated serrated

Screw & Clamp:

- Steel, nickel plated
- M3.5 captive steel, chrome plate

Splash Proof Cover: Silicone rubber

Keys: Brass, nickel plated, 2 supplied

Electrical Properties:

Switch Rating:

AC12 Resistive Load 220-240V...	3A
380-415V...	1.5A
AC15 Electromagnetic Loads...	3A
380-415V...	1.5A

Electrical Life (operations):

500,000 at full load

Mechanical Life (operations): 1,000,000

Contact Resistance (new): Less than 30mΩ

Insulation Resistance:

Above 100MΩ @500Vdc

Dielectric Strength:

Across open contacts:	>1KV	>2KV
Between poles:	>3KV	>3KV
Between live parts and accessible metal:	>4KV	>5KV

Contact Gap: >3mm

Termination: Screw and clamp

Max. Wire size (per terminal):

- 1x 0.5 – 2.5mm² or
- 2 x 1mm² each side of screw
- 2 x 1.5mm² dia max. multi strand (2 wires per clamp)

Physical Properties:

Operating Temp. (min./max.):

-10° + 65° in house

Storage Temp. (1 year): -20°/+60°C

Mechanical Properties:

Panel hole size: 22.5 diameter round with 3.2 dia. keyway

For types R (Emergency Stop - Reset):

40N (with 1 module) to EN418

Sealing: Ingress Rating (IPxx)

Switch: IP66

IP66 types F, L, E, palm

IP65 types push/pull

IP56 types K, S, L, R, M

IP56 D

Switch to panel (22mm): IP66

Splash proof cover, round: IP67 for

Types F, E, L

Splash proof cover, rectangular: IP67 for

Type D

Illumination:

Bayonet BA9s LED – Voltages: 6/24V, 100/120

– 220/240V 380/415V, ac/dc

Bayonet 9mm – Voltages: + 380-415 VAC

Life: 100,000 hours

Product Marking:

Terminal Numbers:

1 & 2 – On Contact Block, CB-01, N.O.

3 & 4 – On Contact Block, CB-10, N.C.