

WHITE AND GREY UNDERCOAT

Page: 1

Compilation date: 04/09/2012

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WHITE AND GREY UNDERCOAT

Product code: WHIU

Synonyms: WHITE AND GREY UNDERCOAT

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

United Kingdom

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; -: R66; -: R67

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH208

Most important adverse effects: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may

cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains methyl ethyl ketoxime. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





WHITE AND GREY UNDERCOAT

Page: 2

Precautionary statements: P271: Use only outdoors or in a well-ventilated area.

P280: Wear eye protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312: Call a POISON CENTER or doctor if you feel unwell. P370+378: In case of fire: Use carbon dioxide for extinction.

Label elements under CHIP:

Risk phrases: R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Precautionary phrases: Contains methyl ethyl ketoxime. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CALCIUM DRIER 4%

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-: R10; N: R51/53; Xn: R65; -: R66	-	0.170%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

proprietry skin cleaner. Do NOT use solvents or thinners. If irritation persists seek $\,$

medical attention.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least

10 minutes, holding the eyelids apart, and seek medical advice.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at

rest and obtain medical attention.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing has stopped,

administer artificial respiration. Give nothing by mouth if unconscious, place in the

recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation with short term redness and stinging.

WHITE AND GREY UNDERCOAT

Page: 3

Ingestion: May cause nausea and diarrhoea.

Inhalation: May cause irritation of the respiratory tract.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO2). Dry chemical powder. Alcohol resistant foam. Sand or earth. Do

NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In a fire, hazardous decomposition products such as smoke and Carbon Monoxide may

be produced.

5.3. Advice for fire-fighters

Advice for fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-

contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour.

Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing (see section

8).

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local

water company should be contacted immediately. In the case of contamination of

streams, rivers or lakes contact the relevant environment agency.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand,

earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which

may produce sparks. Clean preferably with a detergent, avoid the use of solvents.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin

and eye contact. Smoking, eating and drinking should be prohibited in areas of storage

WHITE AND GREY UNDERCOAT

Page: 4

and use. Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct

sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in containers,

should be observed.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel

containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by

the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn

(see Respiratory protection below).

Respiratory protection: All personal protective equipment, including respiratory protective equipment, used to

control exposure to hazardous substances must be selected to meet the requirements

of the COSHH Regulations.

Hand protection: Where repeated skin exposure may occur, wear Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: White and Grey

Odour: Paraffinic.

Solubility in water: Insoluble

Boiling point/range ℃: 150-190 Flash point ℃: 38

Relative density: 1.530 @ 20 C

WHITE AND GREY UNDERCOAT

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may

be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation with short term redness and stinging.

Ingestion: May cause nausea and diarrhoea.

Inhalation: May cause irritation of the respiratory tract.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: Insoluble in water. Partially volatile. Partially absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

WHITE AND GREY UNDERCOAT

Page: 6

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: There is no data available on the product itself.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: Saftey Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

WHITE AND GREY UNDERCOAT

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

[final page]

Page: 7