

QUICK DRY ALUMINUM PAINT

Page: 1

Compilation date: 17/04/2013

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: QUICK DRY ALUMINUM PAINT

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

United Kingdom

NW2 7TX

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411

Classification under CHIP: This product has no classification under CHIP.

2.2. Label elements

Label elements under CLP:

Hazard statements: H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS09: Environmental



Precautionary statements: P273: Avoid release to the environment.

P391: Collect spillage.

P501: Dispose of contents/container to hazardous or special waste collection point.

P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

QUICK DRY ALUMINUM PAINT

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

3-BUTOXYPROPAN-2-OL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
225-878-4	5131-66-8	Xi: R36/38	Eye Irrit. 2: H319; Skin Irrit. 2: H315	1.200%

Section 4: First aid measures

- 4.1. Description of first aid measures
- 4.2. Most important symptoms and effects, both acute and delayed
- 4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

- 5.1. Extinguishing media
- 5.2. Special hazards arising from the substance or mixture
- 5.3. Advice for fire-fighters

Section 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
- 6.2. Environmental precautions
- 6.3. Methods and material for containment and cleaning up
- 6.4. Reference to other sections

Section 7: Handling and storage

- 7.1. Precautions for safe handling
- 7.2. Conditions for safe storage, including any incompatibilities
- 7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

QUICK DRY ALUMINUM PAINT

Page: 3

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Flash point °C: >93

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3-BUTOXYPROPAN-2-OL

ORL	RAT	LD50	5660	μl/kg
SKN	RBT	LD50	3100	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

QUICK DRY ALUMINUM PAINT

Page: 4

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

QUICK DRY ALUMINUM PAINT

Page: 5

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: This data sheet provides guidance on health, safety and environmental aspects of the product and shoud not be construed as any guarantee of technical performance or suitability for particular applications. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.