



Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

February 2018

PRODUCT DATA SHEET

| | |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | Spray Wax |
| Type | A high quality traditional polish based on premium performance waxes, carnauba and beeswax, reinforced with a blend of hydrocarbon waxes to aid application and improve durability. This product has been specially modified to deliver the grain-enhancing beauty of Briwax Original in an easy to use aerosol package |
| Intended Use | For regular interior use on all fine natural wood and antique furniture. |
| Special Features | Quick and easy to use. Makes wood feel silky and smooth. Produces a semi-gloss finish on raw timber. Wax shine on finished wood. Silicone free. Cleans and revitalises. Briwax Spray Wax acts as a n alternative finish on all types of timer, skirting, ceiling timbers, stripped doors etc. in addition to use as a polish. |
| Preparation | The surface must be clean and dry. Briwax Spray Wax can be used on previously waxed surfaces. For best results initially clean the surface with Briwax Furniture Cleaner |
| Application | On finished surfaces; spray at a distance of 40 – 50 cms from the surface. Allow to dry for 2 – 3 minutes, then buff with a soft clean cloth to a waxy shine. On unfinished surfaces; spray at a distance of 40 – 50 cms from the surface and work into surface with a clean cloth while still wet. Allow to dry for 4 – 5 minutes then buff with a soft clean cloth to a waxy shine. |
| Coats | One coat is usually sufficient but a second coat may be applied to obtain a higher sheen. |
| Drying Time | Quick drying. |
| Re-coating Time | Re-apply if required after a few minutes. |
| Application Temp. | Do not use if temperature is below 15°C. Ideally do not apply above 25°C |
| Coverage | N/A |
| Maintenance | Re-apply when necessary. |
| Compatibility | Compatible with most timber finishes. If in doubt check on an inconspicuous test area. For best results and to prevent a blotchy appearance, timber should be previously sealed with a varnish, oil or sanding sealer |
| Settlement | Shake well before use |
| Shelf-life/Storage | A very long time if stored in original sealed container in a cool dry place. |
| Hazards | Extremely flammable. Irritating to eyes. Vapours may cause drowsiness. Keep away from children. Keep away from all sources of ignition. No smoking. A full Health & Safety Data Sheet is available on request or from www.antiquax.co.uk |
| Clean-Up | Hands and application cloths can be cleaned in warn soapy water. |
| Sizes | 400 ml aerosol |