

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier

Trade name : Stick 2 Contact Adhesive Thinners and Cleaner 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Everbuild – A Sika Company Site 41 Knowsthorpe Way Cross Green Industrial Estate Leeds West Yorkshire LS9 0SW United Kingdom
Telephone	:	0113 240 3456
E-mail address	:	everbuild.sds@uk.sika.com

#### 1.4 Emergency telephone number

Emergency telephone num-	:	0044 113 240 3456 (office hours only)
ber		

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Type of product : Mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.


# 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Stick 2 Contact Adhesive Thinners and Cleaner





Hazardous components which must be listed on the label:

• 921-024-6 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Hazardous components

Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	

# SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Stick 2 Contact Adhesive Thinners and Cleaner





Revision Date 25.05.2017

Version 1.0

Registration number		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Flam. Liq.2; H225	>= 60 - < 80
<5% II-liexalle	Skin Irrit.2; H315 STOT SE3; H336	
921-024-6	Asp. Tox.1; H304	
01-2119475514-35-XXXX	Aquatic Chronic2; H411	
acetone	Flam. Liq.2; H225	>= 40 - < 60
67-64-1 200-662-2	Eye Irrit.2; H319 STOT SE3; H336	
01-2119471330-49-XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Immediately flush eye(s) with plenty of water.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptoms	s and effects, both acute and delayed
Symptoms	<ul> <li>Aspiration may cause pulmonary oedema and pneumonitis. Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.</li> </ul>
Risks	<ul> <li>Risk of serious damage to the lungs (by aspiration).</li> <li>irritant effects</li> </ul>





May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical
Unsuitable extinguishing media	:	Water, High volume water jet
5.2 Special hazards arising from the substance or mixture		
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod-	:	No hazardous combustion products are known

## 5.3 Advice for firefighters

ucts

Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
Further information	: Use water spray to cool unopened containers. Collect contam- inated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.
	Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.

## 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.	
---	--



If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	: Contain spillage, and then collect with non-combustible ab-
	sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
	miculite) and place in container for disposal according to local
	/ national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe ha	indling :	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drink- ing should be prohibited in the application area. Take precau- tionary measures against static discharge. Open drum careful- ly as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protecti fire and explosion		Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take pre- cautionary measures against electrostatic discharges.
Hygiene measure	s :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for sat	fe storage, incl	luding any incompatibilities
Requirements for areas and contain		Store in original container. Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in ac- cordance with local regulations.
Other data	:	No decomposition if stored and applied as directed.
7.3 Specific end use(	s)	
Specific use(s)	:	No data available

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters





# Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	GB EH40
		STEL	1.500 ppm 3.620 mg/m3	GB EH40

## 8.2 Exposure controls

## Personal protective equipment

Eye protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

# **Environmental exposure controls**





General advice

 Prevent product from entering drains.
 If the product contaminates rivers and lakes or drains inform respective authorities.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties Appearance liquid 1 Colour colourless Odour : characteristic Odour Threshold : No data available -20 °C Flash point ÷ Autoignition temperature : No data available Decomposition temperature : No data available Lower explosion limit (Vol-%) : 1,1 %(V) Upper explosion limit (Vol-%) : 7,4 %(V) Flammability No data available . Explosive properties : No data available Oxidizing properties : No data available pН No data available : Melting point/range / Freez-: No data available ing point Boiling point/boiling range : ca. 50 °C Vapour pressure : 34,6637 hPa : 0,75 g/cm3 Density at 15°C Water solubility : insoluble Partition coefficient: n-: No data available octanol/water Viscosity, dynamic : No data available Viscosity, kinematic : >7 mm2/s at 40 °C Relative vapour density No data available





Evaporation rate : No data available

### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

## **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

## **10.2 Chemical stability**

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

Vapours may form explosive mixture with air.

# 10.4 Conditions to avoid

Conditions to avoid	: Heat, flames and sparks.
---------------------	----------------------------

#### 10.5 Incompatible materials

Materials to avoid	: No data available
--------------------	---------------------

## **10.6 Hazardous decomposition products**

## **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

Acute toxicity				
Not classified based on available information.				
Components:				
acetone: Acute oral toxicity	:	LD50 Oral (Rat): 5.800 mg/kg		
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapour		
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 20.000 mg/kg		
Skin corrosion/irritation				
Causes skin irritation.				
Serious eye damage/eye irritation				
Causes serious ave irritation				





Version 1.0



## Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

## **Components:**

#### acetone :

Toxicity to fish	: LC50: > 5.000 mg/l, 96 h, Fish
Toxicity to daphnia and other aquatic invertebrates	: EC50: 12,700 mg/l, 48 h, Daphnia (water flea)
Toxicity to algae	: ErC50: > 530 mg/l, 96 h, Pseudokirchneriella subcapitata (green algae)

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

## Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.





#### 12.6 Other adverse effects

# Product:

Additional ecological infor-	: An environmental hazard cannot be excluded in the event of	f
mation	unprofessional handling or disposal.	
	Toxic to aquatic life with long lasting effects.	

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

# **SECTION 14: Transport information**

ADR 14.1 UN number 14.2 Description of the goods 14.3 Class 14.4 Packing group Classification Code Labels Tunnel restriction code 14.5 Environmentally hazard- ous	<ul> <li>1993</li> <li>FLAMMABLE LIQUID, N.O.S. (naphtha (petroleum))</li> <li>3</li> <li>II</li> <li>F1</li> <li>3</li> <li>(D/E)</li> <li>yes</li> </ul>
IATA 14.1 UN number 14.2 Description of the goods 14.3 Class 14.4 Packing group	<ul> <li>1993</li> <li>Flammable liquid, n.o.s. (naphtha (petroleum))</li> <li>3</li> <li>II</li> </ul>

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

**Stick 2 Contact Adhesive Thinners and Cleaner** 

Revision Date 25.05.2017

Version 1.0



Labels 14.5 Environmentally hazard- ous	: 3 : yes
IMDG 14.1 UN number 14.2 Description of the goods	: 1993 : FLAMMABLE LIQUID, N.O.S. (naphtha (petroleum))
14.3 Class	: 3
14.4 Packing group	: 11
Labels	: 3
EmS Number 1	: F-E
EmS Number 2	: S-E
14.5 Marine pollutant	: yes naphtha (petroleum)

## 14.6 Special precautions for user

No data available

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Prohibition/Restriction</b> REACH - Restrictions on the mar the market and use of certain dar preparations and articles (Annex	ngerous substances,	:	Not applicable	
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the compone (=> 0.1 %).	ents are listed
REACH - List of substances subject to authorisation (Annex XIV)		:	Not applicable	
REACH Information: All substances contained in our Products are - preregistered or registered by our upstream suppliers, and/or - preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.				
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances.				
E2	ENVIRONMENTAL HAZARDS		Quantity 1 200 t	Quantity 2 500 t
P5c	FLAMMABLE LIQUIDS		5.000 t	50.000 t
VOC-CH (VOCV) :	100 %			





VOC-EU (solvent) : 100 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

## 15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

#### Full text of H-Statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic Asp. Tox. Eye Irrit. Flam. Liq. Skin Irrit.	Chronic aquatic toxicity Aspiration hazard Eye irritation Flammable liquids Skin irritation
STOT SE	Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
untra CD 10000016046	10





PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the
	Council of 18 December 2006 concerning the Registration, Evaluation,
	Authorisation and Restriction of Chemicals (REACH), establishing a
	European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !