## OPEN FRAME POWER SUPPLY 5VDC 20WATT

STONTRONICS: PD-20-5

#### **Features:**

- Universal Input
- High Efficiency
- 3 Year Warranty
- Efficiency Level VI





#### **Description:**

The 20W open frame power supply range has been specially designed to offer high efficiency, long life and high reliability for use in a variety of applications. Each model is approved to CE, CB, UL and comes with a 3 year warranty.

SPECIFICATION		
Part Number		PD-20-5
DC Voltage		5V
Rated Current		4A
Current Range		0~4A
Ripple & Noise	0°C~60°C	<50mV
	-20°C~0°C	<75mV
Voltage ADJ. Range		4.4~5.6V
Line Regulation		±0.5%
Load Regulation		±2.0%
Set-up Time		<2.0S (115Vac input, Full load); <1.0S (230Vac input, Full load)
Hold up Time		>10mS (115Vac input, Full load); >20mS (230Vac input, Full load)
Temperature Coefficient		±0.03%
Overshoot and Undershoot		<5.0%
Input voltage range		85Vac~264Vac,120Vdc~370Vdc
Input frequency range		47Hz~63Hz
Efficiency 115Vacinput		76%
AC Current (max.)		0.5A
Inrush Current		Cold start 20A@115Vac 40A@230Vac
Leakage Current		Input—output:<0.35mA Input—PG:<0.75mA
Over Load		105%~150% rated output power; Hiccup mode, auto recovery
Over Voltage		110%~140% of rated output voltage, Constant Voltage.
Short Circuit		Long-term mode, auto recovery
Operating amb. Temp. & Hum.		-25°C~70°C; 20%~90%RH No condensing (refer to the derating curve)
Storage Temp. & Hum.		-40°C~85°C; 10%~95%RH No condensing
Safety Standards		UL60950-1; EN60950-1:2006
Withstand Voltage		Primary-Secondary:3.0KVa; ≤10mA. Primary-PG:1.5KVac; ≤10mA. Secondary-PG:0.5KVDC; ≤10mA.
Isolation Resistance		≥100M ohms
MTBF		More than 200,000Hrs (25°C, Full load)
Dimension (L*W*H)		89×51×20mm

# OPEN FRAME POWER SUPPLY 5VDC 20WATT



STONTRONICS: PD-20-5

### **Diagrams**

