



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	FLUX SK10
Registration number	-
UFI:	VH3X-M8S2-N00F-PF8K
Synonyms	None.
Product code	BDS001132AE
Issue date	11-March-2022
Version number	1.0
Revision date	11-March-2022

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Anti Corrosion Products
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11 hse@crcind.com www.crcind.com
Company name	CRC Industries UK Ltd.
Address	Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h CET)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

##### Health hazards

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

**Environmental hazards**Hazardous to the aquatic environment,  
long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with  
long lasting effects.**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended**

**Contains:** 1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER, acetone; propan-2-one; propanone, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane, Propan-2-ol; Isopropyl alcohol; Isopropanol, rosin; colophony

**Hazard pictograms****Signal word**

Danger

**Hazard statements**

H222 Extremely flammable aerosol.  
 H229 Pressurized container: May burst if heated.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing mist/vapours.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves.

**Response**

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

**Storage**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information** EUH066 - Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****Mixture****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
acetone; propan-2-one; propanone	25 - 50	67-64-1 200-662-2	01-2119471330-49	606-001-00-8	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
Propan-2-ol; Isopropyl alcohol; Isopropanol	25 - 50	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER	10 - 25	107-98-2 203-539-1	01-2119457435-35	603-064-00-3	#
<b>Classification:</b> Flam. Liq. 3;H226, STOT SE 3;H336					
Carbon dioxide	5 - 10	124-38-9 204-696-9	-	-	#
<b>Classification:</b> Press. Gas;H280					

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	5 - 10	EC921-024-6 921-024-6	01-2119475514-35	-	
<b>Classification:</b> Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
rosin; colophony	5 - 10	8050-09-7 232-475-7	01-2119480418-32	650-015-00-7	#
<b>Classification:</b> Skin Sens. 1;H317					

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 4.1. Description of first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

**4.2. Most important symptoms and effects, both acute and delayed** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable aerosol.

### 5.1. Extinguishing media

**Suitable extinguishing media** Alcohol resistant foam. Powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Special fire fighting procedures** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**For emergency responders** Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

- 6.2. Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
- 6.3. Methods and material for containment and cleaning up** Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
- Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
- 6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

- 7.1. Precautions for safe handling** Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
- 7.2. Conditions for safe storage, including any incompatibilities** Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
- 7.3. Specific end use(s)** Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
1-METHOXY-2-PROPANOL ; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)	STEL	560 mg/m3	
		150 ppm	
	TWA	375 mg/m3 100 ppm	
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	3620 mg/m3	
		1500 ppm	
	TWA	1210 mg/m3 500 ppm	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3 5000 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3	
		500 ppm	
	TWA	999 mg/m3 400 ppm	
rosin; colophony (CAS 8050-09-7)	STEL	0.15 mg/m3	Fume.
	TWA	0.05 mg/m3	Fume.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)**

**General Population**

Components	Value	Assessment factor	Notes
<b>1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)</b>			
Long-term, Systemic, Dermal	78 mg/kg bw/day	16.8	Repeated dose toxicity
Long-term, Systemic, Inhalation	43.9 mg/m <sup>3</sup>		Repeated dose toxicity
Long-term, Systemic, Oral	33 mg/kg bw/day	28	Repeated dose toxicity
<b>acetone; propan-2-one; propanone (CAS 67-64-1)</b>			
Long-term, Systemic, Dermal	62 mg/kg bw/day	20	
Long-term, Systemic, Inhalation	200 mg/m <sup>3</sup>	5	
Long-term, Systemic, Oral	62 mg/kg bw/day	2	
<b>Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,&lt; 5% n-hexane (CAS EC921-024-6)</b>			
Long-term, Systemic, Dermal	699 mg/kg bw/day		
Long-term, Systemic, Inhalation	608 mg/m <sup>3</sup>		
Long-term, Systemic, Oral	699 mg/kg bw/day		
<b>Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)</b>			
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m <sup>3</sup>	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity
<b>rosin; colophony (CAS 8050-09-7)</b>			
Long-term, Systemic, Dermal	1.065 mg/kg bw/day	200	Repeated dose toxicity
Long-term, Systemic, Oral	1.065 mg/kg bw/day	200	Repeated dose toxicity

**Workers**

Components	Value	Assessment factor	Notes
<b>1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)</b>			
Long-term, Systemic, Dermal	183 mg/kg bw/day	10.08	Repeated dose toxicity
Long-term, Systemic, Inhalation	369 mg/m <sup>3</sup>		Repeated dose toxicity
Short-term, Local, Inhalation	553.5 mg/m <sup>3</sup>		Neurotoxicity
Short-term, Systemic, Inhalation	553.5 mg/m <sup>3</sup>		Neurotoxicity
<b>acetone; propan-2-one; propanone (CAS 67-64-1)</b>			
Long-term, Systemic, Dermal	186 mg/kg bw/day		
Long-term, Systemic, Inhalation	1210 mg/m <sup>3</sup>		
Short-term, Local, Inhalation	2420 mg/m <sup>3</sup>		
<b>Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,&lt; 5% n-hexane (CAS EC921-024-6)</b>			
Long-term, Systemic, Dermal	773 mg/kg bw/day		
Long-term, Systemic, Inhalation	2035 mg/m <sup>3</sup>		
<b>Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)</b>			
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m <sup>3</sup>	1	
<b>rosin; colophony (CAS 8050-09-7)</b>			
Long-term, Local, Inhalation	10 mg/m <sup>3</sup>		
Long-term, Systemic, Dermal	2.131 mg/kg bw/day	100	Repeated dose toxicity

**Predicted no effect concentrations (PNECs)**

Components	Value	Assessment factor	Notes
<b>1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)</b>			
Freshwater	10 mg/l	100	
Sediment (freshwater)	52.3 mg/kg		
Soil	4.59 mg/kg		
STP	100 mg/l	10	
<b>acetone; propan-2-one; propanone (CAS 67-64-1)</b>			
Freshwater	10.6 mg/l	50	
Marine water	1.06 mg/l	500	
Sediment (freshwater)	30.4 mg/kg		
Sediment (marine water)	3.04 mg/kg		
Soil	29.5 mg/kg		
STP	100 mg/l	10	
<b>Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)</b>			
Freshwater	140.9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		

Soil	28 mg/kg	
rosin; colophony (CAS 8050-09-7)		
Freshwater	0.002 mg/l	1000
Sediment (freshwater)	0.007 mg/kg	
STP	1000 mg/l	10

## 8.2. Exposure controls

**Appropriate engineering controls** Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

### Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

#### Skin protection

**- Hand protection** When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. For prolonged or repeated skin contact use suitable protective gloves. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

**- Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**Environmental exposure controls** Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state** Liquid.  
**Form** Aerosol.  
**Colour** Colourless to yellow.

**Odour** Solvent.

**Odour threshold** Not available.

**pH** Not applicable.

**Melting point/freezing point** -95 °C (-139 °F) estimated

**Initial boiling point and boiling range** Not available.

56 °C (132.8 °F) estimated

**Flash point** -20.0 °C (-4.0 °F) Closed cup

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not available.

#### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** 2.5 % estimated

**Flammability limit - upper (%)** 12.8 % estimated

**Vapour pressure** 57300 hPa estimated

**Vapour density** Not available.

**Relative density** 0.82 g/cm<sup>3</sup>

**Relative density temperature** 20 °C (68 °F)

<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble in water
<b>Auto-ignition temperature</b>	> 200 °C (> 392 °F)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

## 9.2. Other information

<b>Chemical family</b>	Resin
<b>Heat of combustion (NFPA 30B)</b>	15.77 kJ/g estimated
<b>VOC</b>	700 g/l

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid high temperatures.
<b>10.5. Incompatible materials</b>	Strong acids. Strong oxidising agents. Aluminium. Chlorine. Isocyanates.
<b>10.6. Hazardous decomposition products</b>	Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
-------------------	----------------	---------------------

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)

#### Acute

##### **Dermal**

LD50	Rabbit	13 g/kg
------	--------	---------

##### **Inhalation**

LC50	Rat	54.6 mg/l, 4 Hours
------	-----	--------------------

##### **Oral**

LD50	Rat	5.71 g/kg
------	-----	-----------

acetone; propan-2-one; propanone (CAS 67-64-1)

#### Acute

##### **Dermal**

LD50	Rat	15800 mg/kg
------	-----	-------------

##### **Inhalation**

LC50	Rat	50.1 mg/l, 8 Hours
------	-----	--------------------

##### **Oral**

LD50	Rat	5800 mg/kg
------	-----	------------

Components	Species	Test Results
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	2920 mg/kg bw/day, 24 h
<b>Inhalation</b>		
LC50	Rat	25200 mg/m <sup>3</sup> , 4 h
<b>Oral</b>		
LD50	Rat	5840 mg/kg bw/day
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 25000 mg/m <sup>3</sup> , 6 h
rosin; colophony (CAS 8050-09-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitisation</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.	
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.	
<b>Aspiration hazard</b>	Not likely, due to the form of the product.	
<b>Mixture versus substance information</b>	Not available.	

## SECTION 12: Ecological information

**12.1. Toxicity** Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae > 1000 mg/l, 72 h
Crustacea	EC50	Daphnia > 1000 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss > 1000 mg/l, 96 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC50	Algae > 30 - < 100 mg/l, 72 h
Crustacea	EC50	Daphnia 3 mg/l, 48 h
Fish	LC50	Fish 11.4 mg/l, 96 h
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	LC50	Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours



<b>12.2. Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.
<b>12.3. Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol/water (log Kow)</b>	
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL	-0.49
METHYL ETHER	
acetone; propan-2-one; propanone	-0.24
Propan-2-ol; Isopropyl alcohol; Isopropanol	0.05
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
<b>12.6. Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential. GWP: 0

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Hazard No. (ADR)</b>	Not available.
<b>Tunnel restriction code</b>	D
<b>14.4. Packing group</b>	Not applicable
<b>14.5. Environmental hazards</b>	No
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### RID

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>14.4. Packing group</b>	Not available.
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

### ADN

<b>14.1. UN number</b>	UN1950
<b>14.2. UN proper shipping name</b>	AEROSOLS, flammable

#### 14.3. Transport hazard class(es)

Class 2.1  
Subsidiary risk -  
Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IATA

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

#### 14.3. Transport hazard class(es)

Class 2.1  
Subsidiary risk -

14.4. Packing group Not applicable

14.5. Environmental hazards No

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

#### 14.3. Transport hazard class(es)

Class 2.1  
Subsidiary risk -

14.4. Packing group Not applicable

#### 14.5. Environmental hazards

Marine pollutant No

EmS F-D, S-U

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

ADN; ADR; IATA; IMDG; RID



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended  
Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended  
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended  
Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

acetone; propan-2-one; propanone (CAS 67-64-1)  
Carbon dioxide (CAS 124-38-9)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

acetone; propan-2-one; propanone (CAS 67-64-1)  
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)  
rosin; colophony (CAS 8050-09-7)

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL ETHER (CAS 107-98-2)  
acetone; propan-2-one; propanone (CAS 67-64-1)  
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.  
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).  
CAS: Chemical Abstract Service.  
Ceiling: Short Term Exposure Limit Ceiling value.  
CEN: European Committee for Standardization.  
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.  
GWP: Global Warming Potential.  
IATA: International Air Transport Association.  
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.  
IMDG: International Maritime Dangerous Goods.  
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
PBT: Persistent, bioaccumulative and toxic.  
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
STEL: Short term exposure limit.  
TLV: Threshold Limit Value.  
TWA: Time Weighted Average.  
VOC: Volatile organic compounds.  
vPvB: Very persistent and very bioaccumulative.  
STEL: Short-term Exposure Limit.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
None.

**Revision information**

**Training information**

**Disclaimer**

Follow training instructions when handling this material.

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.